



W66 N220 Commerce Court • Cedarburg, WI 53012

Phone: 262.375.4400 • Fax: 262.375.4248

www.lsr.com


TEST REPORT # 316053 A
LSR Job #: C-2395

Compliance Testing of:
Sterling LWB

Test Date(s):
May 6th to June 10th 2016


Prepared For:
Attention: Josh Bablitch
LSR
W66N220 Commerce Ct.
Cedarburg, WI 53012

This Test Report is issued under the Authority of:
Khairul Aidi Zainal, Engineering Manager-Test Services.

Signature: 

Date: 7/19/16

Test Report Reviewed by:
Michael Hintzke, EMC Engineer III

Signature: 

Date: 7/19/16

Project Engineer:
Khairul Aidi Zainal, Engineering Manager-
Test Services.

Signature: 

Date: 7/18/16

This Test Report may not be reproduced, except in full, without written approval of LS Research, LLC.

TABLE OF CONTENTS

EXHIBIT 1. INTRODUCTION.....	3
1.1 - Scope.....	3
1.2 - LS Research, LLC Test Facility	4
1.3 – Location of Testing	5
1.4 – Test Equipment Utilized.....	5
EXHIBIT 2. PERFORMANCE ASSESSMENT	6
2.1 – Client Information	6
2.2 - Equipment Under Test (EUT) Information	6
2.3 - EUT'S Technical Specifications.....	7
2.4 - Product Description	8
2.5 – Test Configuration	9
EXHIBIT 3. EUT OPERATING CONDITIONS & CONFIGURATIONS DURING TESTS	11
3.1 - Climate Test Conditions	11
3.2 - Summary Of Test Results	11
3.3 - Modifications Incorporated In The EUT For Compliance Purposes.....	11
3.4 - Deviations & Exclusions From Test Specifications	11
EXHIBIT 4. DECLARATION OF CONFORMITY	12
EXHIBIT 5: Frequency Allocation.....	13
EXHIBIT 6: Frequency Tolerance.....	14
EXHIBIT 7. Antenna Power and EIRP Power Density	15
EXHIBIT 8. Absolute Antenna Gain.....	25
EXHIBIT 9. Occupied Bandwidth and Spreading Bandwidth	42
EXHIBIT 10. Transmitter Spurious Emissions	49
EXHIBIT 11. Secondary Emissions	54
EXHIBIT 12. Dwell Time	59
EXHIBIT 13. Spreading Factor	60
EXHIBIT 14. Antenna Power Tolerance	62
EXHIBIT 15. Amount of carrier in 1 MHz.....	63
EXHIBIT 16. “Not Easily To Open”	65
EXHIBIT 17. Voltage fluctuation.....	66
EXHIBIT 18. Interference Prevention Function.....	67
APPENDIX A – Test Equipment List.....	68
APPENDIX B - Uncertainty Statement.....	69

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 2 of 69

EXHIBIT 1. INTRODUCTION

1.1 - Scope

Normative References:	Article 2 Paragraph 1 of the Certification Ordinance ARIB STD-T66 V2.1 "Second Generation Low Power data Communication System/Wireless LAN System" ARIB STD-T33 1 "Low Power data Communication System/Wireless LAN System" Ordinance Regulating radio Equipment
Purpose of Test:	To test for compliance against the requirements of the Japanese Radio Law for products operating under category WW and Article 2 item (19)
Test procedures:	Radio Law (Law No. 131) Ministerial Ordinance No. 37 (Rules Concerning Technical Regulations Conformity Certification of Specified Radio Equipment) Ordinance Regulating Radio Equipment MIC notice 88 (test methods and appendix to Post of the Ministerial Ordinance N0.37)

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 3 of 69

1.2 - LS Research, LLC Test Facility

LS Research, LLC is accredited by A2LA (American Association for Laboratory Accreditation) as conforming to ISO/IEC 17025, 2005 "General Requirements for the Competence of Calibration and Testing Laboratories".

As an EMC Testing Laboratory, our Accreditation and Assessments are recognized through the following:



A2LA – American Association for Laboratory Accreditation

*Accreditation based on ISO/IEC 17025: 2005 with Electrical (EMC) Scope of Accreditation
A2LA Certificate Number: 1255.01*



Federal Communications Commission (FCC) – USA

*Listing of 3 Meter Semi-Anechoic Chamber based on Title 47 CFR – Part 2.948
FCC Registration Number: 90750*



Industry Canada

*On file, 3 Meter Semi-Anechoic Chamber based on RSS-GEN – Issue 4
File Number: IC 3088A-2
On file, 3 Meter Semi-Anechoic Chamber based on RSS-GEN – Issue 4
File Number: IC 3088A-3*

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 4 of 69

1.3 – Location of Testing

All testing was performed at the following location utilizing the facilities listed below, unless otherwise noted.

LS Research, LLC
W66 N220 Commerce Court
Cedarburg, Wisconsin, 53012 USA,

List of Facilities Located at LS Research, LLC:

Semi-Anechoic Chamber

1.4 – Test Equipment Utilized

A complete list of equipment utilized in testing is provided in Appendix A of this test report. Calibration dates are indicated in Appendix A. All test equipment is calibrated by a calibration laboratory accredited to the requirements of ISO/IEC 17025, and traceable to SI standards.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 5 of 69

EXHIBIT 2. PERFORMANCE ASSESSMENT

2.1 – Client Information

Manufacturer Name:	LSR
Address:	W66N220 Commerce Ct. Cedarburg. WI 53012
Contact Name:	Josh Bablitch
E-mail address:	Josh.bablitch@lairdtech.com

2.2 - Equipment Under Test (EUT) Information

The following information has been supplied by the applicant.

Product Name:	Sterling-LWB
Model Number:	STERLING-LWB
Serial Number:	49

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 6 of 69

2.3 - EUT'S Technical Specifications

EUT Frequency Range (in MHz)	2412 MHz to 2472MHz
Antenna Power	<input checked="" type="checkbox"/> Conducted Measurement <input type="checkbox"/> Radiated Measurement
Minimum (mW/MHz):	802.11b = 4.710 802.11g = 1.648 802.11n (20MHz) = 1.230
Maximum (mW/MHz):	802.11b = 6.397 802.11g = 2.307 802.11n (20MHz) = 1.652
Maximum Occupied Bandwidth and Spreading Bandwidth (99% and 90%)	90% (MHz): 802.11b = 9.641 802.11g = 13.8 802.11n (20MHz) = 14.6 99%(MHz): 802.11b = 13.900 802.11g = 16.900 802.11n (20MHz) = 17.900
Type of Modulation	OFDM (802.11n,g), DSSS (802.11b)
Frequency Tolerance %, Hz, ppm	Better than 50 ppm
Antenna Information	
Detachable/non-detachable	Non-detachable and detachable
Type	Chip, Dipole, FlexNotch, FlexPIFA
Gain and Pattern	Peak Gain (dBi): Chip = 1.5 Dipole = 2.0 FlexNotch = 2.0 FlexPIFA = 2.0 Pattern : Omni-directional

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 7 of 69

2.4 - Product Description

The Sterling-LWB is a multi-standard module with support for WLAN (802.11 b/g/n), and Bluetooth V2.1 and Bluetooth 4.0 & 4.1 with multiple antenna options.

This device has been designed to operate with the antenna listed below, and having a maximum gain of 2.0 dBi. The required antenna impedance is 50 ohms.

Chip Antenna: Johanson Part # 2450AT18D0100 Peak Gain 1.5 dBi

U.FL Antenna port utilizes the following antenna options:

LSR 2.4 GHz Dipole Antenna 2dBi

LSR 2.4 GHz FlexPIFA 2dBi


LSR 2.4 GHz FlexNotch 2dBi

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 8 of 69

2.5 – Test Configuration

The EUT was powered using a switching mode power supply. The power supply was set to the nominal (+3.3 VDC) voltage and $\pm 10\%$ of the nominal voltage for testing (+3.6 VDC and + 3.0 VDC).

The EUT was connected to a laptop running the TiWi-CW RF Eval tool, Version 2.0.0.0 proprietary software. The EUT was connected to this laptop via a USB A to USB mini cable.



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 9 of 69

Test Setup photos:

Conducted Measurement Setup



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 10 of 69

EXHIBIT 3. EUT OPERATING CONDITIONS & CONFIGURATIONS DURING TESTS

3.1 - Climate Test Conditions

Temperature:	70-71° F
Humidity:	32-35%
Pressure:	729-742mmHg

3.2 - Summary Of Test Results

Ordinance Number	Description	Compliance (Yes/No)
Article 49.20	Frequency Allocation	Yes
Article 5, Annex 1	Frequency Tolerance	Yes
Article 49.20	Antenna Power	Yes
Article 14	Output Power Tolerance	Yes
Article 49.20	Spreading Bandwidth	Yes
Article 6, Annex 2 30	Occupied Bandwidth	Yes
Article 49.20	E.I.R.P	Yes
Article 49.20	Antenna Absolute gain	Yes
Article 49.20	Spreading Factor	Yes
Article 7, Annex 3	Transmitter Spurious emissions	Yes
Article 24	Secondary/receiver emissions	Yes
Article 49.20	Dwell Time	N/A
Article 49.20	Housing Requirement	Yes
Article 9.4.9	Interference Prevention function	Yes
Article 15.1	Voltage fluctuation	Yes
Article 49.20	OFDM Sub-carriers	Yes

3.3 - Modifications Incorporated In The EUT For Compliance Purposes

☒ None ☐ Yes (explain below)

3.4 - Deviations & Exclusions From Test Specifications

☒ None ☐ Yes (explain below)

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 11 of 69

EXHIBIT 4. DECLARATION OF CONFORMITY

The EUT was found to MEET the requirements for a Direct Sequence Spread Spectrum and OFDM Transmitter device under Article 2 Paragraph 1 of the Certification Ordinance.

LS Research, LLC certifies that the data contained herein was taken under conditions that meet or exceed the requirements of the test specifications. The results in this Test Report apply only to the item(s) tested on the above-specified dates. Any modifications made to the EUT subsequent to the indicated test date(s) will invalidate the data herein, and void this certification.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 12 of 69

EXHIBIT 5: Frequency Allocation.

Test Engineer:	Khairul Aidi Zainal
Test Date:	5/6/2016

Requirement:

The requirement per Article 49.20 of the Ordinance Regulating Radio equipment authorizes equipment within the range 2400 MHz to 2483.5MHz

Result:

The EUT was found to operate between:

1. 2412 MHz to 2472MHz for WLAN mode.

The EUT Complies with the requirements of the Ordinance regulating Radio Equipment.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 13 of 69

EXHIBIT 6: Frequency Tolerance.

Test Engineer:	Coty Hammerer
Test Date:	4/7/2016

Requirement:

Article 5, Annex 1 tables 7-8 of the Ordinance regulating Radio Equipment has a limit of ± 50 ppm.

Test note:

1. EUT was set to single channel transmission (low, medium and high).
2. EUT was set to continuously transmitting un-modulated.
3. Frequency counter function of the Spectrum analyzer was used to measure the frequency.
4. Measurement performed at nominal, +10% nominal and -10% nominal supply voltage.

Result:

The EUT had a maximum deviation of 1396Hz which is better than 50ppm. The EUT complies with the requirement of the Ordinance regulating Radio Equipment.

Data:

1. WLAN mode:

	3.0 VDC	3.3 VDC	3.6 VDC	
Channel	Frequency (Hz)	Frequency (Hz)	Frequency (Hz)	Frequency Drift (Hz)
2412	2412006465	2412007301	2412005905	1396
2437	2437006708	2437006097	2437006082	626
2462	2462007066	2462006529	2462007160	631

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 14 of 69

EXHIBIT 7. Antenna Power and EIRP Power Density

Test Engineer:	Khairul Aidi Zainal
Test Date:	5/26/16 – 6/8/16

Requirement:

Article 49.20 of the Ordinance regulating Radio Equipment allows an absolute maximum (including +20% tolerance) antenna power of 10mW/MHz for a DSSS, OFDM (26MHz occupied bandwidth) system that occupies the frequency range 2400 to 2483.5 MHz. It also allows for a maximum EIRP power density of 12.14 dBm/MHz for non-directional antennas and 22.14 dBm/MHz for directional antennas.

Test note:

1. The EUT was tested at the lowest, middle and high channels.
2. Measurement performed at nominal, +10% nominal and -10% nominal supply voltage.
3. Antenna gain used in EIRP density calculation is 2.0dBi (from data sheet)
4. Measurement procedure:
 - a. Step 1:
 - i. Spectrum analyzer Center frequency: Center of the channel or band
 - ii. Resolution BW = 1 MHz
 - iii. Video BW = 3 MHz
 - iv. Detector = Average (RMS)
 - v. Sweep time = 60s
 - vi. Trace mode = Max Hold
 - b. Step 2: Find the peak value of the envelope and record as the highest antenna power.

Result:

The WLAN (802.11b, 802.11g and 802.11n) mode of the EUT has a maximum antenna power and maximum EIRP power which are below the stated limits and is therefore found to be compliant to the requirement of the Ordinance regulating Radio Equipment.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 15 of 69

Data:

A. WLAN

a. 802.11b

i. 1 MBPS

Low channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	7.7	5.916	9.2	1.5	2.0	9.7	9.376	11.4	1.6
2.97VDC (-10%)	7.8	6.026	9.2	1.4	2.0	9.8	9.550	11.4	1.6
3.6VDC (Max declared)	8.1	6.397	9.2	1.1	2.0	10.1	10.139	11.4	1.3

Middle Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	7.9	6.124	9.2	1.3	2.0	9.9	9.705	11.4	1.5
2.97VDC (-10%)	7.8	5.984	9.2	1.4	2.0	9.8	9.484	11.4	1.6
3.6VDC (Max declared)	7.5	5.585	9.2	1.7	2.0	9.5	8.851	11.4	1.9

High Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	7.2	5.248	9.2	2.0	2.0	9.2	8.318	11.4	2.2
2.97VDC (-10%)	7.8	5.984	9.2	1.4	2.0	9.8	9.484	11.4	1.6
3.6VDC (Max declared)	7.2	5.284	9.2	2.0	2.0	9.2	8.375	11.4	2.1

Note:

1. The limits listed in the tables take into account the upper end of the output power tolerance (+20%) hence is shown to be lower than the 10mW/MHz or 10dBm/MHz.3/

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 16 of 69

ii. 11 MBPS

Low channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	7.1	5.129	9.2	2.1	2.0	9.1	8.128	11.4	2.3
2.97VDC (-10%)	7.3	5.383	9.2	1.9	2.0	9.3	8.531	11.4	2.0
3.6VDC (Max declared)	7.1	5.117	9.2	2.1	2.0	9.1	8.110	11.4	2.3

Middle Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	7.0	4.966	9.2	2.3	2.0	9.0	7.870	11.4	2.4
2.97VDC (-10%)	7.1	5.164	9.2	2.1	2.0	9.1	8.185	11.4	2.2
3.6VDC (Max declared)	7.0	5.012	9.2	2.2	2.0	9.0	7.943	11.4	2.4

High Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	6.7	4.710	9.2	2.5	2.0	8.7	7.464	11.4	2.6
2.97VDC (-10%)	6.9	4.932	9.2	2.3	2.0	8.9	7.816	11.4	2.4
3.6VDC (Max declared)	6.8	4.786	9.2	2.4	2.0	8.8	7.586	11.4	2.6

Note:

- The limits listed in the tables take into account the upper end of the output power tolerance (+20%) hence is shown to be lower than the 10mW/MHz or 10dBm/MHz.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 17 of 69

b. 802.11g
i. 6 MBPS

Low channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	3.5	2.218	9.2	5.8	2.0	5.5	3.516	11.4	5.9
2.97VDC (-10%)	3.6	2.307	9.2	5.6	2.0	5.6	3.656	11.4	5.7
3.6VDC (Max declared)	3.5	2.259	9.2	5.7	2.0	5.5	3.581	11.4	5.8

Middle Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	3.4	2.163	9.2	5.9	2.0	5.4	3.428	11.4	6.0
2.97VDC (-10%)	3.5	2.223	9.2	5.7	2.0	5.5	3.524	11.4	5.9
3.6VDC (Max declared)	3.4	2.193	9.2	5.8	2.0	5.4	3.475	11.4	5.9

High Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	2.9	1.968	9.2	6.3	2.0	4.9	3.119	11.4	6.4
2.97VDC (-10%)	3.3	2.143	9.2	5.9	2.0	5.3	3.396	11.4	6.0
3.6VDC (Max declared)	3.0	2.004	9.2	6.2	2.0	5.0	3.177	11.4	6.3

Note:

- The limits listed in the tables take into account the upper end of the output power tolerance (+20%) hence is shown to be lower than the 10mW/MHz or 10dBm/MHz.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 18 of 69

ii. 54 MBPS

Low channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	2.4	1.718	9.2	6.9	2.0	4.4	2.723	11.4	7.0
2.97VDC (-10%)	2.6	1.807	9.2	6.6	2.0	4.6	2.864	11.4	6.8
3.6VDC (Max declared)	2.4	1.754	9.2	6.8	2.0	4.4	2.780	11.4	6.9

Middle Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	2.4	1.730	9.2	6.8	2.0	4.4	2.742	11.4	7.0
2.97VDC (-10%)	2.5	1.758	9.2	6.8	2.0	4.5	2.786	11.4	6.9
3.6VDC (Max declared)	2.3	1.694	9.2	6.9	2.0	4.3	2.685	11.4	7.1

High Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	2.2	1.648	9.2	7.0	2.0	4.2	2.612	11.4	7.2
2.97VDC (-10%)	2.3	1.690	9.2	6.9	2.0	4.3	2.679	11.4	7.1
3.6VDC (Max declared)	2.2	1.671	9.2	7.0	2.0	4.2	2.649	11.4	7.1

Note:

1. The limits listed in the tables take into account the upper end of the output power tolerance (+20%) hence is shown to be lower than the 10mW/MHz or 10dBm/MHz.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 19 of 69

c. 802.11n (HT20)

i. MCS0

Low channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	2.0	1.596	9.2	7.2	2.0	4.0	2.529	11.4	7.3
2.97VDC (-10%)	2.0	1.578	9.2	7.2	2.0	4.0	2.500	11.4	7.4
3.6VDC (Max declared)	2.1	1.603	9.2	7.2	2.0	4.1	2.541	11.4	7.3

Middle Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	2.2	1.641	9.2	7.1	2.0	4.2	2.600	11.4	7.2
2.97VDC (-10%)	2.1	1.626	9.2	7.1	2.0	4.1	2.576	11.4	7.2
3.6VDC (Max declared)	2.2	1.652	9.2	7.0	2.0	4.2	2.618	11.4	7.2

High Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	1.9	1.545	9.2	7.3	2.0	3.9	2.449	11.4	7.5
2.97VDC (-10%)	1.9	1.545	9.2	7.3	2.0	3.9	2.449	11.4	7.5
3.6VDC (Max declared)	1.9	1.563	9.2	7.3	2.0	3.9	2.477	11.4	7.4

Note:

- The limits listed in the tables take into account the upper end of the output power tolerance (+20%) hence is shown to be lower than the 10mW/MHz or 10dBm/MHz.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 20 of 69

ii. MCS7

Low channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	0.7	1.186	9.2	8.5	2.0	2.7	1.879	11.4	8.6
2.97VDC (-10%)	0.8	1.213	9.2	8.4	2.0	2.8	1.923	11.4	8.5
3.6VDC (Max declared)	0.8	1.189	9.2	8.5	2.0	2.8	1.884	11.4	8.6

Middle Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	0.9	1.230	9.2	8.3	2.0	2.9	1.950	11.4	8.5
2.97VDC (-10%)	1.0	1.256	9.2	8.2	2.0	3.0	1.991	11.4	8.4
3.6VDC (Max declared)	1.0	1.245	9.2	8.3	2.0	3.0	1.972	11.4	8.4

High Channel									
EUT supply voltage (V)	RMS power (dBm/MHz)	RMS power (mW/MHz)	RMS power limit (dBm/MHz)	RMS power margin (dB)	Antenna Gain (dBi)	EIRP (dBm/MHz)	EIRP (mW/MHz)	EIRP limit (dBm/MHz)	EIRP margin (dB)
3.3VDC (Nominal)	1.0	1.247	9.2	8.3	2.0	3.0	1.977	11.4	8.4
2.97VDC (-10%)	1.0	1.259	9.2	8.2	2.0	3.0	1.995	11.4	8.4
3.6VDC (Max declared)	0.9	1.239	9.2	8.3	2.0	2.9	1.963	11.4	8.4

Note:

- The limits listed in the tables take into account the upper end of the output power tolerance (+20%) hence is shown to be lower than the 10mW/MHz or 10dBm/MHz.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 21 of 69


Captures:

Captures shown are those at nominal voltage


A. WLAN

1. 802.11b:

1 MBPS




11 MBPS




Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 22 of 69

2. 802.11g:

6 MBPS




54 MBPS




Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 23 of 69

3. 802.11n (HT20):

MCS0



MCS7



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 24 of 69

EXHIBIT 8. Absolute Antenna Gain

Test Engineer:	N/A
Test Date:	N/A

Requirement:

The absolute maximum antenna gain allowed by Article 49.20 of the Ordinance regulating Radio Equipment is 12.14 dBi.

Result:

This device has been designed to operate with the antenna listed below, and having a maximum gain of 2.0 dBi. The required antenna impedance is 50 ohms.

Chip Antenna: Johanson Part # 2450AT18D0100 Peak Gain 1.5 dBi

U.FL Antenna port utilizes the following antenna options:

LSR 2.4 GHz Dipole Antenna 2dBi

LSR 2.4 GHz FlexPIFA 2dBi

LSR 2.4 GHz FlexNotch 2dBi

The peak gain value is below the stated limit and is therefore compliant to the requirement of the Ordinance regulating Radio Equipment.

Data:

The information provided was taken from the antenna manufacturer's data sheet.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 25 of 69

Chip Antenna:

"High Frequency Ceramic Solutions"

2.45 GHz SMD Antenna, EIA 1210, Detuning resilient, Edge Mount Design

P/N 2450AT18D0100

Detail Specification: 9/17/2015

Page 1 of 6

This antenna is optimal for edge middle mounting; rectangular and circular PCB shape applications, go to pages 2-4 for more info.

General Specifications

Part Number	2450AT18D0100	Input/Output Power	2W max. (CW)
Frequency (MHz)	2400 - 2500	Impedance	50 Ω
Peak Gain	1.5 dBi typ. (XZ-total)	Reel Quantity	3,000
Average Gain	-1.0 dBi typ. (XZ-total)	Storage Temp	-40 to +85°C
Return Loss	10.0 dB min.	Total Radiation Efficiency ¹	72%
Operating Temperature	-40 to +125°C	¹ Efficiency measured on 2450AT18D0100-EB18MA 40x20mm EVB on page 2	

"High Frequency Ceramic Solutions"

2.45 GHz SMD Antenna, EIA 1210, Detuning resilient, Edge Mount Design


P/N 2450AT18D0100

Detail Specification: 04/04/12

Page 3 of 5

This antenna is optimal for edge middle mounting; rectangular and circular PCB shape applications, go to pages 2-4 for more info.

Typical Return Loss (S11) Electrical Performance (T=25°C)



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 26 of 69

"High Frequency Ceramic Solutions"

2.45 GHz SMD Antenna, EIA 1210, Detuning resilient, Edge Mount Design

P/N 2450AT18D0100


Detail Specification: 9/17/2015

Page 4 of 5



This antenna is optimal for edge middle mounting; rectangular and circular PCB shape applications, go to pages 2-4 for more info.

Typical EM Radiation Performance (T=25°C)



Typical Radiation Patterns




XY cut @2.45GHz
— Vertical
..... Horizontal



XZ cut @2.45GHz
— Vertical
..... Horizontal



YZ cut @2.45GHz
— Vertical
..... Horizontal



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 27 of 69

Dipole Antenna:



ModFLEX Accessories – 2.4 GHz Dipole Antenna DATASHEET

2.4 GHz – 2.5 GHz Dipole 2dBi Antenna for Reverse Polarity SMA



ORDERING INFORMATION

Order Number	Description
001-0001	2.4 GHz dipole antenna for reverse polarity SMA connector.


SPECIFICATIONS

Specification	Value
Gain	+2 dBi
Impedance	50 ohms, Nominal
Type	Dipole
Polarization	Linear Vertical
VSWR	$\leq 2.5 : 1$, Maximum
Frequency	2400-2500MHz
Weight	13g
Size	105×10 mm
Antenna Color	Black

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 28 of 69


TYPICAL ANTENNA RADIATION PERFORMANCE

LSR ANTENNA STRAIGHT 2405 MHz



— Vertical Polarization Gain (dBi)
--- Horizontal Polarization Gain (dBi)


LSR ANTENNA STRAIGHT 2440 MHz



— Vertical Polarization Gain (dBi)
--- Horizontal Polarization Gain (dBi)


Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 29 of 69

LSR ANTENNA STRAIGHT 2480 MHz



— Vertical Polarization Gain (dBi)
--- Horizontal Polarization Gain (dBi)


LSR ANTENNA BENT 2405 MHz



— Vertical Polarization Gain (dBi)
--- Horizontal Polarization Gain (dBi)


Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 30 of 69

LSR ANTENNA BENT 2440 MHz



— Vertical Polarization Gain (dBi)
--- Horizontal Polarization Gain (dBi)

LSR ANTENNA BENT 2480 MHz



— Vertical Polarization Gain (dBi)
--- Horizontal Polarization Gain (dBi)

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 31 of 69

FlexNotch Antenna:



2.4 GHz FlexNotch Antenna, 100mm Datasheet

2.4 GHz – 2.5 GHz FlexNotch 2 dBi Antenna w/U.FL Cable, 100mm



ORDERING INFORMATION

Order Number	Description
001-0015	2.4 GHz FlexNotch Antenna w/U.FL Cable, 100mm
001-0023	2.4GHz FlexNotch Antenna w/ MHF4L Cable, 100mm

Table 1 Orderable Part Numbers

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 32 of 69


SPECIFICATIONS

Specification	Value
Peak Gain	+2 dBi
Average Gain	>-1.6 dBi
Impedance	50 ohms
Type	Flexible Notch
Polarization	Linear
VSWR	< 2.5:1, 2400 - 2480 MHz
Frequency	2400 – 2480 MHz
Weight	0.85g
Size	32.0mm × 21.08mm
Antenna Color	Clear Yellow
Adhesive	3M 100MP
Operating Temp	-40°C to +85°C

Table 2 Specifications

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 33 of 69

Horizontal Orientation at 2440 MHz:



____ Vertical Polarization Gain (dBi) min: -7.8 max: -3.9 avg: -5.6
 ---- Horizontal Polarization Gain (dBi) min: -32.3 max: -13.2 avg: -18.1

Figure 4 Horizontal Orientation Pattern

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 34 of 69

Vertical Orientation at 2440 MHz:




Figure 6 Vertical Orientation Pattern

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 35 of 69

Flat Orientation at 2440 MHz:




Figure 8 Flat Orientation Pattern

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 36 of 69

FlexPIFA antenna:



2.4 GHz FlexPIFA Antenna, 100mm Datasheet

2.4 GHz – 2.5 GHz FlexPIFA 2 dBi Antenna w/U.FL Cable, 100mm



ORDERING INFORMATION

Order Number	Description
001-0014	2.4 GHz FlexPIFA Antenna w/U.FL Cable, 100mm
001-0022	2.4GHz FlexPIFA Antenna w/MHF4L Cable, 100mm

Table 1 Orderable Part Numbers

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 37 of 69


SPECIFICATIONS

Specification	Value
Peak Gain	+2 dBi
Average Gain	>-2.3 dBi
Impedance	50 ohms
Type	Flexible Planar Inverted F Antenna (FlexPIFA)
Polarization	Linear
VSWR	< 2.0:1, 2400 - 2480 MHz
Frequency	2400 – 2480 MHz
Weight	1.13g
Size	40.1mm × 11mm × 2.5mm
Antenna Color	Clear Yellow
Adhesive	3M 100MP
Operating Temp	-40°C to +85°C

Table 2 Specifications

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 38 of 69

Vertical Orientation at 2440 MHz:



____ Total Gain (dBi) min: -8.0 max: +2.0 avg: -0.7

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 39 of 69

Horizontal Orientation at 2440 MHz:





Figure 6 Horizontal Orientation Pattern

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 40 of 69

Flat Orientation at 2440 MHz:



____ Total Gain (dBi) min: -6.2 max: -1.1 avg: -3.0

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 41 of 69

EXHIBIT 9. Occupied Bandwidth and Spreading Bandwidth

Test Engineer:	Khairul Aidi Zainal
Test Date:	5/6/16 – 5/25/16

Requirement:

Article 49.20 of the Ordinance regulating Radio Equipment requires that the minimum spreading bandwidth for DSSS system, which is the 90% bandwidth, be a minimum of 500 kHz.

Article 6, Annex 2 of the Ordinance regulating Radio Equipment requires that the occupied bandwidth, which is defined as the 99% bandwidth, be:

1. 26 MHz for DSSS systems
2. 26 MHz – 38 MHz for OFDM systems

Test note:

1. The EUT was tested at the lowest, middle and high channels.
2. Measurement performed at nominal, +10% nominal and -10% nominal supply voltage.
3. The Occupied Bandwidth measurement function of the Spectrum analyzer was used to perform the measurements.

Result:

The occupied bandwidth value is below the stated limit and is therefore compliant to the requirement of the Ordinance regulating Radio Equipment.

The spreading bandwidth value is above the stated limit and is therefore compliant to the requirement of the Ordinance regulating Radio Equipment.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 42 of 69

Data:

A. 802.11b

1MBPS																		
EUT supply voltage (V)	Low Channel (2412MHz)						Middle channel (2442MHz)						High Channel (2472MHz)					
	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)
3.3VDC (Nominal)	13.9	26.0	12.1	9219.0	500.0	8719.0	13.9	26.0	12.1	9240.3	500.0	8740.3	13.9	26.0	12.1	9256.1	500.0	8756.1
2.97VDC (-10%)	13.9	26.0	12.1	9219.0	500.0	8719.0	13.9	26.0	12.1	9240.3	500.0	8740.3	13.9	26.0	12.1	9256.1	500.0	8756.1
3.6VDC (Max declared)	13.9	26.0	12.1	9219.0	500.0	8719.0	13.9	26.0	12.1	9240.3	500.0	8740.3	13.9	26.0	12.1	9256.1	500.0	8756.1

	5.5MBPS																	
	Low Channel						Middle channel						High Channel					
EUT supply voltage (V)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)
3.3VDC (Nominal)	13.9	26.0	12.1	9641.5	500.0	9141.5	13.9	26.0	12.1	9638.0	500.0	9138.0	13.9	26.0	12.1	9601.7	500.0	9101.7
2.97VDC (-10%)	13.9	26.0	12.1	9641.5	500.0	9141.5	13.9	26.0	12.1	9638.0	500.0	9138.0	13.9	26.0	12.1	9601.7	500.0	9101.7
3.6VDC (Max declared)	13.9	26.0	12.1	9641.5	500.0	9141.5	13.9	26.0	12.1	9638.0	500.0	9138.0	13.9	26.0	12.1	9601.7	500.0	9101.7

	11MBPS																	
	Low Channel						Middle channel						High Channel					
EUT supply voltage (V)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (kHz)	Limit (kHz)- minimum	Margin (kHz)
3.3VDC (Nominal)	13.8	26.0	12.2	9557.3	500.0	9057.3	13.8	26.0	12.2	9557.8	500.0	9057.8	13.8	26.0	12.2	9543.1	500.0	9043.1
2.97VDC (-10%)	13.8	26.0	12.2	9557.3	500.0	9057.3	13.8	26.0	12.2	9557.8	500.0	9057.8	13.8	26.0	12.2	9543.1	500.0	9043.1
3.6VDC (Max declared)	13.8	26.0	12.2	9557.3	500.0	9057.3	13.8	26.0	12.2	9557.8	500.0	9057.8	13.8	26.0	12.2	9543.1	500.0	9043.1

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 43 of 69

B. 802.11g

	6 MBPS																	
	Low Channel						Middle channel						High Channel					
EUT supply voltage (V)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)
3.3VDC (Nominal)	16.8	26.0	9.2	13.7	N/A	N/A	16.9	26.0	9.2	13.7	N/A	N/A	16.76	26.0	9.2	13.7	N/A	N/A
2.97VDC (-10%)	16.8	26.0	9.2	13.7	N/A	N/A	16.9	26.0	9.2	13.7	N/A	N/A	16.76	26.0	9.2	13.7	N/A	N/A
3.6VDC (Max declared)	16.8	26.0	9.2	13.7	N/A	N/A	16.9	26.0	9.2	13.7	N/A	N/A	16.76	26.0	9.2	13.7	N/A	N/A

	54 MBPS																	
	Low Channel						Middle channel						High Channel					
EUT supply voltage (V)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)
3.3VDC (Nominal)	16.6	26.0	9.4	13.8	N/A	N/A	16.6	26.0	9.4	13.8	N/A	N/A	16.6	26.0	9.4	13.7	N/A	N/A
2.97VDC (-10%)	16.6	26.0	9.4	13.8	N/A	N/A	16.6	26.0	9.4	13.8	N/A	N/A	16.6	26.0	9.4	13.7	N/A	N/A
3.6VDC (Max declared)	16.6	26.0	9.4	13.8	N/A	N/A	16.6	26.0	9.4	13.8	N/A	N/A	16.6	26.0	9.4	13.7	N/A	N/A

C. 802.11n

MCS 0																		
EUT supply voltage (V)	Low Channel						Middle channel						High Channel					
	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)
3.3VDC (Nominal)	17.9	26.0	8.1	14.5	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A
2.97VDC (-10%)	17.9	26.0	8.1	14.5	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A
3.6VDC (Max declared)	17.9	26.0	8.1	14.5	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A

	MCS7																	
	Low Channel						Middle channel						High Channel					
EUT supply voltage (V)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)	Occupied Bandwidth / 99% BW (MHz)	Limit (MHz)	Margin (MHz)	Spreading Bandwidth/ 90% BW (MHz)	Limit (kHz)-minimum	Margin (kHz)
3.3VDC (Nominal)	17.8	26.0	8.2	14.6	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A	17.8	26.0	8.2	14.5	N/A	N/A
2.97VDC (-10%)	17.8	26.0	8.2	14.6	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A	17.8	26.0	8.2	14.5	N/A	N/A
3.6VDC (Max declared)	17.8	26.0	8.2	14.6	N/A	N/A	17.7	26.0	8.3	14.5	N/A	N/A	17.8	26.0	8.2	14.5	N/A	N/A

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 44 of 69

Captures:


The plots provided are those at nominal supply voltage only.

A. 802.11b (Low channel only):

1MBPS




5.5MBPS




Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 45 of 69

11MBPS




B. 802.11g (Low channel only):

6MBPS



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 46 of 69


54MBPS




Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 47 of 69

C. 802.11n HT20 (Low channel only):

MCS0



MCS7



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 48 of 69

EXHIBIT 10. Transmitter Spurious Emissions

Test Engineer:	Khairul Aidi Zainal
Test Date:	6/10/16

Requirement:

Article 7 of the Ordinance Regulating Radio Equipment, table 3, sets forth the requirements for Transmitter spurious emissions.

The limits for category WW:

Frequency band	Permissible average power at 1MHz band -width of spurious emission
Lower than 2,387 MHz and higher than 2,496.5MHz	Lower than 2.5 μ W
Higher than 2,387 MHz, lower than 2400MHz, and higher than 2,483.5 and lower than 2,496.5 MHz.	Lower than 25 μ W

Exclusion bands:

In case of the frequency hopping systems and a combination of hopping and other modulation method(s), the range from 2,374 MHz to 2,509.5 MHz is excluded. For other modulation methods, the range from 2,400 MHz to 2,483.5 MHz is excluded.

Test note:

1. EUT was tested at the lowest, middle and high channels.
2. Measurement performed at nominal, +10% nominal and -10% nominal supply voltage.
3. Testing performed across all modulations/modes.
4. Measurement
 - a. RBW=VBW=1MHz
 - b. Measure emissions that are within 3dB of the limit (over or under)
 - c. Sweep points > 400 points
 - d. Detector = RMS (Final measurement), Peak (Pre-scan)
 - e. Sweep time >= 1 second (Final measurement), Auto (pre-scan)


Result:

The transmitter spurious emissions of the EUT were more than 6dB below the limit. The EUT is found to be compliant to the requirement of the Ordinance regulating Radio Equipment.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 49 of 69

Screen Captures:
802.11b:

30MHz to 2387MHz & 2496.5MHz to 12500MHz




Note:

- The plots above were obtained at nominal supply voltage. Emissions were unchanged at different supply voltages

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 50 of 69

2387MHz to 2400MHz & 2483.5MHz to 2496.5MHz

Nominal supply voltage




Note:

1. Varying the supply voltage did not change the emissions level.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 51 of 69

802.11g:

30MHz to 2387MHz & 2496.5MHz to 12500MHz




Note:

1. The plots above were obtained at nominal supply voltage. Emissions were unchanged at different supply voltages

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 52 of 69

2387MHz to 2400MHz & 2483.5MHz to 2496.5MHz

Nominal supply voltage




Note:

1. Varying the supply voltage did not change the emissions level.


Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 53 of 69

802.11n:


30MHz to 2387MHz & 2496.5MHz to 12500MHz




30MHz to 2387 MHz (low channel)




2496.5MHz to 12500MHz (low channel)



30MHz to 2387 MHz (middle channel)



2496.5MHz to 12500MHz (middle channel)



30MHz to 2387 MHz (high channel)

2496.5MHz to 12500MHz (high channel)


Note:

1. The plots above were obtained at nominal supply voltage. Emissions were unchanged at different supply voltages

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 54 of 69

2387MHz to 2400MHz & 2483.5MHz to 2496.5MHz

Nominal supply voltage



Note:

1. Varying the supply voltage did not change the emissions level.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 55 of 69

EXHIBIT 11. Secondary Emissions

Test Engineer:	Khairul Zainal
Test Date:	6/10/16

Requirement:

Article 24 of the Ordinance Regulating Radio Equipment sets forth the requirements for secondary/receiver emissions.

The limits:

30 MHz to 1000 MHz	Lower than 4.0 nW
1000 MHz to 12500 MHz	Lower than 20.0 nW

Test note:

1. EUT was tested at the low, middle and high channels.
2. Measurement performed at nominal, +10% nominal and -10% nominal supply voltage.
3. Emissions did not change with change in supply voltage.

Result:


The secondary emissions of the EUT were more than 6dB below the limit. The EUT is found to be compliant to the requirement of the Ordinance regulating Radio Equipment.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 56 of 69


Screen Captures:

The plots provided are those at nominal supply voltage only.

Low Channel




Middle Channel



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 57 of 69

High Channel



Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 58 of 69

EXHIBIT 12. Dwell Time

Test Engineer:	N/A
Test Date:	N/A

Requirement:

Article 49.20 and article 2 of the Ordinance Regulating Radio Equipment sets forth the requirements for dwell time/retention time. This requirement only applies to FHSS systems with direct modulation.

The dwell time of an FHSS system is limited to 0.4 seconds or less.

Result:

Requirement does not apply for this mode (WLAN)

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 59 of 69

EXHIBIT 13. Spreading Factor

Test Engineer:	Khairul Aidi Zainal
Test Date:	5/6/2016, 5/25/2016

Requirement:

Article 49.20 of the Ordinance Regulating Radio Equipment sets forth the requirements for spreading factor.

The spreading factor for category WW is greater than 5.

Result:

The worst case spreading factor was calculated to be **6.9**. The EUT is found to be compliant to the requirement of the Ordinance regulating Radio Equipment.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 60 of 69

Data:

802.11 b 1MBPS									
Low channel			Middle Channel			High Channel			
EUT supply voltage (V)	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor
3.3VDC (Nominal)	9.2	1.0	9.2	9.2	1.0	9.2	9.3	1.0	9.3
2.97VDC (-10%)	9.2	1.0	9.2	9.2	1.0	9.2	9.3	1.0	9.3
3.6VDC (Max declared)	9.2	1.0	9.2	9.2	1.0	9.2	9.3	1.0	9.3

802.11 b 5.5MBPS									
Low channel			Middle Channel			High Channel			
EUT supply voltage (V)	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor
3.3VDC (Nominal)	9.6	1.38	7.0	9.6	1.38	7.0	9.6	1.38	7.0
2.97VDC (-10%)	9.6	1.38	7.0	9.6	1.38	7.0	9.6	1.38	7.0
3.6VDC (Max declared)	9.6	1.38	7.0	9.6	1.38	7.0	9.6	1.38	7.0

802.11 b 11MBPS									
Low channel			Middle Channel			High Channel			
EUT supply voltage (V)	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor	Spreading Bandwidth/ 90% BW (MHz)	Transmission rate (Msymbol/s)	Spreading factor
3.3VDC (Nominal)	9.6	1.38	7.0	9.6	1.38	7.0	9.5	1.38	6.9
2.97VDC (-10%)	9.6	1.38	7.0	9.6	1.38	7.0	9.5	1.38	6.9
3.6VDC (Max declared)	9.6	1.38	7.0	9.6	1.38	7.0	9.5	1.38	6.9

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 61 of 69

EXHIBIT 14. Antenna Power Tolerance

Test Engineer:	Khairul Aidi Zainal
Test Date:	5/26/16 – 6/8/16

Requirement:

Article 14 of the Ordinance Regulating Radio Equipment sets forth the requirements for antenna power tolerance. The antenna power of a device shall be within -80% and +20% of the rated or declared antenna power.

Result:

The measured antenna power for the EUT was within the prescribed range. The EUT is found to be compliant to the requirement of the Ordinance regulating Radio Equipment.

Data:

802.11b															
EUT supply voltage (V)	Low channel					Middle Channel					High Channel				
	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail
15.0VDC (Nominal)	7.7	5.916	6.000	1.20mW < P < 7.20mW	Pass	7.9	6.124	6.000	1.20mW < P < 7.20mW	Pass	7.2	5.248	6.000	1.20mW < P < 7.20mW	Pass
13.5 VDC (-10%)	7.8	6.026	6.000	1.20mW < P < 7.20mW	Pass	7.8	5.984	6.000	1.20mW < P < 7.20mW	Pass	7.8	5.984	6.000	1.20mW < P < 7.20mW	Pass
16.5 VDC (+10%)	8.1	6.397	6.000	1.20mW < P < 7.20mW	Pass	7.5	5.585	6.000	1.20mW < P < 7.20mW	Pass	7.2	5.284	6.000	1.20mW < P < 7.20mW	Pass

802.11g															
EUT supply voltage (V)	Low channel					Middle Channel					High Channel				
	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail
15.0VDC (Nominal)	3.5	2.218	2.000	0.40mW < P < 2.40mW	Pass	3.4	2.163	2.000	0.40mW < P < 2.40mW	Pass	2.9	1.968	2.000	0.40mW < P < 2.40mW	Pass
13.5 VDC (-10%)	3.6	2.307	2.000	0.40mW < P < 2.40mW	Pass	3.5	2.223	2.000	0.40mW < P < 2.40mW	Pass	3.3	2.143	2.000	0.40mW < P < 2.40mW	Pass
16.5 VDC (+10%)	3.5	2.259	2.000	0.40mW < P < 2.40mW	Pass	3.4	2.193	2.000	0.40mW < P < 2.40mW	Pass	3.0	2.004	2.000	0.40mW < P < 2.40mW	Pass

802.11n															
EUT supply voltage (V)	Low channel					Middle Channel					High Channel				
	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail	RMS power (dBm/MHz)	RMS power,P (mW/MHz)	Rated RMS power (mW/MHz)	Tolerance	Pass/Fail
15.0VDC (Nominal)	2.0	1.596	1.500	0.30mW < P < 1.80mW	Pass	2.2	1.641	1.500	0.30mW < P < 1.80mW	Pass	1.9	1.545	1.500	0.30mW < P < 1.80mW	Pass
13.5 VDC (-10%)	2.0	1.578	1.500	0.30mW < P < 1.80mW	Pass	2.1	1.626	1.500	0.30mW < P < 1.80mW	Pass	1.9	1.545	1.500	0.30mW < P < 1.80mW	Pass
16.5 VDC (+10%)	2.1	1.603	1.500	0.30mW < P < 1.80mW	Pass	2.2	1.652	1.500	0.30mW < P < 1.80mW	Pass	1.9	1.563	1.500	0.30mW < P < 1.80mW	Pass

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 62 of 69

EXHIBIT 15. Amount of carrier in 1 MHz

Requirement:

Article 2, Item (19) 49.20 1) g / 49.20 3) h Notice 88 Appendix 43, 44, 45 requires that if OFDM is applied the amount of carriers within 1 MHz shall be 1 or more.

Result:

There is more than one (1) subcarrier within 1 MHz hence the EUT is found to be compliant to the requirement of the Ordinance regulating Radio Equipment.

Data:

Amount of carriers within 1MHz = Number of subcarriers/Occupied bandwidth (MHz)

- 802.11g = 52 carriers
- 802.11n = 56 carriers

Note: Since the Occupied bandwidth (99%) is less than the number of defined subcarriers the device is compliant with this requirement.

6 MBPS									
Low Channel				Middle channel			High Channel		
EUT supply voltage (V)	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz
3.3VDC (Nominal)	16.8	52.0	3.1	16.9	52.0	3.1	16.76	52.0	3.1

54 MBPS									
Low Channel				Middle channel			High Channel		
EUT supply voltage (V)	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz
3.3VDC (Nominal)	16.6	52.0	3.1	16.6	52.0	3.1	16.6	52.0	3.1

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 63 of 69

MCS 0									
EUT supply voltage (V)	Low Channel			Middle channel			High Channel		
	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz
3.3VDC (Nominal)	17.9	56.0	3.1	17.7	56.0	3.2	17.7	56.0	3.2

MCS7									
EUT supply voltage (V)	Low Channel			Middle channel			High Channel		
	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz	Occupied Bandwidth / 99% BW (MHz)	Number of subcarriers	Carriers / 1MHz
3.3VDC (Nominal)	17.8	56.0	3.1	17.7	56.0	3.2	17.8	56.0	3.2

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 64 of 69

EXHIBIT 16. “Not Easily To Open”

Requirement:

Article 2 of the Ordinance Regulating Radio Equipment states that the EUT shall be constructed in such a way that the RF parts cannot be reached easily by the user

Result:

The radio module, except for the antenna port, is located under a shield.

The EUT is found to be compliant to the requirement of the Ordinance regulating Radio Equipment.

Data:

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 65 of 69

EXHIBIT 17. Voltage fluctuation

Requirement:

Article 15-1 of the Ordinance Regulating Radio Equipment states that all measurements shall be carried out with three different supply voltages: The rated nominal value, -10% and +10%. However if the EUT uses an internal voltage regulator, supplying power to all critical parts of the radio circuitry, it is acceptable to restrict the measurements to the nominal supply voltage value under the condition that the regulator is capable to reduce the voltage variation to a value smaller than 1% of input (if the input is varied by 10%).

Result:

All testing were performed with supply voltage varied at $\pm 10\%$ of the nominal voltage. Results show that there was no change to the radio parameters when the supply voltage was varied. The supply voltage variance was between -10% and +10% variance.

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 66 of 69

EXHIBIT 18. Interference Prevention Function

Requirement:

Article 2 of the Ordinance Regulating Radio Equipment states that the EUT shall have the capability to transmit or to receive the MAC identification automatically, so that sender and receiver shall exclude other equipment.

Result:

Statement from manufacturer:

“The device has a radio module that implements the IEEE 802.11 b/g/n (HT20) protocols, as well as, Bluetooth 2.1 + EDR & 4.0 (BLE) protocols. The module’s 48 bit MAC address is transmitted during the connection phase to a master or peer.”

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 67 of 69

APPENDIX A – Test Equipment List



Date : 6-May-2016

Type Test : Conducted measurements


Job # : C-2395

Prepared By: Aidi

Customer : LSR

Quote #: 316053

No.	Asset #	Description	Manufacturer	Model #	Serial #	Cal Date	Cal Due Date	Equipment Status
1	EE 960090	Power Meter	Anritsu	ML2495A	1335006	3/25/2015	3/25/2016	Active Calibration
2	EE 960073	Spectrum Analyzer	Agilent	E4446A	US45300564	10/25/2015	10/25/2016	Active Calibration
3	AA 960144	Phaseflex	Gore	EKD01D010720	5800373	Verification	Verification	System
4	EE 960054	Multimeter	HP	971A	JP40011152	3/16/2015	3/16/2016	Active Calibration

Project Engineer: 

Quality Assurance: 

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 68 of 69

APPENDIX B - Uncertainty Statement

Table of Expanded Uncertainty Values, (K=2) for Specified Measurements

<i>Measurement Type</i>	<i>Particular Configuration</i>	<i>Uncertainty Values</i>
<i>Radiated Emissions</i>	<i>3 – Meter chamber, Biconical Antenna</i>	<i>4.82 dB</i>
<i>Radiated Emissions</i>	<i>3-Meter Chamber, Log Periodic Antenna</i>	<i>4.88 dB</i>
<i>Radiated Emissions</i>	<i>3-Meter Chamber, Horn Antenna</i>	<i>4.85 dB</i>
<i>Radiated Emissions</i>	<i>10-Meter OATS, Biconical Antenna</i>	<i>4.32 dB</i>
<i>Radiated Emissions</i>	<i>10-Meter OATS, Log Periodic Antenna</i>	<i>3.63 dB</i>
<i>Absolute Conducted Emissions</i>	<i>Agilent PSA/ESA Series</i>	<i>1.38 dB</i>
<i>AC Line Conducted Emissions</i>	<i>Shielded Room/EMCO LISN</i>	<i>3.20 dB</i>
<i>Radiated Immunity</i>	<i>3 Volts/Meter in 3-Meter Chamber</i>	<i>2.05 Volts/Meter</i>
<i>Conducted Immunity</i>	<i>3 Volts level</i>	<i>2.33 V</i>
<i>EFT Burst, Surge, VDI</i>	<i>230 VAC</i>	<i>54.4 V</i>
<i>ESD Immunity</i>	<i>Discharge at 15kV</i>	<i>3200 V</i>
<i>Temperature/Humidity</i>	<i>Thermo-hygrometer</i>	<i>0.64° / 2.88 %RH</i>

Prepared For: Fluke Corporation	Model #: STERLING-LWB	LSR
Report # 316053 A	Serial #: 49	Template: ARIB STD-T66 template
LSR Job #: C-2395		Page 69 of 69