CE Test Report

Equipment	:	**Sterling-LWB5 Module**
Model No.	:	**450-0162, 450-0168, 450-0169** **(Refer to item 1.1.1 for more details)**
Brand Name	:	**Laird**
Applicant	:	**Laird Technologies**
Address	:	**W66N220 Commerce Court, Cedarburg, Wisconsin 53012, USA**
Standard	:	**EN 300 328 V2.1.1 (2016-11)**
Received Date	:	**Jul. 03, 2017**
Tested Date	:	**Aug. 04 ~ Sep. 04, 2017**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

James Fan / Assistant Manager

Approved by:

Gary Chang / Manager

Testing Laboratory 2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 9
1.3 Test Setup Chart 9
1.4 Test Equipment List and Calibration Data 10
1.5 Testing Applied Standards 12
1.6 Measurement Uncertainty 12

2 TEST CONFIGURATION 13

2.1 Testing Condition 13
2.2 The Worst Test Modes and Channel Details 13

3 TRANSMITTER TEST RESULTS 14

3.1 RF Output Power 14
3.2 Power Spectral Density 19
3.3 Occupied Channel Bandwidth 21
3.4 Transmitter Unwanted Emissions in the Out-Of-Band Domain 23
3.5 Transmitter Unwanted Emissions in the Spurious Domain 32

4 RECEIVER TEST RESULTS 70

4.1 Receiver Spurious Emissions 70

5 ADAPTIVITY TEST RESULTS 96

5.1 Adaptivity and Unwanted Signal Parameters 96

6 RECEIVER BLOCKING TEST RESULTS 102

6.1 Receiver Blocking 102

7 PHOTOGRAPHS OF THE TEST CONFIGURATION 106

8 TEST LABORATORY INFORMATION 109

Release Record

Report No.	Version	Description	Issued Date
ER770305AC	Rev. 01	Initial issue	Sep. 14, 2017
ER770305AC	Rev. 02	Revising the model name	Sep. 25, 2017

Summary of Test Results

Ref. Std. Clause	Test Items	Measured	Result
4.3.2.2	RF Output Power	15.43 dBm.	Pass
4.3.2.3	Power Spectral Density	Meet the requirement of limit.	Pass
4.3.2.4	Duty Cycle, Tx-sequence, Tx-gap	Only for non-adaptive equipment.	N/A
4.3.2.5	Medium Utilisation (MU) factor	Only for non-adaptive equipment.	N/A
4.3.2.6	Adaptivity	Meet the requirement of limit.	Pass
4.3.2.7	Occupied Channel Bandwidth	Meet the requirement of limit.	Pass
4.3.2.8	Transmitter unwanted emissions in the out of band domain	Meet the requirement of limit.	Pass
4.3.2.9	Transmitter unwanted emissions in the spurious domain	Meet the requirement of limit.	Pass
4.3.2.10	Receiver spurious emissions	Meet the requirement of limit.	Pass
4.3.2.11	Receiver Blocking	Meet the requirement of limit.	Pass
4.3.2.12	Geo-location Capability	The device has no this capability.	N/A

1 General Description

1.1 Information

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
Laird	450-0162	Sterling-LWB5 Module	SIP Module
	450-0168		U.FL Module
	450-0169		Chip Antenna Module

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N_{TX})	Data Rate / MCS
2400-2483.5	b	2412-2472	1-13 [13]	1	1-11 Mbps
2400-2483.5	g	2412-2472	1-13 [13]	1	6-54 Mbps
2400-2483.5	n (HT20)	2412-2472	1-13 [13]	1	MCS 0-7
2400-2483.5	n (HT40)	2422-2462	3-11 [9]	1	MCS 0-7
Note 1: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation. Note 2: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.					

1.1.3 Antenna Details

Ant. No.	Model	Type	Connector	Gain (dBi)	Remarks
1	LSR/001-0009	Dipole	IPEX U.FL	2	---
2	LSR/FlexPIFA 001-0016	PIFA	IPEX U.FL		---
3	LSR/001-0012	Dipole	IPEX U.FL		---
4	CHIP ANTENNA: Johanson P/N: 2450AD14A5500#	Chip	IPEX U.FL	1	---

1.1.4 EUT Operational Condition

Power Supply Type	3.3Vdc from host		
SW Version	6.37.39.77		
Operational Climatic	☒ Tnom (20°C)	☒ Tmax (85°C)	☒ Tmin (-40°C)

1.1.5 Accessories

N/A

1.1.6 Adaptive Equipment

Adaptive Equipment		
☐	non-Adaptive Equipment:	
	The maximum RF Output Power (e.i.r.p.): dBm	
	The maximum (corresponding) Duty Cycle: %	
☒	Adaptive Equipment without the possibility to switch to a non-adaptive mode:	
	☒	The equipment has implemented an LBT based DAA mechanism:
		☐ The equipment is Frame Based equipment
		☒ The equipment is Load Based equipment
		☐ The equipment can switch dynamically between Frame Based and Load Based equipment
	☐	The equipment has implemented an non-LBT based DAA mechanism
	☐	The equipment can operate in more than one adaptive mode
	☐	Adaptive Frequency Hopping using other forms of DAA (non-LBT based)/without Short Control Signaling Transmissions
☐	Adaptive Equipment which can also operate in a non-adaptive mode	

1.1.7 Channel List

Frequency band (MHz)		2400~2483.5	
802.11 b / g / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	10	2457
9	2452	11	2462
10	2457	---	---
11	2462	---	---
12	2467	---	---
13	2472	---	---

1.1.8 Test Tool and Duty Cycle

Test Tool	Sterling WLAN RF Eval Tool, Ver. 2.10.0.0	
Modulation Mode	**Duty Cycle Of Test Signal (%)**	**Duty Factor (dB)**
b	99.29%	0.03
g	97.20%	0.12
n (HT20)	96.72%	0.14
n (HT40)	92.06%	0.36

1.1.9 Power Setting

Modulation Mode	Test Frequency (MHz)					
	b / g / n HT20			n HT40		
	2412	2442	2472	2422	2442	2462
b	14	14	14	---	---	---
g	14	14	14	---	---	---
n (HT20)	12	12	12	---	---	---
n (HT40)	---	---	---	9	9	9

1.2 Local Support Equipment List

Support Equipment List						
No.	**Equipment**	**Brand**	**Model**	**S/N**	**FCC ID**	**Signal cable / Length (m)**
1	Notebook	DELL	Latitude E6430	J5GB4X1	DoC	USB, 1m shielded.
2	DC Power Supply	GWINSTEK	GPC-3060D	EM884797	---	---
3	Fixture	---	---	---	---	---

Note: Fixture is provided by applicant.

1.3 Test Setup Chart

Test Setup Diagram (Conducted)



Test Setup Diagram (Radiated)



1.4 Test Equipment List and Calibration Data

Test Item	Radiated Emissions				
Test Site	Fully-anechoic chamber 2 / (05CH02-WS)				
Tested Date	Aug. 04, 2017				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	Agilent	N9010A	MY52221474	Oct. 14, 2016	Oct. 13, 2017
Bilog Antenna 30-1000MHz	SCHWARZBECK	VULB9168	9168-563	Jan. 05, 2017	Jan. 04, 2018
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	9120D-1205	Jan. 05, 2017	Jan. 04, 2018
Preamplifier	Agilent	83017A	MY53270013	Jan. 10, 2017	Jan. 09, 2018
Preamplifier 30-1000MHz	EMC	EMC02325	980188	Dec. 13, 2016	Dec. 12, 2017
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22622/4	Dec. 13, 2016	Dec. 12, 2017
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22623/4	Dec. 14, 2016	Dec. 13, 2017
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22621/4	Dec. 14, 2016	Dec. 13, 2017
RF cable-4M	HUBER+SUHNER	SUCOFLEX104	MY22579/4	Dec. 14, 2016	Dec. 13, 2017
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-002	Dec. 14, 2016	Dec. 13, 2017
LF cable-3M	EMC	EMC8D-NM-NM-3000	131102	Dec. 14, 2016	Dec. 13, 2017
LF cable-10M	EMC	EMC8D-NM-NM-10000	131101	Dec. 14, 2016	Dec. 13, 2017
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Adaptivity				
Test Site	(TH01-WS)				
Tested Date	Aug. 30, 2017				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	R&S	FSV-7	101607	Dec. 07, 2016	Dec. 06, 2017
Signal Generator	R&S	SMB 100A	175727	Oct. 19,2016	Oct. 18,2017
RF Cable	HUBER+SUHNER	SUCOFLEX_104	MY15686/4	Dec. 16, 2016	Dec. 15, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX_104	296081/4	Dec. 16, 2016	Dec. 15, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX_104	329023/4	Dec. 16, 2016	Dec. 15, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX_104	329021/4	Dec. 16, 2016	Dec. 15, 2017
Vector signal generator	Agilent	MXG	N5182B	Apr. 15, 2017	Apr. 14, 2018
Preamplifier	Burgeon	BPA-530	100219	Jul. 28, 2017	Jul. 27, 2018
Oscilloscope	National Instruments	USB-5133	F651FF	Jul. 28, 2017	Jun. 27, 2018
Measurement Software	Sporton	Sporton-3	2.2.0.0	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Sep. 04, 2017				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40	101486	Nov. 15, 2016	Nov. 14, 2017
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 21, 2016	Nov. 20, 2017
Power Sensor	Agilent	U2021XA	MY53480019	Feb. 06, 2017	Feb. 05, 2018
Power Sensor	Agilent	U2021XA	MY53510003	Feb. 06, 2017	Feb. 05, 2018
Power Sensor	Agilent	U2021XA	MY54070003	Feb. 15, 2017	Feb. 14, 2018
Power Sensor	Agilent	U2021XA	MY54060013	Feb. 15, 2017	Feb. 14, 2018
Signal Generator	R&S	SMB100A	175727	Oct. 19, 2016	Oct. 18, 2017
DC POWER SOURCE	GW INSTEK	GPC-6030D	EM892433	Oct. 20, 2016	Oct. 19, 2017
Combiner(1X2)	woken	0120A02201801O	DOM2AEW1A23	Dec. 15, 2016	Dec. 14, 2017
Combiner(1X4)	woken	0120A04056002D	111204	Dec. 15, 2016	Dec. 14, 2017
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Measurement Software	Agilent	EN RF test	1.1501125	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Receiver Blocking				
Test Site	(05CH01-WS)				
Tested Date	Aug. 30, 2017				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Wireless connectivity tester	ROHDE&SCHWARZ	CMW270	100856	Nov. 07, 2016	Nov. 06, 2017
Signal Generator	R&S	SMB100A	175727	Oct. 19, 2016	Oct. 18, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX_104	500202/4	Dec. 16, 2016	Dec. 15, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX_104	296088/4	Dec. 16, 2016	Dec. 15, 2017
RF Cable	HUBER+SUHNER	SUCOFLEX_104	329023/4	Dec. 16, 2016	Dec. 15, 2017
Note: Calibration Interval of instruments listed above is one year.					

1.5 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

EN 300 328 V2.1.1 (2016-11)

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty		
Parameters	**Uncertainty**	**Limit**
Occupied Channel Bandwidth	±0.0034 %	±5 %
RF output power, conducted	±0.537 dB	±1.5 dB
Power Spectral Density, conducted	±0.463 dB	±3 dB
Unwanted Emissions, conducted	±2.505 dB	±3 dB
All emissions, radiated	±3.401 dB	±6 dB
Temperature	±0.6 ^{o}C	±3 °C
Supply voltages	±0.16 %	±3 %
Time	±0.1 %	±5 %

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
RF Conducted	TH01-WS	23°C / 65%	Jack Li
Radiated Emission	05CH02-WS	24°C / 65%	Ryan Lee
Adaptivity	TH01-WS	25°C / 64%	Ryan Lee
Receiver Blocking	05CH01-WS	22.5°C / 64%	David Chiu

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
RF Output Power Power Spectral Density Transmitter unwanted emissions in the out of band domain	11b 11g HT20 HT40	2412 / 2442 / 2472 2412 / 2442 / 2472 2412 / 2442 / 2472 2422 / 2442 / 2462	1 Mbps 6 Mbps MCS 0 MCS 0	1, 2
Occupied Channel Bandwidth Adaptivity	11b 11g HT20 HT40	2412 / 2472 2412 / 2472 2412 / 2472 2422 / 2462	1 Mbps 6 Mbps MCS 0 MCS 0	2
Transmitter Spurious Emissions ≤ 1GHz	11g HT40	2412 / 2472 2422 / 2462	6 Mbps MCS 0	2
Transmitter Spurious Emissions > 1GHz	11b 11g HT20 HT40	2412 / 2472 2412 / 2472 2412 / 2472 2422 / 2462	1 Mbps 6 Mbps MCS 0 MCS 0	2
Receiver Spurious Emissions	11g HT40	2412 / 2472 2422 / 2462	6 Mbps MCS 0	2
Receiver Blocking	11b	2412 / 2472	1 Mbps	2

NOTE:

1. The test configurations are listed as follows:
   Configuration 1 : Antenna Gain 1dBi
   Configuration 2 : Antenna Gain 2dB**i**
2. 50Ω terminator is connected to antenna port of EUT for radiated emission measurement.

3 Transmitter Test Results

3.1 RF Output Power

3.1.1 Limit of RF Output Power

For adaptive equipment using wide band modulations other than FHSS, the maximum RF output power shall be 20 dBm.

3.1.2 Test Procedures

Reference to clause 5.4.2.2 of ETSI EN 300 328 V2.1.1 (2016-11).

3.1.3 Test Setup



3.1.4 Test Result of RF Output Power

Configuration 1 : Antenna Gain 1dBi

RF Output Power (dBm)				
Modulation Mode	11b/1Mbps			
Condition	**Freq. (MHz)**	**EIRP Power**	**Limit (dBm)**	**Results**
$T_{nom}V_{nom}$	2412	13.76	20	Pass
$T_{min}V_{nom}$	2412	14.43	20	Pass
$T_{max}V_{nom}$	2412	13.61	20	Pass
$T_{nom}V_{nom}$	2442	13.32	20	Pass
$T_{min}V_{nom}$	2442	13.99	20	Pass
$T_{max}V_{nom}$	2442	13.09	20	Pass
$T_{nom}V_{nom}$	2472	12.85	20	Pass
$T_{min}V_{nom}$	2472	13.45	20	Pass
$T_{max}V_{nom}$	2472	12.65	20	Pass

RF Output Power (dBm)				
Modulation Mode	11g/6Mbps			
Condition	**Freq. (MHz)**	**EIRP Power**	**Limit (dBm)**	**Results**
$T_{nom}V_{nom}$	2412	13.70	20	Pass
$T_{min}V_{nom}$	2412	14.37	20	Pass
$T_{max}V_{nom}$	2412	13.55	20	Pass
$T_{nom}V_{nom}$	2442	13.30	20	Pass
$T_{min}V_{nom}$	2442	14.06	20	Pass
$T_{max}V_{nom}$	2442	13.13	20	Pass
$T_{nom}V_{nom}$	2472	12.76	20	Pass
$T_{min}V_{nom}$	2472	13.29	20	Pass
$T_{max}V_{nom}$	2472	12.59	20	Pass

RF Output Power (dBm)				
Modulation Mode	HT20/MCS 0			
Condition	**Freq. (MHz)**	**EIRP Power**	**Limit (dBm)**	**Results**
$T_{nom}V_{nom}$	2412	11.81	20	Pass
$T_{min}V_{nom}$	2412	12.60	20	Pass
$T_{max}V_{nom}$	2412	11.61	20	Pass
$T_{nom}V_{nom}$	2442	11.39	20	Pass
$T_{min}V_{nom}$	2442	12.09	20	Pass
$T_{max}V_{nom}$	2442	11.22	20	Pass
$T_{nom}V_{nom}$	2472	10.71	20	Pass
$T_{min}V_{nom}$	2472	11.38	20	Pass
$T_{max}V_{nom}$	2472	10.61	20	Pass

RF Output Power (dBm)				
Modulation Mode	HT40/MCS 0			
Condition	**Freq. (MHz)**	**EIRP Power**	**Limit (dBm)**	**Results**
$T_{nom}V_{nom}$	2422	9.01	20	Pass
$T_{min}V_{nom}$	2422	9.70	20	Pass
$T_{max}V_{nom}$	2422	8.95	20	Pass
$T_{nom}V_{nom}$	2442	8.47	20	Pass
$T_{min}V_{nom}$	2442	9.11	20	Pass
$T_{max}V_{nom}$	2442	8.35	20	Pass
$T_{nom}V_{nom}$	2462	8.27	20	Pass
$T_{min}V_{nom}$	2462	8.88	20	Pass
$T_{max}V_{nom}$	2462	8.17	20	Pass

Configuration 2 : Antenna Gain 2dBi

RF Output Power (dBm)				
Modulation Mode	11b/1Mbps			
Condition	**Freq. (MHz)**	**EIRP Power**	**Limit (dBm)**	**Results**
$T_{nom}V_{nom}$	2412	14.76	20	Pass
$T_{min}V_{nom}$	2412	**15.43**	20	Pass
$T_{max}V_{nom}$	2412	14.61	20	Pass
$T_{nom}V_{nom}$	2442	14.32	20	Pass
$T_{min}V_{nom}$	2442	14.99	20	Pass
$T_{max}V_{nom}$	2442	14.09	20	Pass
$T_{nom}V_{nom}$	2472	13.85	20	Pass
$T_{min}V_{nom}$	2472	14.45	20	Pass
$T_{max}V_{nom}$	2472	13.65	20	Pass

RF Output Power (dBm)				
Modulation Mode	11g/6Mbps			
Condition	**Freq. (MHz)**	**EIRP Power**	**Limit (dBm)**	**Results**
$T_{nom}V_{nom}$	2412	14.70	20	Pass
$T_{min}V_{nom}$	2412	15.37	20	Pass
$T_{max}V_{nom}$	2412	14.55	20	Pass
$T_{nom}V_{nom}$	2442	14.30	20	Pass
$T_{min}V_{nom}$	2442	15.06	20	Pass
$T_{max}V_{nom}$	2442	14.13	20	Pass
$T_{nom}V_{nom}$	2472	13.76	20	Pass
$T_{min}V_{nom}$	2472	14.29	20	Pass
$T_{max}V_{nom}$	2472	13.59	20	Pass

RF Output Power (dBm)				
Modulation Mode	HT20/MCS 0			
Condition	**Freq. (MHz)**	**EIRP Power**	**Limit (dBm)**	**Results**
$T_{nom}V_{nom}$	2412	12.81	20	Pass
$T_{min}V_{nom}$	2412	13.60	20	Pass
$T_{max}V_{nom}$	2412	12.61	20	Pass
$T_{nom}V_{nom}$	2442	12.39	20	Pass
$T_{min}V_{nom}$	2442	13.09	20	Pass
$T_{max}V_{nom}$	2442	12.22	20	Pass
$T_{nom}V_{nom}$	2472	11.71	20	Pass
$T_{min}V_{nom}$	2472	12.38	20	Pass
$T_{max}V_{nom}$	2472	11.61	20	Pass

RF Output Power (dBm)				
Modulation Mode	HT40/MCS 0			
Condition	**Freq. (MHz)**	**EIRP Power**	**Limit (dBm)**	**Results**
$T_{nom}V_{nom}$	2422	10.01	20	Pass
$T_{min}V_{nom}$	2422	10.70	20	Pass
$T_{max}V_{nom}$	2422	9.95	20	Pass
$T_{nom}V_{nom}$	2442	9.47	20	Pass
$T_{min}V_{nom}$	2442	10.11	20	Pass
$T_{max}V_{nom}$	2442	9.35	20	Pass
$T_{nom}V_{nom}$	2462	9.27	20	Pass
$T_{min}V_{nom}$	2462	9.88	20	Pass
$T_{max}V_{nom}$	2462	9.17	20	Pass

3.2 Power Spectral Density

3.2.1 Limit of Power Spectral Density

For equipment using wide band modulations other than FHSS, the maximum Power Spectral Density is limited to 10 dBm per MHz.

3.2.2 Test Procedures

Reference to clause 5.4.3.2 of ETSI EN 300 328 V2.1.1 (2016-11).

3.2.3 Test Setup



3.2.4 Test Result of Power Spectral Density

Configuration 1 : Antenna Gain 1dBi

Modulation Mode	Freq. (MHz)	Power Density (dBm/1MHz)	Limit (dBm/1MHz)	Results
11b/1Mbps	2412	6.14	10	Pass
11b/1Mbps	2442	5.48	10	Pass
11b/1Mbps	2472	5.23	10	Pass
11g/6Mbps	2412	2.03	10	Pass
11g/6Mbps	2442	1.56	10	Pass
11g/6Mbps	2472	1.04	10	Pass
HT20/MCS 0	2412	-0.28	10	Pass
HT20/MCS 0	2442	-0.68	10	Pass
HT20/MCS 0	2472	-1.23	10	Pass
HT40/MCS 0	2422	-5.88	10	Pass
HT40/MCS 0	2442	-6.48	10	Pass
HT40/MCS 0	2462	-6.31	10	Pass

Configuration 2 : Antenna Gain 2dBi

Modulation Mode	Freq. (MHz)	Power Density (dBm/1MHz)	Limit (dBm/1MHz)	Results
11b/1Mbps	2412	7.14	10	Pass
11b/1Mbps	2442	6.48	10	Pass
11b/1Mbps	2472	6.23	10	Pass
11g/6Mbps	2412	3.03	10	Pass
11g/6Mbps	2442	2.56	10	Pass
11g/6Mbps	2472	2.04	10	Pass
HT20/MCS 0	2412	0.72	10	Pass
HT20/MCS 0	2442	0.32	10	Pass
HT20/MCS 0	2472	-0.23	10	Pass
HT40/MCS 0	2422	-4.88	10	Pass
HT40/MCS 0	2442	-5.48	10	Pass
HT40/MCS 0	2462	-5.31	10	Pass

3.3 Occupied Channel Bandwidth

3.3.1 Limit of Occupied Channel Bandwidth

The Occupied Channel Bandwidth shall fall completely within 2.4~2.4835 GHz.

In addition, for non-adaptive equipment using wide band modulations other than FHSS and with e.i.r.p greater than 10 dBm, the occupied channel bandwidth shall be less than 20 MHz.

3.3.2 Test Procedures

Reference to clause 5.4.7.2 of ETSI EN 300 328 V2.1.1 (2016-11).

3.3.3 Test Setup



3.3.4 Test Result of Occupied Channel Bandwidth

Modulation Mode	Frequency (MHz)	99% Bandwidth (MHz)	F_L at 99% BW (MHz)	F_H at 99% BW (MHz)	Limit F_L / F_H (MHz)
11b/1Mbps	2412	10.99	2406.50	2417.49	2400.0
11b/1Mbps	2472	11.34	2466.38	2477.73	2483.5
11g/6Mbps	2412	17.19	2403.43	2420.62	2400.0
11g/6Mbps	2472	17.25	2463.37	2480.62	2483.5
HT20/MCS 0	2412	18.35	2402.85	2421.20	2400.0
HT20/MCS 0	2472	18.35	2462.85	2481.20	2483.5
HT40/MCS 0	2422	36.46	2403.82	2440.29	2400.0
HT40/MCS 0	2462	36.46	2443.82	2480.29	2483.5

3.4 Transmitter Unwanted Emissions in the Out-Of-Band Domain

3.4.1 Limit of Transmitter Unwanted Emissions in the Out-Of-Band Domain



3.4.2 Test Procedures

Reference to clause 5.4.8.2 of ETSI EN 300 328 V2.1.1 (2016-11).

3.4.3 Test Setup



3.4.4 Test Result of Transmitter Unwanted Emissions in the Out-Of-Band Domain

Configuration 1 : Antenna Gain 1dBi

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
$T_{nom}V_{nom}$	11b/1Mbps	2412	2398.50	-36.18	-10
$T_{nom}V_{nom}$	11b/1Mbps	2412	2387.51	-45.80	-20
$T_{nom}V_{nom}$	11b/1Mbps	2472	2485.00	-30.02	-10
$T_{nom}V_{nom}$	11b/1Mbps	2472	2498.34	-42.75	-20

Low Band	Up Band
	

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
$T_{nom}V_{nom}$	11g/6Mbps	2412	2399.50	-37.75	-10
$T_{nom}V_{nom}$	11g/6Mbps	2412	2382.31	-43.98	-20
$T_{nom}V_{nom}$	11g/6Mbps	2472	2484.00	-25.18	-10
$T_{nom}V_{nom}$	11g/6Mbps	2472	2501.25	-39.23	-20

Low Band	Up Band
	

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
$T_{nom}V_{nom}$	HT20/MCS 0	2412	2399.50	-37.41	-10
$T_{nom}V_{nom}$	HT20/MCS 0	2412	2381.15	-46.05	-20
$T_{nom}V_{nom}$	HT20/MCS 0	2472	2484.00	-31.53	-10
$T_{nom}V_{nom}$	HT20/MCS 0	2472	2502.35	-44.14	-20
Low Band			**Up Band**		





Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
$T_{nom}V_{nom}$	HT40/MCS 0	2422	2399.50	-43.73	-10
$T_{nom}V_{nom}$	HT40/MCS 0	2422	2363.04	-47.14	-20
$T_{nom}V_{nom}$	HT40/MCS 0	2462	2484.00	-42.00	-10
$T_{nom}V_{nom}$	HT40/MCS 0	2462	2520.46	-47.01	-20

Low Band	Up Band
	

Configuration 2 : Antenna Gain 2dBi

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
$T_{nom}V_{nom}$	11b/1Mbps	2412	2398.50	-35.29	-10
$T_{nom}V_{nom}$	11b/1Mbps	2412	2387.51	-44.88	-20
$T_{nom}V_{nom}$	11b/1Mbps	2472	2485.00	-28.94	-10
$T_{nom}V_{nom}$	11b/1Mbps	2472	2498.34	-41.75	-20

Low Band	Up Band
	

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
$T_{nom}V_{nom}$	11g/6Mbps	2412	2399.50	-36.43	-10
$T_{nom}V_{nom}$	11g/6Mbps	2412	2382.31	-43.24	-20
$T_{nom}V_{nom}$	11g/6Mbps	2472	2485.00	-24.07	-10
$T_{nom}V_{nom}$	11g/6Mbps	2472	2501.25	-38.12	-20
Low Band			**Up Band**		





Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
$T_{nom}V_{nom}$	HT20/MCS 0	2412	2399.50	-36.36	-10
$T_{nom}V_{nom}$	HT20/MCS 0	2412	2381.15	-45.07	-20
$T_{nom}V_{nom}$	HT20/MCS 0	2472	2484.00	-30.40	-10
$T_{nom}V_{nom}$	HT20/MCS 0	2472	2502.35	-43.06	-20
Low Band			**Up Band**		





Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
$T_{nom}V_{nom}$	HT40/MCS 0	2422	2399.50	-42.70	-10
$T_{nom}V_{nom}$	HT40/MCS 0	2422	2363.04	-46.12	-20
$T_{nom}V_{nom}$	HT40/MCS 0	2462	2484.00	-41.13	-10
$T_{nom}V_{nom}$	HT40/MCS 0	2462	2521.46	-46.05	-20
Low Band			**Up Band**		





3.5 Transmitter Unwanted Emissions in the Spurious Domain

3.5.1 Limit of Transmitter Unwanted Emissions in the Spurious Domain

Frequency Range (MHz)	Maximum power (dBm)	Bandwidth (kHz)
30 to 47	-36	100
47 to 74	-54	100
74 to 87,5	-36	100
87,5 to 118	-54	100
118 to 174	-36	100
174 to 230	-54	100
230 to 470	-36	100
470 to 862	-54	100
862 to 1000	-36	100
1000 to 12750	-30	1000

3.5.2 Test Procedures

Reference to clause 5.4.9.2 of ETSI EN 300 328 V2.1.1 (2016-11).

3.5.3 Test Setup

Below 1GHz



Above 1 GHz



Conducted Emission



3.5.4 Transmitter Conducted Unwanted Emissions (Below 1GHz)

Modulation	11g	Test Freq. (MHz)	2412



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	94.99	-90.40	-54.00	-36.40	0.00	-90.40
2	494.63	-88.20	-54.00	-34.20	0.00	-88.20
3	805.03	-88.25	-54.00	-34.25	0.00	-88.25

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	94.70	-90.80	-54.00	-36.80	0.00	-90.80
2	494.45	-88.66	-54.00	-34.66	0.00	-88.66
3	805.26	-88.59	-54.00	-34.59	0.00	-88.59

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	94.84	-90.65	-54.00	-36.65	0.00	-90.65
2	494.15	-88.66	-54.00	-34.66	0.00	-88.66
3	805.26	-88.45	-54.00	-34.45	0.00	-88.45

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	94.15	-90.45	-54.00	-36.45	0.00	-90.45
2	494.15	-88.47	-54.00	-34.47	0.00	-88.47
3	805.17	-88.55	-54.00	-34.55	0.00	-88.55

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.5.5 Transmitter Conducted Unwanted Emissions (Above 1GHz)

Modulation	11b	Test Freq. (MHz)	2412



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4824.20	-49.31	-30.00	-19.31	0.00	-49.31
2	7237.88	-51.00	-30.00	-21.00	0.00	-51.00

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11b	Test Freq. (MHz)	2472



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4943.90	-44.38	-30.00	-14.38	0.00	-44.38
2	7416.32	-53.98	-30.00	-23.98	0.00	-53.98

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2412



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4824.90	-50.44	-30.00	-20.44	0.00	-50.44
2	7236.50	-50.86	-30.00	-20.86	0.00	-50.86

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4946.90	-47.55	-30.00	-17.55	0.00	-47.55
2	7415.20	-55.23	-30.00	-25.23	0.00	-55.23

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT20	Test Freq. (MHz)	2412



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4824.35	-52.20	-30.00	-22.20	0.00	-52.20
2	7236.40	-52.89	-30.00	-22.89	0.00	-52.89

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT20	Test Freq. (MHz)	2472



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4944.70	-50.13	-30.00	-20.13	0.00	-50.13
2	7416.30	-53.15	-30.00	-23.15	0.00	-53.15

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4843.91	-52.08	-30.00	-22.08	0.00	-52.08
2	7265.58	-53.32	-30.00	-23.32	0.00	-53.32

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4923.37	-51.80	-30.00	-21.80	0.00	-51.80
2	7387.56	-54.59	-30.00	-24.59	0.00	-54.59

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.5.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11g	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	180.45	-76.47	-54.00	-22.47	-3.62	-72.85
2	523.54	-71.47	-54.00	-17.47	4.21	-75.68
3	704.65	-68.60	-54.00	-14.60	8.14	-76.74

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	213.33	-72.86	-54.00	-18.86	-5.14	-67.72
2	533.65	-71.54	-54.00	-17.54	5.50	-77.04
3	704.47	-69.68	-54.00	-15.68	7.11	-76.79

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	180.65	-76.65	-54.00	-22.65	-3.66	-72.99
2	523.45	-71.69	-54.00	-17.69	4.21	-75.90
3	704.41	-68.98	-54.00	-14.98	8.13	-77.11

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	213.65	-72.42	-54.00	-18.42	-5.17	-67.25
2	533.47	-71.90	-54.00	-17.90	5.50	-77.40
3	704.47	-69.58	-54.00	-15.58	7.11	-76.69

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	180.45	-76.93	-54.00	-22.93	-3.62	-73.31
2	523.70	-71.45	-54.00	-17.45	4.22	-75.67
3	704.58	-68.65	-54.00	-14.65	8.13	-76.78

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	213.87	-72.57	-54.00	-18.57	-5.19	-67.38
2	533.84	-71.65	-54.00	-17.65	5.49	-77.14
3	704.47	-69.47	-54.00	-15.47	7.11	-76.58

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	180.45	-76.93	-54.00	-22.93	-3.62	-73.31
2	523.78	-71.47	-54.00	-17.47	4.22	-75.69
3	704.58	-68.65	-54.00	-14.65	8.13	-76.78

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	213.54	-72.55	-54.00	-18.55	-5.16	-67.39
2	533.45	-71.60	-54.00	-17.60	5.50	-77.10
3	704.40	-69.47	-54.00	-15.47	7.11	-76.58

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 802.11b

Modulation	11b	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4823.80	-51.59	-30.00	-21.59	11.62	-63.21
2	7237.24	-44.99	-30.00	-14.99	17.41	-62.40

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11b	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4824.17	-53.89	-30.00	-23.89	11.76	-65.65
2	7237.72	-48.04	-30.00	-18.04	17.26	-65.30

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11b	Test Freq. (MHz)	2472
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4944.10	-49.93	-30.00	-19.93	12.05	-61.98
2	7414.52	-44.69	-30.00	-14.69	16.93	-61.62

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11b	Test Freq. (MHz)	2472
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4944.10	-53.34	-30.00	-23.34	11.56	-64.90
2	7416.06	-46.77	-30.00	-16.77	17.86	-64.63

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 802.11g

Modulation	11g	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4824.65	-53.64	-30.00	-23.64	11.62	-65.26
2	7239.75	-45.75	-30.00	-15.75	17.41	-63.16

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4822.51	-54.99	-30.00	-24.99	11.77	-66.76
2	7237.26	-49.02	-30.00	-19.02	17.26	-66.28

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4946.95	-51.24	-30.00	-21.24	12.08	-63.32
2	7409.90	-46.31	-30.00	-16.31	16.92	-63.23

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4944.20	-54.62	-30.00	-24.62	11.56	-66.18
2	7416.30	-47.61	-30.00	-17.61	17.86	-65.47

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.5.9 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 802.11n HT20

Modulation	HT20	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4824.20	-54.86	-30.00	-24.86	11.62	-66.48
2	7236.45	-48.54	-30.00	-18.54	17.41	-65.95

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4824.50	-54.91	-30.00	-24.91	11.76	-66.67
2	7236.35	-49.16	-30.00	-19.16	17.25	-66.41

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT20	Test Freq. (MHz)	2472
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4944.75	-52.87	-30.00	-22.87	12.05	-64.92
2	7416.85	-47.41	-30.00	-17.41	16.94	-64.35

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT20	Test Freq. (MHz)	2472
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4944.40	-55.29	-30.00	-25.29	11.56	-66.85
2	7416.65	-47.86	-30.00	-17.86	17.85	-65.71

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.5.10 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 802.11n HT40

Modulation	HT40	**Test Freq. (MHz)**	2422
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4842.14	-54.65	-30.00	-24.65	11.59	-66.24
2	7264.45	-48.91	-30.00	-18.91	17.44	-66.35

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4845.17	-54.76	-30.00	-24.76	11.63	-66.39
2	7265.08	-49.49	-30.00	-19.49	17.34	-66.83

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4924.70	-55.39	-30.00	-25.39	11.82	-67.21
2	7386.77	-49.88	-30.00	-19.88	16.97	-66.85

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4921.80	-55.48	-30.00	-25.48	11.43	-66.91
2	7387.52	-48.45	-30.00	-18.45	17.89	-66.34

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4 Receiver Test Results

4.1 Receiver Spurious Emissions

4.1.1 Limit of Receiver Spurious Emissions

Frequency Range	Maximum power (dBm)	Measurement bandwidth (kHz)
30 MHz to 1 GHz	-57	100
Above 1 GHz to 12,75 GHz	-47	1000

4.1.2 Test Procedures

Reference to clause 5.4.10.2 of ETSI EN 300 328 V2.1.1 (2016-11).

4.1.3 Test Setup

Below 1GHz



Above 1 GHz



Conducted Emission



4.1.4 Receiver Conducted Spurious Emissions (Below 1GHz)

Modulation	11g	Test Freq. (MHz)	2412



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	226.91	-91.49	-57.00	-34.49	0.00	-91.49
2	461.65	-91.03	-57.00	-34.03	0.00	-91.03
3	690.57	-91.00	-57.00	-34.00	0.00	-91.00

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	226.58	-91.84	-57.00	-34.84	0.00	-91.84
2	461.85	-91.48	-57.00	-34.48	0.00	-91.48
3	690.45	-91.52	-57.00	-34.52	0.00	-91.52

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	226.54	-91.54	-57.00	-34.54	0.00	-91.54
2	461.15	-91.46	-57.00	-34.46	0.00	-91.46
3	690.45	-91.40	-57.00	-34.40	0.00	-91.40

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	226.50	-91.54	-57.00	-34.54	0.00	-91.54
2	461.45	-91.46	-57.00	-34.46	0.00	-91.46
3	690.52	-91.50	-57.00	-34.50	0.00	-91.50

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4.1.5 Receiver Conducted Spurious Emissions (Above 1GHz)

Modulation	11g	Test Freq. (MHz)	2412



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2411.99	-68.30	-47.00	-21.30	0.00	-68.30
2	3618.09	-65.28	-47.00	-18.28	0.00	-65.28
3	7237.14	-73.12	-47.00	-26.12	0.00	-73.12
4	10854.09	-72.40	-47.00	-25.40	0.00	-72.40

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2472.04	-68.24	-47.00	-21.24	0.00	-68.24
2	3707.88	-64.95	-47.00	-17.95	0.00	-64.95
3	7416.01	-72.83	-47.00	-25.83	0.00	-72.83
4	11123.93	-71.99	-47.00	-24.99	0.00	-71.99

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2422.01	-69.19	-47.00	-22.19	0.00	-69.19
2	3632.96	-65.66	-47.00	-18.66	0.00	-65.66
3	7266.13	-73.74	-47.00	-26.74	0.00	-73.74
4	10898.76	-72.89	-47.00	-25.89	0.00	-72.89

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2461.98	-68.93	-47.00	-21.93	0.00	-68.93
2	3693.06	-64.95	-47.00	-17.95	0.00	-64.95
3	7385.71	-74.05	-47.00	-27.05	0.00	-74.05
4	11078.97	-71.33	-47.00	-24.33	0.00	-71.33

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4.1.6 Receiver Radiated Unwanted Emissions (Below 1GHz)

Modulation	11g	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	280.26	-71.63	-57.00	-14.63	-0.29	-71.34
2	560.59	-71.37	-57.00	-14.37	4.71	-76.08
3	666.32	-70.45	-57.00	-13.45	6.76	-77.21

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	280.26	-73.42	-57.00	-16.42	-0.89	-72.53
2	533.43	-71.15	-57.00	-14.15	5.50	-76.65
3	673.11	-69.40	-57.00	-12.40	7.24	-76.64

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	280.58	-71.45	-57.00	-14.45	-0.30	-71.15
2	560.54	-71.55	-57.00	-14.55	4.71	-76.26
3	666.84	-70.16	-57.00	-13.16	6.78	-76.94

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	280.65	-73.35	-57.00	-16.35	-0.91	-72.44
2	533.45	-71.87	-57.00	-14.87	5.50	-77.37
3	673.63	-69.46	-57.00	-12.46	7.27	-76.73

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	280.58	-71.84	-57.00	-14.84	-0.30	-71.54
2	560.15	-71.55	-57.00	-14.55	4.70	-76.25
3	666.46	-70.63	-57.00	-13.63	6.77	-77.40

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	280.54	-73.13	-57.00	-16.13	-0.90	-72.23
2	533.98	-71.65	-57.00	-14.65	5.49	-77.14
3	673.50	-69.55	-57.00	-12.55	7.26	-76.81

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	280.58	-71.54	-57.00	-14.54	-0.30	-71.24
2	560.45	-71.34	-57.00	-14.34	4.71	-76.05
3	666.78	-70.35	-57.00	-13.35	6.78	-77.13

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	280.52	-73.47	-57.00	-16.47	-0.90	-72.57
2	533.48	-71.47	-57.00	-14.47	5.50	-76.97
3	673.36	-69.46	-57.00	-12.46	7.25	-76.71

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4.1.7 Receiver Radiated Unwanted Emissions (Above 1GHz)

Modulation	11g	**Test Freq. (MHz)**	2412
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	3617.81	-55.57	-47.00	-8.57	8.10	-63.67

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	3618.00	-55.52	-47.00	-8.52	7.77	-63.29

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	3707.56	-55.98	-47.00	-8.98	8.48	-64.46

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	11g	Test Freq. (MHz)	2472
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	3708.05	-55.21	-47.00	-8.21	8.23	-63.44

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	3633.20	-55.44	-47.00	-8.44	8.17	-63.61

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2422
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	3632.76	-55.49	-47.00	-8.49	7.85	-63.34

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	3693.09	-55.72	-47.00	-8.72	8.42	-64.14

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	HT40	Test Freq. (MHz)	2462
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	3692.87	-57.14	-47.00	-10.14	8.13	-65.27

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

5 Adaptivity Test Results

5.1 Adaptivity and Unwanted Signal Parameters

5.1.1 Limit of Adaptivity and Unwanted Signal Parameters

Adaptivity and Unwanted Signal Limit	
☒	Only for adaptive systems and RF Output Power > 10 dBm
☐	Non-LBT based Detect and Avoid: ◆ minimum remain unavailable = 1sec; ◆ minimum Idle Period time = 100us; ◆ maximum Channel Occupancy Time (COT) = 40ms ◆ detection threshold level = -70 dBm/MHz + 10 x $\log_{10}$(100mW / Pout) (Pout in mW e.i.r.p);
☐	LBT based Detect and Avoid (Frame Based Equipment): ◆ minimum Clear Channel Assessment (CCA) time = 18 us; ◆ COT = 1 ms to 10 ms ◆ Idle Period = 5% of COT ◆ detection threshold level = -70 dBm/MHz + 10 x $\log_{10}$(100mW / Pout) (Pout in mW e.i.r.p);
☒	LBT based Detect and Avoid (Load Based Equipment with spectrum sharing mechanism IEEE Std.): ◆ LBT based spectrum sharing mechanism may implement IEEE 802.11™-2012 [i.3] clause 9, clause 10, clause 16,clause 17, clause 19 and clause 20, or in IEEE 802.15.4™-2011 [i.4], clause 4, clause 5 and clause 8 ◆ detection threshold level = -70 dBm/MHz + 10 x $\log_{10}$(100mW / Pout) (Pout in mW e.i.r.p);
☒	Short Control Signalling Transmissions: ◆ Short Control Signalling Transmissions shall have a maximum duty cycle of 10 % within an observation period of 50 ms.

Unwanted Signal Parameters				
Equipment Type	**Wanted Signal Mean Power from Companion Device**	**Blocking Signal Frequency (MHz)**	**Blocking Signal Mean power (dBm)**	**Type of Interfering Signal**
LBT	sufficient to maintain the link (see note 2)	2395 or 2488,5 (see note 1)	-35 (see note 3)	CW
Non-LBT	-30 dBm			

Note 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz.
Note 2: A typical value which can be used in most cases is -50 dBm/MHz.
Note 3: The level specified is the level in front of the UUT antenna. In case of conducted measurements, this level has to be corrected by the actual antenna assembly gain.

5.1.2 Test Procedures

Reference to clause 5.4.6.2 of ETSI EN 300 328 V2.1.1 (2016-11).

5.1.3 Test Setup



5.1.4 Test Result of Adaptivity、Unwanted Signal and Short Control Signalling Transmissions

Adaptivity and Unwanted Signal Result						
EUT firmware / software version			6.37.39.77			
Adaptivity Detection Threshold Level (dBm)			-63.43			
Unwanted Signal Level (dBm)			-33			
Modulation Mode	**Freq. (MHz)**	**Short Control Signalling Transmissions (ms)**	**Channel Occupancy Time (ms)**	**Idle Period Time (μs)**	**Adaptivity**	**Unwanted Signal Test Status**
802.11b	2412	0.687	1.312	49	Pass	Pass
802.11b	2472	3.569	1.312	68		
802.11g	2412	1.668	1.234	51		
802.11g	2472	2.628	1.234	52		
802.11n (HT20)	2412	3.579	5.085	51		
802.11n (HT20)	2472	1.222	5.243	52		
802.11n (HT40)	2422	0.739	5.274	66		
802.11n (HT40)	2462	0.940	3.680	70		
Limit		< 5 ms	< 13 ms	>18μs		
Result		**Complied**				

5.1.5 Test Result of Adaptivity and Unwanted Signal Plots

Adaptivity & Unwanted Signal Result Plots	
Unwanted signal: 2488.5 MHz	**Unwanted signal: 2395 MHz**
802.11b - 2412MHz	**802.11b - 2472MHz**
	
802.11g - 2412MHz	**802.11g - 2472MHz**
	
802.11n (HT20) - 2412MHz	**802.11n (HT20) - 2472MHz**
	
802.11n (HT40) - 2422MHz	**802.11n (HT40) - 2462MHz**
	

5.1.6 Test Result of Short Control Signalling Transmissions Plots

Short Control Signalling Transmissions Plots	
802.11b - 2412MHz	**802.11b - 2472MHz**
	
802.11g - 2412MHz	**802.11g - 2472MHz**
	
802.11n (HT20) - 2412MHz	**802.11n (HT20) - 2472MHz**
	
802.11n (HT40) - 2422MHz	**802.11n (HT40) - 2462MHz**
	

Channel Occupancy Time

802.11b - 2412MHz

Max On Time



1.312ms

802.11b - 2472MHz

Max On Time



1.312ms

802.11g - 2412MHz

Max On Time



1.234ms

802.11g - 2472MHz

Max On Time



1.234ms

802.11n (HT20) - 2412MHz

Max On Time



5.085ms

802.11n (HT20) - 2472MHz

Max On Time



5.243ms

802.11n (HT40) - 2422MHz

Max On Time



5.274ms

802.11n (HT40) - 2462MHz

Max On Time



3.68ms

Idle Period Time	
802.11b - 2412MHz	**802.11b - 2472MHz**
	
802.11g - 2412MHz	**802.11g - 2472MHz**
	
802.11n (HT20) - 2412MHz	**802.11n (HT20) - 2472MHz**
	
802.11n (HT40) - 2422MHz	**802.11n (HT40) - 2462MHz**
	

6 Receiver Blocking Test Results

6.1 Receiver Blocking

6.1.1 Limit of Receiver Blocking

Receiver Blocking Parameters for Receiver Category 1 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm)	**Blocking Signal Frequency (MHz)**	**Blocking Signal Power (dBm) (see Note 2)**	**Type of Blocking Signal**
P_{min} + 6 dB	2 380 2 503,5	-53	CW
P_{min} + 6 dB	2 300 2 330 2 360	-47	CW
P_{min} + 6 dB	2 523,5 2 553,5 2 583,5 2 613,5 2 643,5 2 673,5	-47	CW
Note 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria (The minimum performance criterion shall be a PER less than or equal to 10 %) in the absence of any blocking signal. Note 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.			

Receiver Blocking Parameters for Receiver Category 2 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm)	**Blocking Signal Frequency (MHz)**	**Blocking Signal Power (dBm) (see Note 2)**	**Type of Blocking Signal**
P_{min} + 6 dB	2 380 2 503,5	-57	CW
P_{min} + 6 dB	2 300 2 583,5	-47	CW
Note 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria (The minimum performance criterion shall be a PER less than or equal to 10 %) in the absence of any blocking signal. Note 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.			

Receiver Blocking Parameters for Receiver Category 3 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm)	**Blocking Signal Frequency (MHz)**	**Blocking Signal Power (dBm) (see Note 2)**	**Type of Blocking Signal**
P_{min} + 12 dB	2 380 2 503,5	-57	CW
P_{min} + 12 dB	2 300 2 583,5	-47	CW
Note 1: P_{min} is the minimum level of the wanted signal (in dBm) required to meet the minimum performance criteria (The minimum performance criterion shall be a PER less than or equal to 10 %) in the absence of any blocking signal. Note 2: The levels specified are levels in front of the UUT antenna. In case of conducted measurements, the levels have to be corrected by the actual antenna assembly gain.			

6.1.2 Test Procedures

Reference to clause 5.4.11.2 of ETSI EN 300 328 V2.1.1 (2016-11).

6.1.3 Test Setup



6.1.4 Test Result of Receiver Blocking

11b / 2412 MHz
Without Interference Signal Sensitivity Level



PER minimum performance criteria	10 %		
Sensitivity Level	-93		**dBm**
Want Signal Mean Power form Companion Device (dBm)	**Blocking Signal Frequency (MHz)**	**Blocking Signal Power (dBm)**	**Test Result**
-87	2380.0	-51	Pass
-87	2503.5		Pass
-87	2300.0	-45	Pass
-87	2330.0		Pass
-87	2360.0		Pass
-87	2523.5	-45	Pass
-87	2553.5		Pass
-87	2583.5		Pass
-87	2613.5		Pass
-87	2643.5		Pass
-87	2673.5		Pass

11b / 2472 MHz
Without Interference Signal Sensitivity Level



PER minimum performance criteria	10 %		
Sensitivity Level	-93		**dBm**
Want Signal Mean Power form Companion Device (dBm)	**Blocking Signal Frequency (MHz)**	**Blocking Signal Power (dBm)**	**Test Result**
-87	2380.0	-51	Pass
-87	2503.5		Pass
-87	2300.0	-45	Pass
-87	2330.0		Pass
-87	2360.0		Pass
-87	2523.5	-45	Pass
-87	2553.5		Pass
-87	2583.5		Pass
-87	2613.5		Pass
-87	2643.5		Pass
-87	2673.5		Pass

7 Photographs of the Test Configuration

Conducted Spurious Emission Test



Radiated Spurious Emission Test





Adaptivity, Unwanted Signal and Short Control Signalling Transmissions Test



Receiver Blocking Test



8 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou	**Kwei Shan**	**Kwei Shan Site II**
Tel: 886-2-2601-1640	Tel: 886-3-271-8666	Tel: 886-3-271-8640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

═END═