AS/NZS Test Report

Equipment	:	**Bluetooth 4.2 module (BLE only)**
Model No.	:	**BL652-SA, BL652-SC** **(Refer to item 1.1.1 for more details)**
Brand Name	:	**Laird**
Applicant	:	**Laird Technologies**
Address	:	**W66N220 Commerce Court, Cedarburg, Wisconsin 53012, USA**
Standard	:	**AS/NZS 4268:2017**
Received Date	:	**May 14, 2018**
Tested Date	:	**May 31, 2018**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

James Fan / Assistant Manager

Approved by:

Gary Chang / Manager

Testing Laboratory 2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 7
1.3 Test Setup Chart 7
1.4 Test Equipment and Calibration Data 8
1.5 Testing Applied Standards 9
1.6 Measurement Uncertainty 9

2 TEST CONFIGURATION 10

2.1 Testing Condition 10
2.2 The Worst Test Modes and Channel Details 10

3 RECEIVER TEST RESULTS 11

3.1 Receiver Spurious Emissions 11

4 PHOTOGRAPHS OF THE TEST CONFIGURATION 31

5 TEST LABORATORY INFORMATION 43

Release Record

Report No.	Version	Description	Issued Date
AR662202-08	Rev. 01	Initial issue	Sep. 14, 2018

Summary of Test Results

Ref. Std. Clause	Test Items	Measured	Result
6.3	Maximum EIRP	Note	Note
6.4	Transmitter Spurious Emissions	Note	Note
6.5	Emission Bandwidth	Note	Note
6.6	Operating Frequencies	Note	Note
7.2	Receiver Spurious Emissions	Meet the requirement of limit.	Pass

Note: This test item is not required since the NFC function is passive only.

1 General Description

1.1 Information

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
Laird	BL652-SA	Bluetooth 4.2 module (BLE only)	with chip antenna
	BL652-SC		with MHF4 & IPEX connector type antenna

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information			
Frequency Range (MHz)	**Modulation**	**Ch. Frequency (MHz)**	**Channel Number**
13.553 – 13.567	ASK	13.56	1

1.1.3 Antenna Details

Ant. No.	Brand	Model	Type	Connector	Gain (dBi)	Remarks
1	ACX	AT3216-B2R7HAA	Chip	N/A	0.5	For BL652-SA
2	LSR	FlexPIFA 001-0022	FlexPIFA	MHF4	2	For BL652-SC
3	LSR	FlexNotch 001-0023	Flexible Notch	MHF4	2	
4	MAG. LAYERS	EDA-8709-2G4C1-B27	Dipole	MHF4	2	
5	Walsin	RFDPA870910EMAB302	Dipole	MHF4	2	
6	Walsin	RFDPA870900SBAB8G1	Dipole	MHF4	2	
7	YAMAMOTO METAL	YAN-02-C-MHF4P-050	Chip	MHF4	-1.76	
8	Laird	PCA-4606-2G4C1-A33-CY Laird # 0600-00056	PCB Dipole	IPEX	2.21	
9	Laird	EFA2400A3S-10MH4L	mFlexPIFA	MHF4	2	

1.1.4 EUT Operational Condition

Power Supply Type	3.3Vdc from host		
Operational Climatic	☒ Tnom (20°C)	☒ Tmax (85°C)	☒ Tmin (-40°C)

1.1.5 Accessories

N/A

1.1.6 Receiver Category

	Receiver Category	
☐	1	Highly reliable SRD communication media; e.g. serving human life inherent systems (may result in a physical risk to a person).
☐	2	Medium reliable SRD communication media e.g. causing Inconvenience to persons, which cannot simply be overcome by other means.
☒	3	Standard reliable SRD communication media e.g. Inconvenience to persons, which can simply be overcome by other means (e.g. manual).

1.2 Local Support Equipment List

Support Equipment List					
No.	**Equipment**	**Brand**	**Model**	**S/N**	**Remarks**
1	Notebook	DELL	Latitude E6440	7MW3Z52	---
2	Tablet	SONY	SGP511TW/B	CB5126VXTX	---
3	Extension Board	Laird	DVK-BL652-A1	---	Provided by applicant.

1.3 Test Setup Chart

Test Setup Diagram (for Model: BL652-SA)



No.	Signal cable / Length (m)
1	USB, 1.15m shielded.

Test Setup Diagram (for Model: BL652-SC)



No.	Signal cable / Length (m)
1	USB, 1.15m shielded.

1.4 Test Equipment and Calibration Data

Test Item	Radiated Emissions				
Test Site	Fully-anechoic chamber 2 / (05CH02-WS)				
Tested Date	May 31, 2018				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	Agilent	N9010A	MY54200247	Sep. 28, 2017	Sep. 27, 2018
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Oct. 27, 2017	Oct. 26, 2018
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1094	Nov. 10, 2017	Nov. 09, 2018
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170508	Dec. 19, 2017	Dec. 18, 2018
Preamplifier	Agilent	83017A	MY39501310	Nov. 28, 2017	Nov. 27, 2018
Preamplifier	EMC	EMC02325	980146	Oct. 13, 2017	Oct. 12, 2018
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY22626/4	Nov. 24, 2017	Nov. 23, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16608/4	Nov. 24, 2017	Nov. 23, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16617/4	Nov. 24, 2017	Nov. 23, 2018
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-005	Nov. 24, 2017	Nov. 23, 2018
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-006	Nov. 24, 2017	Nov. 23, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emissions				
Test Site	(10CH01-HY)				
Tested Date	May 31, 2018				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Receiver	R&S	ESI	838496/008	Sep. 01, 2017	Sep. 01, 2018
Preamplifier	EMC	EMC02325	980225	Jul. 28, 2017	Jul. 27, 2018
RF Cable-R03m	Jye Bao	RG142	CB031	Dec. 29, 2017	Dec. 28, 2018
RF Cable-10m	MTJ	RG223/U+RG8/U	CB026-DOOR	Dec. 29, 2017	Dec. 28, 2018
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2017	Nov. 12, 2018
Software	Audix	E3	4.03260c	N/A	N/A
Note: Calibration Interval of instruments listed above is one year.					

1.5 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

AS/NZS 4268:2017
EN 300 330 V2.1.1 (2017-02)

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	**Uncertainty**
RF power radiated	±3.401 dB

2 Test Configuration

2.1 Testing Condition

Testing Location							
☒	ICC Lab	ADD :	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan (R.O.C.)				
		TEL :	886-3-271-8666	FAX :	886-3-318-0155		
☒	Sporton Lab	ADD :	No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)				
		TEL :	886-3-327-3456	FAX :	886-3-327-0973		

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emission > 30 MHz	05CH02-WS	24°C / 65%	Chris Zeng
Radiated Emission ≤ 30 MHz	10CH01-HY*	24°C / 64%	Jack Li

Note: * ICC lab subcontracts this test item to Sporton Lab (TAF:1190).
Sporton Lab is a TAF accreditation test firm and also is an approved provider of ICC lab.

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test channel (MHz)	Test Configuration
Receiver Spurious Emissions	NFC	13.56	1 ~ 6

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** result was found as the worst case and was shown in this report.
2. Test configurations are listed as below:
   Configuration 1: model: BL652-SA, Antenna: AT3216-B2R7HAA
   Configuration 2: model: BL652-SC, Antenna: FlexNotch 001-0023
   Configuration 3: model: BL652-SC, Antenna: EDA-8709-2G4C1-B27
   Configuration 4: model: BL652-SC, Antenna: YAN-02-C-MHF4P-050
   Configuration 5: model: BL652-SC, Antenna: PCA-4606-2G4C1-A33-CY
   Configuration 6: model: BL652-SC, Antenna: EFA2400A3S-10MH4L

3 Receiver Test Results

3.1 Receiver Spurious Emissions

3.1.1 Receiver Spurious Emissions Limits

Measurement below 30 MHz

Frequency 9 kHz ≤ f < 10 MHz	Frequency 10 MHz ≤ f < 30 MHz
5,5 dBµA/m at 9 kHz descending 3 dB/oct	-25 dBµA/m

Measurement above 30 MHz

The measured values shall not exceed 2 nW e.r.p. (-57 dBm).

3.1.2 Test Procedures

Reference to clause 4.3.5.3 of EN 300 330 V2.1.1 (2017-02).

3.1.3 Test Setup

Below 30MHz



Above 30MHz



3.1.4 Receiver Spurious Emissions (Below 30MHz)

Mode	NFC	**Test Freq. (MHz)**	13.56
Test Configuration	1		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	13.29	38.66	59.00	-20.34	21.75	16.91
2	15.15	40.36	59.00	-18.64	21.99	18.37
3	21.48	37.09	59.00	-21.91	22.55	14.54

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Mode	NFC	**Test Freq. (MHz)**	13.56
Test Configuration	2		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	13.56	37.59	59.00	-21.41	21.79	15.80
2	15.27	39.01	59.00	-19.99	22.00	17.01
3	21.30	36.83	59.00	-22.17	22.54	14.29

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Mode	NFC	**Test Freq. (MHz)**	13.56
Test Configuration	3		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	13.56	37.59	59.00	-21.41	21.79	15.80
2	15.27	39.01	59.00	-19.99	22.00	17.01
3	21.30	36.83	59.00	-22.17	22.54	14.29

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Mode	NFC	**Test Freq. (MHz)**	13.56
Test Configuration	4		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	13.56	37.59	59.00	-21.41	21.79	15.80
2	15.27	39.01	59.00	-19.99	22.00	17.01
3	21.30	36.83	59.00	-22.17	22.54	14.29

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Mode	NFC	**Test Freq. (MHz)**	13.56
Test Configuration	5		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	13.56	37.59	59.00	-21.41	21.79	15.80
2	15.27	39.01	59.00	-19.99	22.00	17.01
3	21.30	36.83	59.00	-22.17	22.54	14.29

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Mode	NFC	**Test Freq. (MHz)**	13.56
Test Configuration	6		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	13.56	37.59	59.00	-21.41	21.79	15.80
2	15.27	39.01	59.00	-19.99	22.00	17.01
3	21.30	36.83	59.00	-22.17	22.54	14.29

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

3.1.5 Receiver Radiated Unwanted Emissions (Above 30MHz)

Polarization	Horizontal	Test Configuration	1



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	126.03	-72.79	-57.00	-15.79	-3.28	-69.51
2	504.33	-67.99	-57.00	-10.99	2.61	-70.60
3	605.21	-65.56	-57.00	-8.56	8.69	-74.25

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Vertical	Test Configuration	1



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	144.46	-72.64	-57.00	-15.64	-0.47	-72.17
2	408.30	-69.78	-57.00	-12.78	0.61	-70.39
3	504.33	-69.42	-57.00	-12.42	3.16	-72.58

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Horizontal	Test Configuration	2



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	144.68	-72.76	-57.00	-15.76	-1.70	-71.06
2	471.57	-71.07	-57.00	-14.07	2.22	-73.29
3	582.96	-69.05	-57.00	-12.05	4.36	-73.41

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Vertical	Test Configuration	2



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	143.75	-72.37	-57.00	-15.37	-0.48	-71.89
2	502.42	-69.64	-57.00	-12.64	2.99	-72.63
3	612.71	-67.50	-57.00	-10.50	5.62	-73.12

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Horizontal	Test Configuration	3



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	144.66	-72.74	-57.00	-15.74	-1.70	-71.04
2	471.57	-71.07	-57.00	-14.07	2.22	-73.29
3	582.96	-69.06	-57.00	-12.06	4.36	-73.42

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Vertical	Test Configuration	3



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	143.70	-72.44	-57.00	-15.44	-0.48	-71.96
2	502.42	-69.62	-57.00	-12.62	2.99	-72.61
3	612.71	-67.44	-57.00	-10.44	5.62	-73.06

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Horizontal	Test Configuration	4



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	144.66	-72.77	-57.00	-15.77	-1.70	-71.07
2	471.56	-71.09	-57.00	-14.09	2.22	-73.31
3	582.99	-69.08	-57.00	-12.08	4.36	-73.44

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Vertical	Test Configuration	4



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	143.78	-72.35	-57.00	-15.35	-0.48	-71.87
2	502.41	-69.67	-57.00	-12.67	2.99	-72.66
3	612.71	-67.47	-57.00	-10.47	5.62	-73.09

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Horizontal	Test Configuration	5



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	144.46	-72.51	-57.00	-15.51	-1.71	-70.80
2	471.35	-71.26	-57.00	-14.26	2.22	-73.48
3	582.90	-69.56	-57.00	-12.56	4.35	-73.91

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Vertical	Test Configuration	5



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	143.49	-72.93	-57.00	-15.93	-0.48	-72.45
2	502.39	-69.13	-57.00	-12.13	2.99	-72.12
3	612.97	-67.97	-57.00	-10.97	5.62	-73.59

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Horizontal	Test Configuration	6



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	144.67	-72.43	-57.00	-15.43	-1.70	-70.73
2	471.25	-71.06	-57.00	-14.06	2.22	-73.28
3	582.45	-69.29	-57.00	-12.29	4.33	-73.62

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

Polarization	Vertical	Test Configuration	6



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	143.24	-72.79	-57.00	-15.79	-0.48	-72.31
2	502.48	-69.46	-57.00	-12.46	3.00	-72.46
3	612.76	-67.82	-57.00	-10.82	5.62	-73.44

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB).
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm).

4 Photographs of the Test Configuration

Below 30MHz (Test Configuration 1)





Below 30MHz (Test Configuration 2)





Below 30MHz (Test Configuration 3)





Below 30MHz (Test Configuration 4)





Below 30MHz (Test Configuration 5)





Below 30MHz (Test Configuration 6)





Above 30MHz (Test Configuration 1)





Above 30MHz (Test Configuration 2)



Above 30MHz (Test Configuration 3)





Above 30MHz (Test Configuration 4)





Above 30MHz (Test Configuration 5)





Above 30MHz (Test Configuration 6)





5 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou	**Kwei Shan**	**Kwei Shan Site II**
Tel: 886-2-2601-1640	Tel: 886-3-271-8666	Tel: 886-3-271-8640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

═END═