

CE EMC Test Report

Equipment : Sentrius™ BT510
Bluetooth v5 IP67 Multi Sensor

Model No. : BT510

Brand Name : Laird

Applicant : Laird Connectivity

Address : W66N220 Commerce Court, Cedarburg,
Wisconsin 53012, USA

Standard : Draft EN 301 489-1 V2.2.0 (2017-03)
Draft EN 301 489-17 V3.2.0 (2017-03)

Received Date : Sep. 16, 2019


Tested Date : Oct. 08 ~ Oct. 28, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:


Peter Lin / Supervisor


Eason Chang / Assistant Manager


Kent Chen / Assistant Manager



Table of Contents

1	GENERAL DESCRIPTION	6
1.1	Information.....	6
1.2	Test Equipment and Calibration Data	7
1.3	Testing Applied Standards	8
1.4	Deviation from Test Standard and Measurement Procedure.....	8
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION.....	9
2.1	Testing Condition	9
2.2	The Worst Case Measurement Configuration.....	9
2.3	Local Support Equipment List	10
2.4	Test Setup Chart	10
2.5	Test Software and Operating Condition	11
3	EMISSION TEST RESULTS.....	12
3.1	Conducted Emissions from the AC mains power ports.....	12
4	IMMUNITY TESTS	18
4.1	General Description.....	18
4.2	Performance Criteria Description	19
4.3	Electrostatic Discharge (ESD).....	21
4.4	Radio Frequency Electromagnetic Field (RS).....	25
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	28
6	TEST LABORATORY INFORMATION	30

Release Record

Report No.	Version	Description	Issued Date
EH991601	Rev. 01	Initial issue	Dec. 10, 2019

Summary of Test Results

Draft EN 301 489-1 Emission Tests				
Ref. Std. Clause	Test Standard	Test Items	Measured	Result
8.3/8.4	EN 55032:2015/AC:2016, Class B	Conducted Emissions from the AC mains power ports	-12.55dB AV@ 0.363MHz.	Pass
8.7	EN 55032:2015/AC:2016, Class B	Asymmetric Mode Conducted Emissions	Note ¹	N/A
8.2	EN 55032:2015/AC:2016, Class B	Radiated Emissions	Note ²	N/A
8.5	EN 61000-3-2:2014, Class A	Harmonic Current Emissions	Note ³	N/A
8.6	EN 61000-3-3:2013	Voltage Fluctuations and Flicker	Note ³	N/A
<p>N/A means Not Applicable. Note¹: The EUT w/o telecom port. Note²: According to Clause 7.1 of Draft EN 301 489-1, the test is not required. Note³: The EUT consumes DC power, so the test is not required.</p>				

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Draft EN 301 489-1 Immunity Tests

Draft EN 301 489-1 Immunity Tests					
Ref. Std. Clause	Test Standard	Description of Test		Pass Criterion	Result
9.3	EN 61000-4-2:2009	Electrostatic Discharge (ESD)		A	Pass
9.2	EN 61000-4-3:2006/A1:2008/A2:2010	Radio Frequency Electromagnetic Field (RS)		A	Pass
9.4	EN 61000-4-4:2012	Electrical Fast Transient/Burst (EFT)		Note ¹	N/A
9.8	EN 61000-4-5:2014+A1:2017	Surge		Note ²	N/A
9.5	EN 61000-4-6:2014	Conducted Disturbances (CS)		Note ¹	N/A
9.7	EN 61000-4-11:2004	Voltage Dips	0% residual for 0.5 cycle	Note ²	N/A
			0% residual for 1 cycle	Note ²	N/A
			70% residual for 25 cycle	Note ²	N/A
		Voltage Interruption	0% residual for 250 cycle (w/o battery back-up)	Note ²	N/A
N/A means Not Applicable.					
Note ¹ : The EUT consumes DC power, and it is not intended to be used with cables longer than 3m. So this test is not carried out.					
Note ² : The EUT consumes DC power, so the test is not required.					

Comments and Explanations:

None.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Operating Frequency	2402 MHz ~ 2480 MHz
Modulation Type	Bluetooth 5.0 LE: GFSK
Antenna Type	PCB Trace
S/W Version	1.0.1

1.1.2 Power Supply Type of the Equipment under Test (EUT)

Power Supply Type	3Vdc from host
--------------------------	----------------

1.1.3 Accessories

N/A

1.2 Test Equipment and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Test Date	Oct. 08, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Jan. 08, 2019	Jan. 07, 2020
LISN	R&S	ENV216	101579	Mar. 08, 2019	Mar. 07, 2020
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Nov. 29, 2018	Nov. 28, 2019
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 22, 2019	Oct. 21, 2020
50 ohm terminal (Support Unit)	NA	50	04	May 28, 2019	May 27, 2020
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	ESD				
Test Site	ESD room 1 / (ES01-WS)				
Test Date	Oct. 28, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
ESD Generator	EMTest	Dito	V1248114239	Aug. 17, 2019	Aug. 16, 2020
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Immunity (80 MHz - 6 GHz)				
Test Site	RS room 1 / (RS01-WS)				
Test Date	Oct. 22, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Signal Generator	R&S	SMB100A	103924HA	Oct. 18, 2019	Oct. 17, 2020
Power Sensor	R&S	NRP-Z91	101094-UL	Oct. 16, 2019	Oct. 15, 2020
Power Sensor	R&S	NRP-Z91	101095-KY	Oct. 16, 2019	Oct. 15, 2020
Power Amplifier	BONN	BLWA 0810-160/100D	107972A	N/A	N/A
Power Amplifier	BONN	BLMA 1060-100D	107972B	N/A	N/A
Antenna	SCHWARZBECK MESS-ELEKTRONIK	STLP 9149	9149-073	N/A	N/A
Antenna	R & S	HL046E	100076-Cd	N/A	N/A
Note: Calibration Interval of instruments listed above is one year.					

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Draft EN 301 489-1 V2.2.0 (2017-03)
Draft EN 301 489-17 V3.2.0 (2017-03)

1.4 Deviation from Test Standard and Measurement Procedure

None

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty		
Test Item	Frequency	Uncertainty
Conducted Emissions from the AC mains power ports	150kHz ~ 30MHz	± 2.92 dB

Note: The results of measurements of emissions shall reference the measurement uncertainty considerations contained in CISPR 16-4-2.

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Conducted Emissions from the AC mains power ports	CO01-WS	23°C / 61%	Alex Tsai
ESD	ES01-WS	24°C/51%/103kPa	Zoe Yu
RS	RS01-WS	24°C/51%/100kPa	Zoe Yu

2.2 The Worst Case Measurement Configuration


The Determined Worst Case Configurations	
Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	BT Link, 230V/50Hz
2	BT Link, 110V/60Hz
ESD, RS Tests	
Test Mode	Operating Description
1	BT Link


2.3 Local Support Equipment List

Support Equipment List (EMI)					
No.	Equipment	Brand	Model	S/N	Remarks
1	Notebook	DELL	Latitude E6440	8VXMD12	---
2	Printer	EPSON	XP-30	QSDK002410	---
3	Mouse	DELL	MS111-L	2C3-00MM	---
4	Sentrius™ BT510 Bluetooth v5 IP67 Multi Sensor	Laird	BT510	---	Provided by applicant.

Support Equipment List (EMS)					
No.	Equipment	Brand	Model	S/N	Remarks
1	Notebook	DELL	Latitude E6440	8VXMD12	---
2	Notebook	Kingston	DTSE9G2	7XVW0	---
3	Sentrius™ BT510 Bluetooth v5 IP67 Multi Sensor	Laird	BT510	---	Provided by applicant.
4	DC Power Supply	GWINSTEK	GPC-60300	EM884797	---

2.4 Test Setup Chart





2.5 Test Software and Operating Condition

EMI

- To enable all function of test system.
- The support notebook executed "KM Player" to play colorbar video.
- The support notebook executed "WinEMC.exe" to send "H" patterns to the printer.
- The support notebook executed "Uwterminal.exe" to link BT function of EUT via USB cable.

EMS

- To enable all function of test system.
- The support notebook executed "Uwterminal.exe" to link BT function of EUT via USB cable.

3 Emission Test Results

3.1 Conducted Emissions from the AC mains power ports

3.1.1 Limits of Conducted Emissions from the AC mains power ports


Frequency range (MHz)	Limits values (dB μ V)			
	Class A		Class B	
	Quasi-peak	Average	Quasi-peak	Average
0.15 to 0,50	79	66	66 to 56 *	56 to 46 *
0,50 to 5	73	60	56	46
5 to 30	73	60	60	50

Note 1: “*” Decreasing linearly with the logarithm of the frequency.
 Note 2: If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.
 Note 3: The higher value measured with and without the outer conductor screen of the antenna terminal connected to earth is considered.

3.1.2 Test Procedures


- The EUT was placed on a desk 0.8 meters height from the metal ground plane and 0.4 meter from the conducting wall of the shielding room and it was kept at least 0.8 meters from any other grounded conducting surface.
- A thickness of ≤ 0.15 m insulation should be placed between local AE and associated cabling and the RGP.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The CISPR states that a 50 ohm, 50 microhenry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

3.1.3 Test Setup




- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions from the AC mains power ports




Power Phase		Neutral		Test Mode		1	
-------------	--	---------	--	-----------	--	---	--




	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.162	22.11	55.34	-33.23	12.48	9.57	0.06	Average
2	0.162	32.27	65.34	-33.07	22.64	9.57	0.06	QP
3	0.358	33.06	48.78	-15.72	23.37	9.61	0.08	Average
4	0.358	37.00	58.78	-21.78	27.31	9.61	0.08	QP
5*	0.393	33.87	47.99	-14.12	24.18	9.61	0.08	Average
6	0.393	37.64	57.99	-20.35	27.95	9.61	0.08	QP
7	2.033	25.50	46.00	-20.50	15.69	9.65	0.16	Average
8	2.033	30.39	56.00	-25.61	20.58	9.65	0.16	QP
9	2.346	21.94	46.00	-24.06	12.10	9.65	0.19	Average
10	2.346	29.54	56.00	-26.46	19.70	9.65	0.19	QP
11	10.233	20.28	50.00	-29.72	10.13	9.71	0.44	Average
12	10.233	25.40	60.00	-34.60	15.25	9.71	0.44	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Limit Line (dBuV) – Level (dBuV).



Power Phase		Neutral	Test Mode		2			
-------------	--	---------	-----------	--	---	--	--	--



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.189	19.76	54.06	-34.30	10.11	9.58	0.07	Average
2	0.189	28.71	64.06	-35.35	19.06	9.58	0.07	QP
3*	0.365	34.60	48.61	-14.01	24.91	9.61	0.08	Average
4	0.365	37.98	58.61	-20.63	28.29	9.61	0.08	QP
5	0.396	28.55	47.95	-19.40	18.86	9.61	0.08	Average
6	0.396	33.16	57.95	-24.79	23.47	9.61	0.08	QP
7	2.409	20.42	46.00	-25.58	10.58	9.65	0.19	Average
8	2.409	29.18	56.00	-26.82	19.34	9.65	0.19	QP
9	6.988	20.62	50.00	-29.38	10.55	9.69	0.38	Average
10	6.988	26.35	60.00	-33.65	16.28	9.69	0.38	QP
11	19.326	21.37	50.00	-28.63	10.96	9.81	0.60	Average
12	19.326	26.08	60.00	-33.92	15.67	9.81	0.60	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).

Note 2: Over Limit (dB) = Limit Line (dBuV) – Level (dBuV).

4 Immunity Tests

4.1 General Description

Product Standard: Draft EN 301 489-1, Draft EN 301 489-17		
Basic Standard	Spec. Requirement	Performance Criteria
EN 61000-4-2 (ESD)	Contact Discharge: ± 4 kV Air Discharge: ± 8 kV	B
EN 61000-4-3 (RS)	80 MHz to 6000 MHz 3 V/m, 1 kHz Sine Wave 80%, AM Modulation	A

4.2 Performance Criteria Description

Draft EN 301 489-17		
Criteria	During test	After test
A	<p>Shall operate as intended.</p> <p>May show degradation of performance (see note 1).</p> <p>Shall be no loss of function.</p> <p>Shall be no unintentional transmissions.</p>	<p>Shall operate as intended.</p> <p>Shall be no degradation of performance (see note 3).</p> <p>Shall be no loss of function.</p> <p>Shall be no loss of stored data or user programmable functions.</p>
B	<p>May show loss of function (one or more).</p> <p>May show degradation of performance (see note 2).</p> <p>No unintentional transmissions.</p>	<p>Functions shall be self-recoverable.</p> <p>Shall operate as intended after recovering.</p> <p>Shall be no degradation of performance (see note 3).</p> <p>Shall be no loss of stored data or user programmable functions.</p>
C	<p>May be loss of function (one or more).</p>	<p>Functions shall be recoverable by the operator.</p> <p>Shall operate as intended after recovering.</p> <p>Shall be no degradation of performance (see note 3).</p>
<p>Note 1: Operate as intended during the test allows a level of degradation not below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.</p>		
<p>Note 2: Degradation of performance during the test is understood as a degradation to a level not below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.</p>		
<p>Note 3: No degradation of performance after the test is understood as no degradation below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. After the test no change of actual operating data or user retrievable data is allowed. If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.</p>		

Draft EN 301 489-17 Performance Criteria

CT	The performance criteria A shall apply. Tests shall be repeated with the EUT in standby mode (if applicable) to ensure that unintentional transmission does not occur. In systems using acknowledgement signals, it is recognized that an ACKnowledgement (ACK) or Not ACKnowledgement (NACK) transmission may occur, and steps should be taken to ensure that any transmission resulting from the application of the test is correctly interpreted.
TT	The performance criteria B shall apply, except for voltage dips of 100 ms and voltage interruptions of 5 000 ms duration, for which performance criteria C shall apply. Tests shall be repeated with the EUT in standby mode (if applicable) to ensure that unintentional transmission does not occur. In systems using acknowledgement signals, it is recognized that an acknowledgement (ACK) or not-acknowledgement (NACK) transmission may occur, and steps should be taken to ensure that any transmission resulting from the application of the test is correctly interpreted.
CR	The performance criteria A shall apply. Where the EUT is a transceiver, under no circumstances, shall the transmitter operate unintentionally during the test. In systems using acknowledgement signals, it is recognized that an ACK or NACK transmission may occur, and steps should be taken to ensure that any transmission resulting from the application of the test is correctly interpreted.
TR	The performance criteria B shall apply, except for voltage dips of 100 ms and voltage interruptions of 5 000 ms duration for which performance criteria C shall apply. Where the EUT is a transceiver, under no circumstances, shall the transmitter operate unintentionally during the test. In systems using acknowledgement signals, it is recognized that an ACK or NACK transmission may occur, and steps should be taken to ensure that any transmission resulting from the application of the test is correctly interpreted.

Performance Criteria by Manufacturer

A	Without any transmit delay or any character error or any degradation of performance.
B	Any transmit delay or any character error. Functions shall be self-recoverable after the test.

4.3 Electrostatic Discharge (ESD)


4.3.1 Test Specification of Electrostatic Discharge (ESD)

Basic Standard	EN 61000-4-2
Discharge Voltage	Contact Discharge: ± 2 kV / ± 4 kV Air Discharge: ± 2 kV / ± 4 kV / ± 8 kV
Discharge Impedance	330 ohm / 150 pF
Number of Discharge	Air Discharge: minimum 20 times at each test point Contact Discharge: minimum 20 times at each test point
Discharge Mode	Single Discharge
Discharge Period	1 second minimum

4.3.2 Test Procedures

- a. In the case of air discharge testing the climatic conditions shall be within the following ranges:
 - ambient temperature: 15°C to 35°C;
 - relative humidity : 30% to 60%;
 - atmospheric pressure : 86 kPa (860 mbar) to 106 kPa (1060 mbar).
- b. Test programs and software shall be chosen so as to exercise all normal modes of operation of the EUT. The use of special exercising software is encouraged, but permitted only where it can be shown that the EUT is being comprehensively exercised.
- c. The test voltage shall be increased from the minimum to the selected test severity level, in order to determine any threshold of failure. The final severity level should not exceed the product specification value in order to avoid damage to the equipment.
- d. The test shall be performed with both air discharge and contact discharge. On preselected points at least 10 single discharges (in the most sensitive polarity) shall be applied on air discharge. On preselected points at least 10 single discharges (in the most sensitive polarity) shall be applied on contact discharge.
- e. For the time interval between successive single discharges an initial value of one second is recommended. Longer intervals may be determined whether a system failure has occurred.
- f. In the case of contact discharges, the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.
- g. In the case of painted surface covering a conducting substrate, the following procedure shall be adopted:
 - If the coating is not declared to be an insulating coating by the equipment manufacturer, then the pointed tip of the generator shall penetrate the coating so as to make contact with the conducting substrate.
 - Coating declared as insulating by the manufacturer shall only be submitted to the air discharge.
 - The contact discharge test shall not be applied to such surfaces.
- h. In the case of air discharges, the round discharge tip of the discharge electrode shall be approached as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator (discharge electrode) shall be removed from the EUT. The generator is then retriggered for a new single discharge. This procedure shall be repeated until the discharges are completed. In the case of an air discharge test, the discharge switch, which is used for contact discharge, shall be closed.

4.3.3 Test Setup



The test setup shall consist of a non-conductive table, $(0,8 \pm 0,08) \text{ m}$ high, standing on the ground reference plane.



A horizontal coupling plane (HCP), $(1,6 \pm 0,02) \text{ m} \times (0,8 \pm 0,02) \text{ m}$, shall be placed on the table. The EUT and its cables shall be isolated from the coupling plane by an insulating support $(0,5 \pm 0,05) \text{ mm}$ in thickness.

4.3.4 Test Result of Electrostatic Discharge (ESD)

Test Mode	1				
Direct Application					
Test Voltage (kV)	Polarity	Test Point	Contact Discharge	Air Discharge	Performance Criteria
2, 4, 8	+/-	1, 2, 3	N/A	Note	A
Indirect Application					
Test Voltage (kV)	Polarity	Test Point	Horizontal Coupling Plane (HCP)	Vertical Coupling Plane (VCP)	Performance Criteria
2, 4	+/-	At front, rear, left and right side	Note	Note	A

Note: There was no abnormal situation during the test compared with initial operation.

4.3.5 Test Point Photo



4.4 Radio Frequency Electromagnetic Field (RS)

4.4.1 Test Specification of Radio Frequency Electromagnetic Field (RS)

Basic Standard	EN 61000-4-3
Frequency Range	80 MHz ~ 6000 MHz
Field Strength	3 V/m
Modulation	1 kHz Sine Wave, 80%, AM Modulation
Frequency Step	1 % of preceding frequency value
Polarity of Antenna	Horizontal and Vertical
Antenna Height	1.5 m
Antenna Distance	80 MHz ~ 1000 MHz: 3 m 1000 MHz ~ 6000 MHz: 1 m
Dwell Time	3 seconds

4.4.2 Test Procedures

- The test level shall be 3 V/m (measured unmodulated). The test signal shall be amplitude modulated to a depth of 80 % by a sinusoidal audio signal of 1000 Hz. If the wanted signal is modulated at 1000 Hz, then an audio signal of 400 Hz shall be used.
- The test shall be performed over the frequency range 80 MHz to 6000 MHz with the exception of the exclusion band for transmitters, receivers and duplex transceivers, as appropriate.
- For receivers and transmitters the stepped frequency increments shall be 1 % frequency increment of the momentary used frequency, unless specified otherwise in the part of EN 301 489 series [i.13] dealing with the relevant type of radio equipment.
- Further product related spot frequency tests may be specified in the relevant part of EN 301 489 series [i.13] dealing with the particular type of radio equipment.
- Responses on receivers occurring at discrete frequencies, which are narrow band responses, shall be disregarded from the test.
- The frequencies selected and used during the test shall be recorded in the test report.
- When testing at frequencies above 1 GHz, the test distance shall be 1 m when using the independent windows method. Compliance with the field uniformity requirement shall be verified for the selected test distance.
- The alternative method for frequencies above 1 GHz divides the calibration area into a suitable array of 0,5 m × 0,5 m windows such that the whole area to be occupied by the face of the EUT is covered. The field uniformity shall be independently calibrated over each window.
- During the test, at each frequency the forward power shall be applied to the field-generating antenna. The test shall be repeated with the field-generating antenna repositioned to illuminate each of the required windows in turn.

4.4.3 Exclusion bands

The frequencies on which the transmitter part of the EUT is intended to operate shall be excluded from radiated emission measurements when performed in transmit mode of operation.

There shall be no frequency exclusion band applied to emission measurements of the receiver part of transceivers or the stand alone receiver under test, and/or associated ancillary equipment.

The exclusion band for immunity testing of equipment operating in the 2,4 GHz band shall be:

- lower limit of exclusion band = lowest allocated band edge frequency -120 MHz, i.e. 2 280 MHz;
- upper limit of exclusion band = highest allocated band edge frequency +120 MHz, i.e. 2 603,5MHz.

The exclusion band for immunity testing of equipment operating in the 5 GHz Wi-Fi band shall be:


- lower limit of exclusion band = lowest allocated band edge frequency -270 MHz, i.e. 4 880 MHz;
- upper limit of exclusion band = highest allocated band edge frequency +270 MHz, i.e. 5 995 MHz.

The exclusion band for immunity testing of equipment operating in the 5,8 GHz band shall be:

- lower limit of exclusion band = lowest allocated band edge frequency -270 MHz, i.e. 5 455 MHz;
- as the immunity requirements have an upper frequency range of 6 GHz and any upper edge exclusion band would be greater than this for the 5,8 GHz band. The above frequency shall also be regarded as the upper end of the test range.

NOTE: These receiver exclusion band ranges align with the relevant blocking test ranges.

4.4.4 Test Setup



Note: The procedure defined in this part requires the generation of electromagnetic fields within which the test sample is placed and its operation observed. To generate fields that are useful for simulation of actual (field) conditions may require significant antenna drive power and the resultant high field strength levels. To comply with local regulations and to prevent biological hazards to the testing personnel, it is recommended that these tests be carried out in a shielded enclosure or semi-anechoic chamber.


4.4.5 Test Result of Radio Frequency Electromagnetic Field (RS)

Test Mode	1				
Frequency Range (MHz)	Azimuth	Polarity	Test Field Strength (V/m)	Observation	Performance Criteria
80 – 6000	0	V&H	3	Note	A
80 – 6000	90	V&H	3	Note	A
80 – 6000	180	V&H	3	Note	A
80 – 6000	270	V&H	3	Note	A


Note: There was no abnormal situation during the test compared with initial operation.

5 Photographs of the Test Configuration


Conducted Emissions from the AC mains power ports



ESD Test



RS Test



6 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan,
R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==