

Laird Connectivity vehicular mounts are the industry standard for performance and durability.

FEATURES AND BENEFITS



- All brass construction and gold-plated contact design ensure the most corrosion resistance and best power transfer available
- 78 Rockwell Hardness brass material resists corrosion
- Silver soldered ground lug and contact virtually eliminates RF noise or static
- Multiple cable options are available

3/4" or 3/8" Hole Alternative Mounts (cable not included)

MODEL	CONNECTOR TYPE
MO	3/4 Steel mount
MBO	3/4 Brass mount for use with a RG58-size cable
MBOX	3/4 Brass mount for RG8X-size cable
MBOF	3/4 Brass mount for Teflon® cable
MABO	3/8 Brass mount for use with RG58-size cable
MABTO	3/4 or 3/8 Brass thick plate mount for 3/16" to 1/4" thick surfaces
MABVTO	3/4 or 3/8 Hole 1/2" thick plane (adjustable mount only)
MXGPO	3/8 Snap-in ground plane mount
MXO	Snap-in mount

5/8" Hole Alternative Mounts

MODEL	CONNECTOR TYPE
VTPM	1" Extra thick plate mount (UHF barrel – 1-3/8" total stud length)
VTPM800	800 MHz – 1/2" thick plate mount (N Barrel – 1-3/16" total stud length)

3/4" Hole Brass Mounts*



MODEL	CONNECTOR TYPE
Models w/ 17' of RG58A/U stranded center conductor cable	
MB8	No connector
MB8B	BNC crimp
MB8M	Mini UHF crimp
MB8N	N crimp
MB8NS	N solder
MB8P	UHF (PL259) crimp
MB8PS	UHF (PL259) solder
MB8PST	UHF (PL259) Teflon® solder
MB8T	TNC crimp
Models w/ 17' of RG58U solid center conductor cable	
MB8U	No connector
MB8UB	BNC crimp
MB8UM	Mini UHF crimp
MB8UN	N crimp
MB8UNS	N solder
MB8UP	UHF (PL259) crimp
MB8UPST	UHF (PL259) Teflon® solder
MB8UT	TNC crimp
Models w/ 17' of RG8X low loss solid center conductor cable	
MB8X	No connector
MB8XB	BNC crimp
MB8XM	Mini UHF crimp
MB8XN	N crimp
MB8XNS	N solder
MB8XP	UHF (PL259) crimp
MB8XPST	UHF (PL259) Teflon® solder
MB8XT	TNC crimp

MODEL	CONNECTOR TYPE
Models w/ 17' of Teflex™ cable	
MBD	No connector
MBDB	BNC crimp
MBDM	Mini UHF crimp
MBDN	N crimp
MBDNS	N solder
MBDP	UHF (PL259) crimp
MBDPST	UHF (PL259) Teflon® solder
MBDT	TNC crimp
Models with 17' of Teflon® cable	
MBF	No connector
MBFB	BNC crimp
MBFM	Mini UHF crimp
MBFN	N crimp
Models with 17' of ATX195 cable	
MB195	No connector (good for higher frequencies)
Installation Accessories	
P34	Package of six 3/4" hole plugs
MOGSK	Package of six 3/4" mount gaskets
MORNG	Package of O-rings for M mounts

3/8" Hole Brass Mounts*



MODEL	CONNECTOR TYPE
Models w/ 17' of RG58A/U stranded center conductor cable	
MAB8	No connector
MAB8B	BNC crimp
MAB8M	Mini UHF crimp
MAB8N	N crimp
MAB8NS	N solder
MAB8P	UHF (PL259) crimp
MAB8PS	UHF (PL259) solder
MAB8PST	UHF (PL259) Teflon® solder
MAB8T	TNC crimp
Models w/ 17' of RG58U solid center conductor cable	
MAB8U	No connector
MAB8UB	BNC crimp
MAB8UM	Mini UHF crimp
MAB8UN	N crimp
MAB8UNS	N solder
MAB8UP	UHF (PL259) crimp
MAB8UPST	UHF (PL259) Teflon® solder
MAB8UT	TNC crimp

MODEL	CONNECTOR TYPE
Models w/ 17' of RG8X low loss solid center conductor cable	
MAB8X	No connector
MAB8XB	BNC crimp
MAB8XM	Mini UHF crimp
MAB8XN	N crimp
MAB8XNS	N solder
MAB8XP	UHF (PL259) crimp
MAB8XPST	UHF (PL259) Teflon® solder
MAB8XT	TNC crimp
Models w/ 17' of Teflex™ Cable	
MABD	No connector
MABDB	BNC crimp
MABDM	Mini UHF crimp
MABDN	N crimp
MABDNS	N solder
MABDP	UHF (PL259) crimp
MABDPST	UHF (PL259) Teflon® solder
MABDT	TNC crimp


Thick Plane Models* – Up to 1/4"



MODEL	CONNECTOR TYPE
Models w/ 17' of RG58A/U stranded center conductor cable	
MABT8	No connector
MABT8B	BNC crimp
MABT8M	Mini UHF crimp
MABT8N	N crimp
MABT8P	UHF (PL259) crimp
MABT8PS	UHF (PL259) solder

MODEL	CONNECTOR TYPE
Models w/ 17' of RG58U solid center conductor cable	
MABT8U	No connector
MABT8UB	BNC crimp
MABT8UM	Mini UHF crimp
MABT8UN	N crimp
MABT8UP	UHF (PL259) crimp

Thick Plane Models* – Up to 1/2"



MODEL	CONNECTOR TYPE
Models w/ 17' of RG58A/U stranded center conductor cable	
MABVT8	No connector
MABVT8M	Mini UHF crimp
MABVT8B	BNC crimp
MABVT8UP	UHF (PL259) crimp

MODEL	CONNECTOR TYPE
Models w/ 17' of RG58U solid center conductor cable	
MABVT8U	No connector

* All connectors are shipped loose. Choose the "I" option for installed connectors.

ORDERING GUIDE

Mount Style and Hole Size	
M	3/4" steel hole mounts
MAB	3/8" brass hole mounts
MABT	3/8" or 3/4" brass mounts for thick plate up to 1/4"
MABVT	3/8" or 3/4" brass hole mounts adjustable up to 1/2"
MB	3/4" brass hole mounts
MX	3/8" brass snap-in hole mount

Connector Style	
Blank	No connector
B	BNC crimp
M	Mini UHF crimp
N	N crimp
NS	N solder
P	PL259 crimp
PS	PL259 solder
PST	PL259 solder Teflon®
SM	SMA crimp
T	TNC crimp

Cable Style	
8	RG58A/U
8U	RG58U
8X	RG8X "low loss"
D	Teflex™
F	Teflon® coax cable
O	Only (mount only – no cable)

Installation Options	
Blank	Loose connector
I	Installed connector (added cost for crimp or solder)

Cable Length	
Blank	Standard 17-foot cable length
I	Optional 14-foot cable length

Other lengths available upon request.

FEATURES AND BENEFITS



- Corrosion resistant materials used throughout for high durability and weather resistance
- Neoprene seal for moisture protection
- High 80-lb pull strength will allow antenna to stay put
- Optional rubber boot provides additional protection to mounting surface
- Triple reinforced coax strain relief eliminates cable pull out
- 3-1/4" diameter

3/4" Style Magnetic Mounts *

MODEL	CONNECTOR TYPE
Chrome Models with 12' of RG58A/U Stranded Center Cable	
G8	No connector
G8B	BNC crimp
G8BI	BNC crimp, installed
G8MI	Minu UHF crimp, installed
G8N	N crimp
G8NS	N solder
G8P	UHF (PL259) crimp
G8PI	UHF (PL259) crimp, installed
GR8PI	UHF (PL259) crimp, installed
G8PS	UHF (PL259) solder
G9PST	UHF (PL259) Teflon® solder
G8TI	TNC crimp, installed
Chrome Models with 12' of RG58A/U Solid Center Conductor Cable	
G8U	No connector
G8UB	BNC crimp
G8UM	Minu UHF crimp
G8UN	N crimp
G8UNS	N solder
G8UP	UHF (PL259) crimp
G8UPST	UHF (PL259) Teflon® solder
G8UT	TNC crimp

MODEL	CONNECTOR TYPE
Chrome Models with 12' of RG8X Low Loss Cable	
G8X	No connector
G8XBI	BNC crimp, installed
G8XM	Minu UHF crimp
G8XNI	N crimp, installed
G8XNS	N solder
G8XP	UHF (PL259) solder
G8XPST	UHF (PL259) Teflon® solder
Chrome Models with 12' of Teflex™ Cable	
GD	No connector
GDBI	BNC crimp, installed
GDM	Minu UHF crimp
GDNI	N crimp, installed
GDNS	N solder
GDPI	UHF (PL259) solder
GDPST	UHF (PL259) Teflon® solder
GDT	TNC crimp
Black Models with 12' of RG58A/U Stranded Center Cable	
GB8	RG58A/U
GBR8PI	Rubber boot option – RG58A/U w/ PL259 installed

* All connectors are shipped loose. Choose the "I" option for installed connectors.

Mobile-to-Base Converters



This is a value-conscious option for VHF, UHF, 800 MHz, and up applications.

MODEL	CONNECTOR TYPE
MBC	Mobile-to-base converter for VHF and UHF, S0239 terminated
MBCN	Mobile-to-base converter for VHF and UHF, N terminated
MBC800	Mobile-to-base converter for 800 and 900, N terminated
MBC800LBT	Mobile-to-base converter for 800 and up, N terminated



FEATURES AND BENEFITS

- Ideal for small antennas - 2-3/8" diameter
- 50-lb pull strength
- Brass, ceramic magnet, and chrome-plated steel materials are very durable and resist corrosion
- Gold plated contact

3/4" Style Mini Magnetic Mounts *

MODEL	CONNECTOR TYPE
Chrome Models with 12' of RG58A/U Stranded Center Cable	
GM8	No connector
GM8B	BNC crimp
GM8M	Minu UHF crimp
GM8N	N crimp
GM8NS	N solder
GM8P	UHF (PL259) crimp
GM8PI	UHF (PL259) crimp, installed
GM8PS	UHF (PL259) solder
GM9PST	UHF (PL259) Teflon® solder
GM8T	TNC crimp
Chrome Models with 12' of RG58A/U Solid Center Conductor Cable	
GM8U	No connector
GM8UB	BNC crimp
GM8UM	Minu UHF crimp
GM8UN	N crimp
GM8UNS	N solder
GM8UP	UHF (PL259) crimp
GM8UPST	UHF (PL259) Teflon® solder
GM8UT	TNC crimp

MODEL	CONNECTOR TYPE
Chrome Models with 12' of RG8X Low Loss Cable	
GMC	No connector
GMD8	BNC crimp
GMDM	Minu UHF crimp
GMDN	N crimp
GMDNS	N solder
GMDPI	UHF (PL259) crimp, installed
GMDPST	UHF (PL259) Teflon® solder
GMDT	TNC crimp
Black Models with 12' of RG58A/U Stranded Center Cable	
GM88	No connector

Mini Trunk Lid Mounts



FEATURES AND BENEFITS

- Stainless steel brackets and hardware are the ultimate in corrosion resistance
- Elegant design enables proper fit on high tolerance trunk lid seams
- Non staining rubber cushion minimizes scratches and stains
- Gold plated contact

Mini-Trunk Lid Mounts *

MODEL	CONNECTOR TYPE
Models with 17' of RG58A/U Stranded Center Cable	
TM8	No connector
TMB8	No connector
TM8B	BNC crimp
TM8M	Minu UHF crimp
TM8N	N crimp
TM8NS	N solder
TM8P	UHF (PL259) crimp
TM8PS	UHF (PL259) solder
TM8PST	UHF (PL259) Teflon® solder
TM8T	TNC connector

MODEL	CONNECTOR TYPE
Models with 17' of RG58U Solid Center Conductor Cable	
TM8U	No connector
TMB8U	No connector
TM8UB	BNC crimp
TM8UM	Minu UHF crimp
TM8UN	N crimp
TM8UNS	N solder
TM8UP	UHF (PL259) crimp
TM8UPST	UHF (PL259) Teflon® solder
TM8UT	TNC crimp

* All connectors are shipped loose. Choose the "I" option for installed connectors.



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2019 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

sales@lairdconnect.com
support@lairdconnect.com
www.lairdconnect.com

