CE Test Report

Equipment	:	**BTv4.0 Dual Mode USB HCI Module (Please refer to section 1.1.1 for more details)**
Model No.	:	**BT800 (Please refer to section 1.1.1 for more details)**
Brand Name	:	**Laird Connectivity**
Applicant	:	**Laird Connectivity, Inc.**
Address	:	**W66N220 Commerce Court, Cedarburg, WI 53012 United States Of America**
Standard	:	**EN 300 328 V2.2.2 (2019-07)**
Received Date	:	**Apr. 06, 2017**
Tested Date	:	**Feb. 16 ~ Mar. 23, 2016(for original test) Jun. 15 ~ Jun. 22, 2020 (for new test)**

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

Reviewed by: **James Fan / Assistant Manager**

Approved by: **Gary Chang / Manager**

Testing Laboratory 2732

Table of Contents

1 GENERAL DESCRIPTION 5

1.1 Information 5
1.2 Local Support Equipment List 8
1.3 Test Setup Chart 8
1.4 Test Equipment List and Calibration Data 9
1.5 Testing Applied Standards 11
1.6 Measurement Uncertainty 11

2 TEST CONFIGURATION 12

2.1 Testing Condition 12
2.2 Testing Facility 12
2.3 The Worst Test Modes and Channel Details 13

3 TRANSMITTER TEST RESULTS 14

3.1 RF Output Power 14
3.2 Accumulated Transmit Time, Minimum Frequency Occupation and Hopping Sequence 16
3.3 Hopping Frequency Separation 19
3.4 Occupied Channel Bandwidth 20
3.5 Transmitter Unwanted Emissions in the Out-Of-Band Domain 21
3.6 Transmitter Unwanted Emissions In The Spurious Domain 26

4 RECEIVER TEST RESULTS 60

4.1 Receiver Spurious Emissions 60

5 RECEIVER BLOCKING TEST RESULTS 94

5.1 Receiver Blocking 94

6 PHOTOGRAPHS OF THE TEST CONFIGURATION 98

7 TEST LABORATORY INFORMATION 101

Release Record

Report No.	Version	Description	Issued Date
ER490301-04AD	Rev. 01	Initial issue	Aug. 03, 2020

Summary of Test Results

Ref. Std. Clause	Test Items	Measured	Result
4.3.1.2	RF Output Power	EIRP (dBm): 9.95	Pass
4.3.1.3	Duty cycle, Tx-Sequence, Tx-gap	Only for non-adaptive equipment	N/A
4.3.1.4	Dwell time, Minimum Frequency Occupation & Hopping Sequence	Meet the requirement of limit.	Pass
4.3.1.5	Hopping Frequency Separation	Meet the requirement of limit.	Pass
4.3.1.6	Medium Utilisation (MU) factor	Only for non-adaptive equipment	N/A
4.3.1.7	Adaptivity	The RF Output power is less than 10 dBm e.i.r.p. This item is not applicable	N/A
4.3.1.8	Occupied Channel Bandwidth	Meet the requirement of limit.	Pass
4.3.1.9	Transmitter unwanted emissions in the out of band domain	Meet the requirement of limit.	Pass
4.3.1.10	Transmitter unwanted emissions in the spurious domain	Meet the requirement of limit.	Pass
4.3.1.11	Receiver spurious emissions	Meet the requirement of limit.	Pass
4.3.1.12	Receiver Blocking	Meet the requirement of limit.	Pass
4.3.1.13	Geo-location capability	The device has no geo-location capability.	N/A

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

This report is issued as a supplementary report to original ICC report no. ER490301-03AD, ER362601-04AD. The difference is concerned with following items:

- ✧ Updating standard version from V2.1.1 to V2.2.2.
- ✧ Remove model BT810
- ✧ Change brand, applicant and address.

Therefore, related test items had been performed and presented in the following sections.

1.1.1 Product Details

The following models are provided to this EUT.

Model Name	Description	Difference
BT800	BTv4.0 Dual Mode USB HCI Module	-
BT820	BTv4.0 Dual Mode USB Dongle	BT800 module mounted onto a carrier board with USB connector and enclosed in plastics to allow external use.
BT800-ST	BTv4.0 Dual Mode USB HCI Module – External Antenna variant	BT800 module mounted onto a PCB carrier board with external chip antenna.
✦ The above models, only BT800-ST, BT820 is elected as representative one for additional external antenna and only its data was recorded in this report.		

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	**Bluetooth Mode**	**Ch. Frequency (MHz)**	**Channel Number**	**Data Rate**
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	3 Mbps
Note 1: Bluetooth BR uses a GFSK modulation. Note 2: Bluetooth EDR uses a combination of π/4-DQPSK and 8DPSK modulation.				

1.1.3 Antenna Details

Ant. No.	Brand	Model	Type	Gain (dBi)	Connector	Remark
1	ACX	AT3216-B2R7HAA_3216	Chip	0.5	N/A	For BT800 & BT820
2	ACX	AT3216-B2R7HAA	Chip	0.5	UFL	For BT800-ST

1.1.4 EUT Operational Condition

Power Supply Type	5Vdc from host		
SW Version	V02		
Operational Climatic	☒ Tnom (20°C)	☒ Tmax (85°C)	☒ Tmin (-40°C)

1.1.5 Accessories

N/A

1.1.6 Channel List

Frequency band (MHz)				**2400~2483.5**			
Channel	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**	**Channel**	**Frequency (MHz)**
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	--	--

1.1.7 Test Tool and Duty Cycle

Configuration 1 BT800-ST

Test Tool	BlueTest3
Duty Cycle Of Test Signal (%)	78.51% - BR 78.91% - EDR
Duty Factor (dB)	1.05 - BR 1.03 - EDR

Configuration 2: BT820

Test Tool	CSR BlueSuite 2.5.0
Duty Cycle Of Test Signal (%)	78.46% - BR 78.76% - EDR
Duty Factor (dB)	1.05 - BR 1.04 - EDR

1.1.8 Power Setting

Modulation Mode	**Test Frequency (MHz)**		
	2402	**2441**	**2480**
BR-1Mbps	63	63	63
EDR-3Mbps	63	63	63

1.2 Local Support Equipment List

Support Equipment List					
No.	**Equipment**	**Brand**	**Model**	**FCC ID**	**Signal cable / Length (m)**
1	Notebook	DELL	Latitude E6430	DoC	USB, 1.2m shielded
2	Fixture	---	---	---	---

1.3 Test Setup Chart

Test Setup Diagram (Model: BT800-ST)



1. USB, 1.2m shielded

Test Setup Diagram (Model: BT820)



1.4 Test Equipment List and Calibration Data

Test Item	Radiated Emissions below 1GHz				
Test Site	Fully-anechoic chamber 1 / (05CH01-WS)				
Tested Date	Jun. 16 ~ Jun. 22, 2020				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	Agilent	N9010A	MY54200247	Oct. 07, 2019	Oct. 06, 2020
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Nov. 04, 2019	Nov. 03, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1094	Nov. 04, 2019	Nov. 03, 2020
Preamplifier	Agilent	83017A	MY39501310	Nov. 27, 2019	Nov. 26, 2020
Preamplifier	EMC	EMC02325	980146	Oct. 18, 2019	Oct. 17, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY22626/4	Oct. 14, 2019	Oct. 13, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16608/4	Oct. 14, 2019	Oct. 13, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY15686/4	Oct. 14, 2019	Oct. 13, 2020
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-005	Oct. 14, 2019	Oct. 13, 2020
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-006	Oct. 14, 2019	Oct. 13, 2020
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Receiver Blocking				
Test Site	(05CH01-WS)				
Tested Date	Jun. 15, 2020				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Wireless connectivity tester	ROHDE&SCHWARZ	CMW270	100856	Oct. 24, 2019	Oct. 23,2020
Signal Generator	ROHDE&SCHWARZ	SMB100A	175727	Dec. 27, 2019	Dec. 26, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX_104	500202/4	Oct. 16, 2019	Oct. 15, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX_104	296088/4	Oct. 16, 2019	Oct. 15, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX_104	329023/4	Oct. 16, 2019	Oct. 15, 2020
Combiner(1X2)	WOKEN	2WAYDIV	12101200003	Oct. 16, 2019	Oct. 15, 2020
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emissions above 1GHz				
Test Site	Fully-anechoic chamber 2 / (05CH02-WS)				
Tested Date	Feb. 16 ~ Mar. 22, 2016				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	Agilent	N9010A	MY52221474	Sep. 08, 2015	Sep. 07, 2016
Bilog Antenna 30-1000MHz	SCHWARZBECK	VULB9168	9168-563	Dec. 29, 2015	Dec. 28, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	9120D-1205	Jan. 08, 2016	Jan. 07, 2017
Preamplifier	Agilent	83017A	MY53270013	Jan. 27, 2016	Jan. 26, 2017
Preamplifier 30-1000MHz	EMC	EMC02325	980188	Dec. 10, 2015	Dec. 09, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22622/4	Dec. 04, 2015	Dec. 03, 2016
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22623/4	Dec. 04, 2015	Dec. 03, 2016
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22621/4	Dec. 04, 2015	Dec. 03, 2016
RF cable-4M	HUBER+SUHNER	SUCOFLEX104	MY22579/4	Dec. 04, 2015	Dec. 03, 2016
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-002	Dec. 04, 2015	Dec. 03, 2016
LF cable-3M	EMC	EMC8D-NM-NM-3000	131102	Dec. 04, 2015	Dec. 03, 2016
LF cable-10M	EMC	EMC8D-NM-NM-10000	131101	Dec. 04, 2015	Dec. 03, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Feb.17~ Mar. 23, 2016				
Instrument	**Manufacturer**	**Model No.**	**Serial No.**	**Calibration Date**	**Calibration Until**
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40	101486	Oct. 14, 2015	Oct. 13, 2016
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 27, 2015	Nov. 26, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
DC POWER SOURCE	GW INSTEK	GPC-3060D	EM884797	Oct. 20, 2015	Oct. 19, 2016
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 26, 2015	Oct. 25, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Measurement Software	Agilent	EN RF test	1.1501125	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

EN 300 328 V2.2.2 (2019-07)

1.6 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Uncertainty		
Parameters	**Uncertainty**	**Limit**
Occupied Channel Bandwidth	±0.0034 %	±5 %
RF output power, conducted	±0.592 dB	±1.5 dB
Power Spectral Density, conducted	±0.583 dB	±3 dB
Unwanted Emissions, conducted	±2.715 dB	±3 dB
All emissions, radiated	±3.14 dB	±6 dB
Temperature	±0.4 ^{o}C	±3 °C
Supply voltages	±0.15 %	±3 %
Time	±0.1 %	±5 %

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
RF Conducted	TH01-WS	22.5°C / 63% 22.1°C / 61%	Jack Li
Radiated Emission≤1GHz	05CH01-WS	24°C / 60%	Nai Xu
Radiated Emission>1GHz	05CH02-WS	24°C / 60% 19°C / 70%	Ryan Lee
Receiver Blocking	05CH01-WS	25°C / 65%	Jack Li

2.2 Testing Facility

Test Laboratory	International Certification Corp.
Test Site	TH01-WS, 05CH01-WS
Address of Test Site (Kwei Shan)	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.
Test Site	05CH02-WS
Address of Test Site (Kwei Shan II)	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

2.3 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
RF Output Power	GFSK 8DPSK	Hopping Hopping	1 Mbps 3 Mbps	1, 2
Accumulated Transmit Time Minimum Frequency Occupation Hopping Sequence	GFSK 8DPSK	Hopping Hopping	1 Mbps 3 Mbps	1, 2
Hopping Frequency Separation	GFSK 8DPSK	two-adjacent	1 Mbps 3 Mbps	1, 2
Occupied Channel Bandwidth	GFSK 8DPSK	2402 / 2480 2402 / 2480	1 Mbps 3 Mbps	1, 2
Transmitter unwanted emissions in the OOB domain	GFSK 8DPSK	Hopping Hopping	1 Mbps 3 Mbps	1, 2
Transmitter Spurious Emissions≤1GHz Receiver Spurious Emissions≤1GHz	GFSK 8DPSK	2402 / 2480 2402 / 2480	1 Mbps 3 Mbps	1, 2
Transmitter Spurious Emissions>1GHz Receiver Spurious Emissions>1GHz	GFSK 8DPSK	2402 / 2480 2402 / 2480	1 Mbps 3 Mbps	1, 2
Receiver Blocking	GFSK	Hopping	1 Mbps	1

NOTE:
1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** result was found as the worst case and was shown in this report.
2. 2 types EUT were selected to perform configuration
   1) Configuration 1 : BT800-ST
   2) Configuration 2 : BT820

3 Transmitter Test Results

3.1 RF Output Power

3.1.1 Limit of RF Output Power

The maximum RF output power shall be equal to or less than 20 dBm

3.1.2 Test Procedures

Reference to clause 5.4.2.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.1.3 Test Setup



3.1.4 Test Result of RF Output Power

Configuration 1 BT800-ST

Condition	Modulation Mode	Freq. (MHz)	EIRP Power	Limit (dBm)
TnomVnom	BR-1Mbps	Hopping	9.22	20
TminVnom	BR-1Mbps	Hopping	**9.65**	20
TmaxVnom	BR-1Mbps	Hopping	7.75	20
TnomVnom	EDR-3Mbps	Hopping	6.70	20
TminVnom	EDR-3Mbps	Hopping	7.11	20
TmaxVnom	EDR-3Mbps	Hopping	5.34	20

Configuration 2: BT820

Condition	Modulation Mode	Freq. (MHz)	EIRP Power	Limit (dBm)
TnomVnom	BR-1Mbps	Hopping	8.44	20
TminVnom	BR-1Mbps	Hopping	**9.95**	20
TmaxVnom	BR-1Mbps	Hopping	7.09	20
TnomVnom	EDR-3Mbps	Hopping	5.49	20
TminVnom	EDR-3Mbps	Hopping	6.98	20
TmaxVnom	EDR-3Mbps	Hopping	4.16	20

3.2 Accumulated Transmit Time, Minimum Frequency Occupation and Hopping Sequence

3.2.1 Limit of Accumulated Transmit Time, Minimum Frequency Occupation and Hopping Sequence

Adaptive mode

Adaptive Frequency Hopping equipment shall be capable of operating over a minimum of 70 % of the band 2.4GHz to 2.4835GHz. The Accumulated Transmit Time on any hopping frequency shall not be greater than 400 ms within any observation period of 400 ms multiplied by the minimum number of hopping frequencies (N) that have to be used. In order for the equipment to comply with the Frequency Occupation requirement, it shall meet either of the following two options:

Option 1: Each hopping frequency of the hopping sequence shall be occupied at least once within a period not exceeding four times the product of the dwell time and the number of hopping frequencies in use.

Option 2: The occupation probability for each frequency shall be between ((1 / U) × 25 %) and 77 % where U is the number of hopping frequencies in use. The hopping sequence(s) shall contain at least N hopping frequencies at all times, where N is 15 or 15 divided by the minimum Hopping Frequency Separation in MHz, whichever is the greater.

Non-Adaptive mode

The Accumulated Transmit Time on any hopping frequency shall not be greater than 15 ms within any observation period of 15 ms multiplied by the minimum number of hopping frequencies (N) that have to be used. Non-adaptive medical devices requiring reverse compatibility with other medical devices placed on the market that are compliant with version 1.7.1 or earlier versions of ETSI EN 300 328, are allowed to have an operating mode in which the maximum Accumulated Transmit Time is 400 ms within any observation period of 400 ms multiplied by the minimum number of hopping frequencies (N) that have to be used, only when communicating to these legacy devices already placed on the market. In order for the equipment to comply with the Frequency Occupation requirement, it shall meet either of the following two options:

Option 1: Each hopping frequency of the hopping sequence shall be occupied at least once within a period not exceeding four times the product of the dwell time and the number of hopping frequencies in use.

Option 2: The occupation probability for each frequency shall be between ((1 / U) × 25 %) and 77 % where U is the number of hopping frequencies in use. The hopping sequence(s) shall contain at least N hopping frequencies where N is 15 or 15 divided by the minimum Hopping Frequency Separation in MHz, whichever is the greater.

3.2.2 Test Procedures

Reference to clause 5.4.4.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.2.3 Test Setup



Configuration 1 BT800-ST

3.2.4 Test Result of Hopping Sequence

Modulation Mode	Freq. (MHz)	Hopping Mode	Hopping Channels	Hopping Channels Limits	F_l 20dB (MHz)	F_h 20dB (MHz)	Min. Hopping Range (%)	Min. Hopping Range Limit (%)
BR-1Mbps	Hopping	Non-AFH	79	15	N/A	N/A	N/A	N/A
EDR-3Mbps	Hopping	AFH	20	20	2415	2479	82.05%	70.00%

3.2.5 Test Result of Accumulated Transmit Time

Modulation Mode	Freq. (MHz)	Hopping Mode	Worst Duty Cycle Data Packet	Minimum Number of Hop Freq. (N)	Dwell Time per Hop (ms)	Number of Hop in [N x MDT]	[N x MDT] (s)	Dwell Time in [N x MDT] (ms)	Max. Dwell Time (MDT) Limit (ms)
BR-1Mbps	Hopping	Non-AFH	DH5	79	2.96	106.6	31.6	315.11	400.00
EDR-3Mbps	Hopping	AFH	DH5	20	2.97	106.6	8	316.71	400.00

3.2.6 Test Result of Minimum Frequency Occupation

Modulation Mode	Freq. (MHz)	Hopping Mode	Worst Duty Cycle Data Packet	Actual No. of Hopping Freq. (N)	Dwell Time per Hop (ms)	No. of Hop in [4 x dwell time per hop x N]	[4 x dwell time per hop x N] (ms)	Dwell Time in [4 x dwell time per hop x N] (ms)	Min. No. of Hopping Limit in [4 x dwell time per hop x N]
BR-1Mbps	Hopping	Non-AFH	DH5	79	2.956	3.16	934.10	9.34	1
EDR-3Mbps	Hopping	AFH	3-DH5	20	2.971	3.16	237.68	9.39	1

Configuration 2: BT820

3.2.7 Test Result of Hopping Sequence

Modulation Mode	Freq. (MHz)	Hopping Mode	Hopping Channels	Hopping Channels Limits	F_l 20dB (MHz)	F_h 20dB (MHz)	Min. Hopping Range (%)	Min. Hopping Range Limit (%)
BR-1Mbps	Hopping	Non-AFH	79	15	N/A	N/A	N/A	N/A
EDR-3Mbps	Hopping	AFH	20	20	2417	2478	78.21%	70.00%

3.2.8 Test Result of Accumulated Transmit Time

Modulation Mode	Freq. (MHz)	Hopping Mode	Worst Duty Cycle Data Packet	Minimum Number of Hop Freq. (N)	Dwell Time per Hop (ms)	Number of Hop in [N x MDT]	[N x MDT] (s)	Dwell Time in [N x MDT] (ms)	Max. Dwell Time (MDT) Limit (ms)
BR-1Mbps	Hopping	Non-AFH	DH5	79	2.96	106.6	31.6	315.16	400.00
EDR-3Mbps	Hopping	AFH	DH5	20	2.96	106.6	8	315.16	400.00

3.2.9 Test Result of Minimum Frequency Occupation

Modulation Mode	Freq. (MHz)	Hopping Mode	Worst Duty Cycle Data Packet	Actual No. of Hopping Freq. (N)	Dwell Time per Hop (ms)	No. of Hop in [4 x dwell time per hop x N]	[4 x dwell time per hop x N] (ms)	Dwell Time in [4 x dwell time per hop x N] (ms)	Min. No. of Hopping Limit in [4 x dwell time per hop x N]
BR-1Mbps	Hopping	Non-AFH	DH5	79	2.9565	3.15	934.25	9.31	1
EDR-3Mbps	Hopping	AFH	3-DH5	20	2.9565	3.15	236.52	9.31	1

3.3 Hopping Frequency Separation

3.3.1 Limit of Hopping Frequency Separation

For adaptive Frequency Hopping equipment, the minimum Hopping Frequency Separation shall be 100 kHz. For non-adaptive Frequency Hopping equipment, the Hopping Frequency Separation shall be equal or greater than the Occupied Channel Bandwidth, with a minimum separation of 100 kHz.

3.3.2 Test Procedures

Reference to clause 5.4.5.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.3.3 Test Setup



3.3.4 Test Result of Hopping Frequency Separation

Configuration 1 BT800-ST

Modulation Mode	Freq. (MHz)	Hopping Mode	$F2402_{PK}$ (MHz)	$F2403_{PK}$ (MHz)	F_{HS} (MHz)	Limit F_{HS} (kHz)
BR-1Mbps	two-adjacent	Non-AFH	2401.9747	2402.9732	0.9985	100
EDR-3Mbps	two-adjacent	AFH	2401.992	2402.9906	0.9986	100

Configuration 2: BT820

Modulation Mode	Freq. (MHz)	Hopping Mode	$F2402_{PK}$ (MHz)	$F2403_{PK}$ (MHz)	F_{HS} (MHz)	Limit F_{HS} (kHz)
BR-1Mbps	two-adjacent	Non-AFH	2401.979	2402.9776	0.9986	100
EDR-3Mbps	two-adjacent	AFH	2402.0007	2402.9906	0.9899	100

3.4 Occupied Channel Bandwidth

3.4.1 Limit of Occupied Channel Bandwidth

The Occupied Channel Bandwidth for each hopping frequency shall fall completely within 2.4~2.4835 GHz. For non-adaptive Frequency Hopping equipment with e.i.r.p greater than 10 dBm, the Occupied Channel Bandwidth for every occupied hopping frequency shall be equal to or less than the value declared by the supplier. This declared value shall not be greater than 5 MHz.

3.4.2 Test Procedures

Reference to clause 5.4.7.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.4.3 Test Setup



3.4.4 Test Result of Occupied Channel Bandwidth

Configuration 1 BT800-ST

Modulation Mode	Frequency (MHz)	99% Bandwidth (MHz)	F_L at 99% BW (MHz)	F_H at 99% BW (MHz)	20dB Bandwidth (MHz)	Limit F_L / F_H (MHz)
BR-1Mbps	2402	0.88	2401.55	2402.44	0.94	2400.0
BR-1Mbps	2480	0.87	2479.55	2480.42	0.94	2483.5
EDR-3Mbps	2402	1.21	2401.39	2402.60	1.36	2400.0
EDR-3Mbps	2480	1.23	2479.37	2480.60	1.37	2483.5

Configuration 2: BT820

Modulation Mode	Frequency (MHz)	99% Bandwidth (MHz)	F_L at 99% BW (MHz)	F_H at 99% BW (MHz)	20dB Bandwidth (MHz)	Limit F_L / F_H (MHz)
BR-1Mbps	2402	0.88	2401.56	2402.44	0.93	0.88
BR-1Mbps	2480	0.88	2479.55	2480.43	0.94	0.88
EDR-3Mbps	2402	1.21	2401.39	2402.6	1.36	1.21
EDR-3Mbps	2480	1.21	2479.37	2480.59	1.37	1.21

3.5 Transmitter Unwanted Emissions in the Out-Of-Band Domain

3.5.1 Limit of Transmitter Unwanted Emissions in the Out-Of-Band Domain



3.5.2 Test Procedures

Reference to clause 5.4.8.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.5.3 Test Setup



3.5.4 Test Result of Transmitter Unwanted Emissions in the Out-Of-Band Domain

Configuration 1 BT800-ST

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
TnomVnom	BR-1Mbps	Hopping	2399.50	-40.97	-10
TnomVnom	BR-1Mbps	Hopping	2398.50	-53.62	-20
TnomVnom	BR-1Mbps	Hopping	2484.00	-56.02	-10
TnomVnom	BR-1Mbps	Hopping	2485.00	-55.85	-20

Low Band	Up Band
	

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
TnomVnom	EDR-3Mbps	Hopping	2399.50	-50.87	-10
TnomVnom	EDR-3Mbps	Hopping	2398.30	-57.01	-20
TnomVnom	EDR-3Mbps	Hopping	2484.00	-55.21	-10
TnomVnom	EDR-3Mbps	Hopping	2485.23	-57.95	-20
Low Band			**Up Band**		





Configuration 2: BT820

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
TnomVnom	BR-1Mbps	Hopping	2399.5	-40.92	-10
TnomVnom	BR-1Mbps	Hopping	2398.5	-54.07	-20
TnomVnom	BR-1Mbps	Hopping	2484.00	-57.06	-10
TnomVnom	BR-1Mbps	Hopping	2485.00	-56.79	-20

Low Band	Up Band
	

Condition	Modulation Mode	Freq. (MHz)	OOB Freq. (MHz)	OOB Emissions (dBm)	Limit (dBm)
TnomVnom	EDR-3Mbps	Hopping	2399.5.0	-52.47	-10
TnomVnom	EDR-3Mbps	Hopping	2398.29	-57.95	-20
TnomVnom	EDR-3Mbps	Hopping	2484.00	-57.94	-10
TnomVnom	EDR-3Mbps	Hopping	2485.21	-59.53	-20
Low Band			**Up Band**		





3.6 Transmitter Unwanted Emissions In The Spurious Domain

3.6.1 Limit of Transmitter Unwanted Emissions In The Spurious Domain

Frequency Range (MHz)	Maximum power (dBm)	Bandwidth (kHz)
30 to 47	-36	100
47 to 74	-54	100
74 to 87.5	-36	100
87.5 to 118	-54	100
118 to 174	-36	100
174 to 230	-54	100
230 to 470	-36	100
470 to 694	-54	100
694 to 1000	-36	100
1000 to 12750	-30	1000

3.6.2 Test Procedures

Reference to clause 5.4.9.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.6.3 Test Setup

Below 1GHz



Above 1 GHz



Configuration 1 BT800-ST

3.6.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	93.05	-71.51	-54.00	-17.51	-7.04	-64.47
2	207.51	-62.47	-54.00	-8.47	-4.07	-58.40
3	631.45	-68.70	-54.00	-14.70	6.82	-75.52

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	219.15	-66.76	-54.00	-12.76	-4.49	-62.27
2	589.69	-69.98	-54.00	-15.98	6.12	-76.10
3	634.13	-68.50	-54.00	-14.50	6.52	-75.02

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	93.05	-71.22	-54.00	-17.22	-7.04	-64.18
2	213.33	-58.06	-54.00	-4.06	-4.07	-53.99
3	682.72	-68.44	-54.00	-14.44	7.89	-76.33

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	52.31	-64.42	-54.00	-10.42	0.03	-64.45
2	213.33	-64.32	-54.00	-10.32	-4.90	-59.42
3	682.72	-68.55	-54.00	-14.55	7.30	-75.85

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	93.05	-71.64	-54.00	-17.64	-7.04	-64.60
2	210.42	-65.15	-54.00	-11.15	-4.24	-60.91
3	682.72	-68.65	-54.00	-14.65	7.89	-76.54

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	52.31	-66.37	-54.00	-12.37	-0.79	-65.58
2	195.87	-67.17	-54.00	-13.17	-3.98	-63.19
3	683.69	-69.07	-54.00	-15.07	7.41	-76.48

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	93.05	-71.34	-54.00	-17.34	-7.04	-64.30
2	208.48	-60.23	-54.00	-6.23	-4.15	-56.08
3	682.72	-69.67	-54.00	-15.67	7.89	-77.56

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV
1	52.31	-66.51	-54.00	-12.51	0.03	-66.54
2	213.33	-69.14	-54.00	-15.14	-4.90	-64.24
3	682.72	-69.60	-54.00	-15.60	7.30	-76.90

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.6.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4803.92	-31.65	-30.00	-1.65	11.64	-43.29

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.07	-32.83	-30.00	-2.83	11.89	-44.72

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4959.88	-38.27	-30.00	-8.27	12.23	-50.50

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4959.88	-38.85	-30.00	-8.85	11.66	-50.51

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.18	-37.54	-30.00	-7.54	11.64	-49.18

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.12	-38.67	-30.00	-8.67	11.89	-50.56

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4960.06	-43.22	-30.00	-13.22	12.23	-55.45

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4960.16	-43.78	-30.00	-13.78	11.66	-55.44

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Configuration 2: BT820

3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	158.04	-60.54	-36.00	-24.54	0.36	-60.90
2	514.62	-67.33	-54.00	-13.33	3.99	-71.32
3	664.38	-66.78	-54.00	-12.78	6.70	-73.48

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	59.10	-61.86	-54.00	-7.86	-2.64	-59.22
2	602.62	-66.56	-54.00	-12.56	7.34	-73.90
3	664.38	-66.64	-54.00	-12.64	7.04	-73.68

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	59.10	-63.91	-54.00	-9.91	-1.50	-62.41
2	528.58	-69.80	-54.00	-15.80	4.36	-74.16
3	724.52	-66.41	-36.00	-30.41	8.62	-75.03

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	59.10	-60.98	-54.00	-6.98	-2.64	-58.34
2	664.38	-66.48	-54.00	-12.48	7.04	-73.52
3	831.22	-64.64	-36.00	-28.64	9.93	-74.57

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	158.20	-60.79	-36.00	-24.79	0.37	-61.16
2	514.41	-67.16	-54.00	-13.16	3.99	-71.15
3	664.23	-66.50	-54.00	-12.50	6.69	-73.19

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	59.23	-61.52	-54.00	-7.52	-2.63	-58.89
2	602.20	-66.95	-54.00	-12.95	7.31	-74.26
3	664.10	-65.77	-54.00	-11.77	7.03	-72.80

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	59.23	-63.96	-54.00	-9.96	-1.54	-62.42
2	528.65	-69.45	-54.00	-15.45	4.37	-73.82
3	724.40	-66.12	-36.00	-30.12	8.62	-74.74

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	59.20	-60.53	-54.00	-6.53	-2.64	-57.89
2	664.23	-66.00	-54.00	-12.00	7.04	-73.04
3	831.56	-64.15	-36.00	-28.15	9.94	-74.09

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.28	-43.91	-30.00	-13.91	11.64	-55.55
2	7205.31	-44.99	-30.00	-14.99	17.38	-62.37

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.06	-47.78	-30.00	-17.78	11.89	-59.67
2	7206.68	-43.36	-30.00	-13.36	17.17	-60.53

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4959.77	-38.06	-30.00	-8.06	12.23	-50.29
2	7439.46	-40.73	-30.00	-10.73	17.00	-57.73

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4959.66	-44.86	-30.00	-14.86	11.66	-56.52
2	7440.03	-41.36	-30.00	-11.36	17.71	-59.07

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.37	-44.28	-30.00	-14.28	11.64	-55.92
2	7206.79	-42.89	-30.00	-12.89	17.38	-60.27

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.29	-48.57	-30.00	-18.57	11.89	-60.46
2	7206.57	-44.76	-30.00	-14.76	17.17	-61.93

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4960.42	-38.56	-30.00	-8.56	12.23	-50.79
2	7440.14	-42.21	-30.00	-12.21	17.00	-59.21

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4959.59	-44.90	-30.00	-14.90	11.66	-56.56
2	7440.78	-42.87	-30.00	-12.87	17.71	-60.58

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4 Receiver Test Results

4.1 Receiver Spurious Emissions

4.1.1 Limit of Receiver Spurious Emissions

Frequency Range	Maximum power (dBm)	Measurement bandwidth(kHz)
30 MHz to 1 GHz	-57	100
Above 1 GHz to 12,75 GHz	-47	1000

4.1.2 Test Procedures

Reference to clause 5.4.10.2 of ETSI EN 300 328 V2.2.2 (2019-07).

4.1.3 Test Setup

Below 1GHz



Above 1 GHz



Configuration 1 BT800-ST

4.1.4 Receiver Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	225.94	-64.03	-57.00	-7.03	-3.61	-60.42
2	461.65	-71.33	-57.00	-14.33	2.99	-74.32
3	782.72	-65.02	-57.00	-8.02	9.13	-74.15

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	207.51	-61.80	-57.00	-4.80	-4.44	-57.36
2	438.37	-72.66	-57.00	-15.66	2.81	-75.47
3	727.43	-67.79	-57.00	-10.79	8.54	-76.33

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	225.94	-64.03	-57.00	-7.03	-3.61	-60.42
2	461.65	-71.33	-57.00	-14.33	2.99	-74.32
3	782.72	-65.02	-57.00	-8.02	9.13	-74.15

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	206.44	-62.82	-57.00	-5.82	-4.55	-58.27
2	439.20	-72.24	-57.00	-15.24	2.84	-75.08
3	725.15	-66.91	-57.00	-9.91	8.43	-75.34

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	226.94	-63.24	-57.00	-6.24	-3.48	-59.76
2	461.76	-71.38	-57.00	-14.38	2.99	-74.37
3	782.57	-64.71	-57.00	-7.71	9.13	-73.84

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	207.65	-61.72	-57.00	-4.72	-4.43	-57.29
2	438.52	-72.87	-57.00	-15.87	2.81	-75.68
3	727.53	-68.03	-57.00	-11.03	8.54	-76.57

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	225.13	-64.11	-57.00	-7.11	-3.71	-60.40
2	461.53	-71.74	-57.00	-14.74	2.99	-74.73
3	782.21	-65.06	-57.00	-8.06	9.12	-74.18

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	206.35	-62.75	-57.00	-5.75	-4.56	-58.19
2	439.35	-72.60	-57.00	-15.60	2.85	-75.45
3	725.51	-66.60	-57.00	-9.60	8.44	-75.04

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4.1.5 Receiver Radiated Unwanted Emissions (Above 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4803.63	-51.77	-47.00	-4.77	11.64	-63.41

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4803.42	-52.07	-47.00	-5.07	11.90	-63.97

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4959.94	-50.93	-47.00	-3.93	12.23	-63.16

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4960.49	-52.25	-47.00	-5.25	11.66	-63.91

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4803.45	-52.53	-47.00	-5.53	11.64	-64.17

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4803.37	-53.14	-47.00	-6.14	11.90	-65.04

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4959.62	-52.49	-47.00	-5.49	43.34	-95.83

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4960.97	-52.88	-47.00	-5.88	42.78	-95.66

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Configuration 2: BT820

4.1.6 Receiver Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	159.98	-61.90	-57.00	-4.90	-0.74	-61.16
2	664.38	-67.47	-57.00	-10.47	6.68	-74.15
3	926.28	-64.58	-57.00	-7.58	11.38	-75.96

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	64.92	-60.22	-57.00	-3.22	-2.10	-58.12
2	336.52	-67.35	-57.00	-10.35	0.09	-67.44
3	666.32	-65.33	-57.00	-8.33	7.04	-72.37

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	159.98	-62.11	-57.00	-5.11	-0.74	-61.37
2	515.00	-68.69	-57.00	-11.69	4.08	-72.77
3	823.46	-65.37	-57.00	-8.37	10.01	-75.38

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	59.10	-59.80	-57.00	-2.80	-1.79	-58.01
2	580.96	-67.17	-57.00	-10.17	6.08	-73.25
3	833.16	-65.09	-57.00	-8.09	10.27	-75.36

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	159.78	-62.01	-57.00	-5.01	-0.77	-61.24
2	664.45	-67.51	-57.00	-10.51	6.68	-74.19
3	926.64	-64.21	-57.00	-7.21	11.41	-75.62

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	64.23	-60.32	-57.00	-3.32	-2.07	-58.25
2	336.43	-67.43	-57.00	-10.43	0.08	-67.51
3	666.26	-65.65	-57.00	-8.65	7.04	-72.69

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	159.56	-61.94	-57.00	-4.94	-0.79	-61.15
2	515.23	-67.99	-57.00	-10.99	4.08	-72.07
3	823.32	-65.46	-57.00	-8.46	10.03	-75.49

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	59.23	-59.47	-57.00	-2.47	-1.82	-57.65
2	580.53	-67.28	-57.00	-10.28	6.08	-73.36
3	833.20	-64.82	-57.00	-7.82	10.27	-75.09

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4.1.7 Receiver Radiated Unwanted Emissions (Above 1GHz)

Modulation	GFSK	**Test Freq. (MHz)**	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2336.00	-59.40	-47.00	-12.40	4.63	-64.03
2	3200.00	-60.43	-47.00	-13.43	6.80	-67.23
3	6424.00	-61.49	-47.00	-14.49	15.09	-76.58

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2440.00	-54.47	-47.00	-7.47	4.22	-58.69
2	4660.00	-60.74	-47.00	-13.74	10.53	-71.27
3	6344.00	-61.87	-47.00	-14.87	14.67	-76.54

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	1987.00	-52.48	-47.00	-5.48	2.87	-55.35
2	3773.00	-54.34	-47.00	-7.34	8.72	-63.06
3	5747.00	-50.98	-47.00	-3.98	13.66	-64.64

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2294.00	-56.60	-47.00	-9.60	4.54	-61.14
2	3576.00	-55.16	-47.00	-8.16	7.57	-62.73
3	6252.00	-50.46	-47.00	-3.46	13.72	-64.18

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2336.10	-56.77	-47.00	-9.77	4.63	-61.40
2	3201.00	-55.99	-47.00	-8.99	6.81	-62.80
3	6423.00	-48.35	-47.00	-1.35	15.09	-63.44

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2441.00	-52.41	-47.00	-5.41	4.22	-56.63
2	4656.00	-52.00	-47.00	-5.00	10.52	-62.52
3	6344.20	-48.94	-47.00	-1.94	14.68	-63.62

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	1987.00	-52.48	-47.00	-5.48	2.87	-55.35
2	3773.21	-53.70	-47.00	-6.70	8.72	-62.42
3	5746.54	-50.73	-47.00	-3.73	13.66	-64.39

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	2293.21	-56.82	-47.00	-9.82	4.54	-61.36
2	3575.20	-54.89	-47.00	-7.89	7.57	-62.46
3	6252.21	-50.22	-47.00	-3.22	13.72	-63.94

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)
Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

5 Receiver Blocking Test Results

5.1 Receiver Blocking

5.1.1 Limit of Receiver Blocking

Receiver Blocking Parameters for Receiver Category 1 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm) (see notes 1 and 4)	**Blocking Signal Frequency (MHz)**	**Blocking Signal Power (dBm) (see note 4)**	**Type of Blocking Signal**
(-133 dBm + 10 × log10(OCBW)) or -68 dBm whichever is less (see note 2)	2 380 2 504	-34	CW
(-139 dBm + 10 × log10(OCBW)) or -74 dBm whichever is less (see note 3)	2 300 2 330 2 360 2 524 2 584 2 674		

Note 1: OCBW is in Hz.
Note 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P_{min} + 26 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.
Note 3: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P_{min} + 20 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.
Note 4: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned.

Receiver Blocking Parameters for Receiver Category 2 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm) (see notes 1 and 3)	**Blocking Signal Frequency (MHz)**	**Blocking Signal Power (dBm) (see note 3)**	**Type of Blocking Signal**
(-139 dBm + 10 × log10(OCBW) + 10 dB) or (-74 dBm + 10 dB) whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW
Note 1: OCBW is in Hz. Note 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P_{min} + 26 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal. Note 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned.			

Receiver Blocking Parameters for Receiver Category 3 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm) (see notes 1 and 3)	**Blocking Signal Frequency (MHz)**	**Blocking Signal Power (dBm) (see note 3)**	**Type of Blocking Signal**
(-139 dBm + 10 × log10(OCBW) + 20 dB) or (-74 dBm + 20 dB) whichever is less	2 380 2 504 2 300 2 584	-34	CW
Note 1: OCBW is in Hz. Note 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative the test may be performed using a wanted signal up to P_{min} + 30 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal Note 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned.			

5.1.2 Test Procedures

Reference to clause 5.4.11.2 of ETSI EN 300 328 V2.2.2 (2019-07).

5.1.3 Test Setup



5.1.4 Test Result of Receiver Blocking

Hopping mode



Receiver Category	2		
Performance Criteria Limit	PER ≤ 10 %		
Wanted Signal Mean Power from Companion Device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm)	Test Result
-69.06	2380	-33.5	Pass
-69.06	2504	-33.5	Pass
-69.06	2300	-33.5	Pass
-69.06	2584	-33.5	Pass

6 Photographs of the Test Configuration

Spurious Emission Test (Configuration 1: BT800-ST)





Receiver Blocking Test (Configuration 1: BT800-ST)



Spurious Emission Test (Configuration 2 : BT820)





7 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou	**Kwei Shan**	**Kwei Shan Site II**
Tel: 886-2-2601-1640	Tel: 886-3-271-8666	Tel: 886-3-271-8640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

══END══