

IC C2PC Test Report

IC : 3147A-MSD50NBT
Equipment : 802.11abgn Molex 60-pin board-to-board module w/SDIO interface
Model No. : MSD50NBT
Brand Name : Laird
Applicant : LAIRD TECHNOLOGIES
Address : W66N220 Commerce Court, Cedarburg, WI 53012 United States Of America
Standard : RSS-247 Issue 2 February 2017
Received Date : Sep. 11, 2015
Tested Date : Dec. 14, 2015 ~ Jan. 26, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Assistant Manager

Approved by:


Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	Unwanted Emissions into Restricted Frequency Bands	14
3.3	Unwanted Emissions into Non-Restricted Frequency Bands	58
3.4	Conducted Output Power	63
3.5	Number of Hopping Frequency	65
3.6	20dB and Occupied Bandwidth	67
3.7	Channel Separation.....	69
3.8	Number of Dwell Time	71
4	TEST LABORATORY INFORMATION	74

Release Record

Report No.	Version	Description	Issued Date
CR591103-02AD	Rev. 01	Initial issue	Apr. 24, 2018

Summary of Test Results

IC Rules	Test Items	Measured	Result
RSS-Gen Section 8.8	Conducted Emissions	[dBuV]: 18.135MHz 20.28 (Margin -29.72dB) - AV	Pass
RSS-247 Section 5.5 RSS-Gen Section 8.9	Radiated Emissions	[dBuV/m at 3m]: 2390.00MHz 47.76 (Margin -6.24dB) - AV	Pass
RSS-247 Section 5.5	Band Edge	Meet the requirement of limit	Pass
RSS-247 Section 5.1(b) RSS-247 Section 5.4(b)	Conducted Output Power	Power [dBm]: 7.37	Pass
RSS-247 Section 5.1(d)	Number of Hopping Channels	Meet the requirement of limit	Pass
RSS-247 Section 5.1(b)	Hopping Channel Separation	Meet the requirement of limit	Pass
RSS-247 Section 5.1(d)	Dwell Time	Meet the requirement of limit	Pass
N/A	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

This is a Class II Permissive Change report (C2PC).

This report is issued as a supplementary report to the original ICC report no. CR591103AD. The modification is concerned as complying with latest version of standard. Test requirements are no change thus all test data remain the same in this test report.

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	3 Mbps
Note 1: RF output power specifies that Maximum Peak Conducted Output Power.				
Note 2: Bluetooth BR uses a GFSK.				
Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.				

1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)				
				2400~2483.5	5150~5250	5250~5350	5470~5725	5725~5850
1	Laird MAF94051	Dipole	RP-SMA	2.1	2.4	2.6	3.4	3.4
2	Laird NanoBlade-IP04	PCB Dipole	IPEX MHF	2	3.9	3.9	4	4
3	Laird MAF95310 Mini NanoBlade Flex	PCB Dipole	IPEX MHF	2.79	3.38	3.38	3.38	3.38
4	Laird NanoBlue-IP04	PCB Dipole	IPEX MHF	2	---	---	---	---
5	Ethertronics WLAN_1000146	Isolated Magnetic Dipole	IPEX MHF	2.5	3.5	3.5	3.5	3.5

Note: Ant. No. 1, 3 & 5 were for 2.4G final test.

Ant. No. 1, 2 & 5 were for 5G final test.

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	3.3Vdc from host
--------------------------	------------------

1.1.4 Accessories

N/A

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

1.1.6 Test Tool and Duty Cycle

Test Tool	CSR BlueSuite, V2.5.8
-----------	-----------------------

1.1.7 Power Setting


Modulation Mode	Test Frequency (MHz)		
	2402	2441	2480
GFSK/1Mbps	63	63	63
$\pi/4$ -DQPSK/2Mbps	63	63	63
8DPSK/3Mbps	63	63	63

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	DC Power Supply	GW INSTEK	GPC-3060D	EM884797	---	---
2	Notebook	DELL	Latitude E6430	9ZFB4X1	DoC	---
3	Fixture	---	---	---	---	---

Note: The fixture is provided by applicant.

1.3 Test Setup Chart



Note: The support notebook was disconnected from EUT and removed from test table when EUT is set to transmit continuously.

1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Jan. 08, 2016				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 21, 2015	Oct. 20, 2016
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2015	Nov. 12, 2016
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 21, 2015	Dec. 20, 2016
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Tested Date	Dec. 14 ~ Dec. 29, 2015				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 14, 2015	Sep. 13, 2016
Receiver	Agilent	N9038A	MY53290044	Oct. 14, 2015	Oct. 13, 2016
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-563	Dec. 30, 2014	Dec. 29, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 03, 2015	Feb. 02, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Preamplifier	EMC	EMC02325	980187	Sep. 21, 2015	Sep. 20, 2016
Preamplifier	Agilent	83017A	MY53270014	Sep. 07, 2015	Sep. 06, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 09, 2015	Feb. 08, 2016
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 09, 2015	Feb. 08, 2016
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 09, 2015	Feb. 08, 2016
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Feb. 09, 2015	Feb. 08, 2016
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 09, 2015	Feb. 08, 2016
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Feb. 09, 2015	Feb. 08, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Jan. 22 ~ Jan. 26, 2016				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
DC POWER SOURCE	GW INSTEK	GPC-3060D	EM884797	Oct. 20, 2015	Oct. 19, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

RSS-247 Issue 2 February 2017

RSS-Gen Issue 4 November 2014

ANSI C63.10-2013

ANSI C63.4-2014

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.134 Hz
Conducted power	± 0.808 dB
Power density	± 0.463 dB
Conducted emission	± 2.670 dB
AC conducted emission	± 2.90 dB
Radiated emission ≤ 1 GHz	± 3.66 dB
Radiated emission > 1 GHz	± 5.37 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	20°C / 60%	Peter Lin
Radiated Emissions	03CH03-WS	20-23°C / 59-64%	Warren Lee Morgan Chen
RF Conducted	TH01-WS	23°C / 65%	Alex Huang

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- IC site registration No.: 10807C-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Conducted Emissions	GFSK	2480	1Mbps	2
Radiated Emissions ≤ 1GHz	GFSK	2480	1Mbps	1, 2, 3
Radiated Emissions > 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	1, 2, 3
Conducted Output Power	GFSK π/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	2
Number of Hopping Channels	GFSK 8DPSK	2402~2480 2402~2480	1Mbps 3Mbps	2
Hopping Channel Separation	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	2
Dwell Time	GFSK 8DPSK	2402 2402	1Mbps 3Mbps	2

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.
2. The following antennas are used for final testing for this module: (See item 1.1.2 for more details.)
 - 1) Configuration 1 : Dipole antenna
 - 2) Configuration 2 : PCB Dipole antenna
 - 3) Configuration 3 : Isolated Magnetic Dipole antenna

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	GFSK	Test Freq. (MHz)	2441
Power Phase	Line		



	Freq	Level	Limit	Over	Read	LISN	cable	Remark
	MHz	dBuV	Line	Limit	Level	factor	loss	
			dBuV	dB	dBuV	dB	dB	
1	0.177	4.08	54.64	-50.56	3.95	0.11	0.02	Average
2	0.177	10.37	64.64	-54.27	10.24	0.11	0.02	QP
3	3.860	1.04	46.00	-44.96	0.73	0.19	0.12	Average
4	3.860	7.39	56.00	-48.61	7.08	0.19	0.12	QP
5	4.549	5.14	46.00	-40.86	4.81	0.20	0.13	Average
6	4.549	15.94	56.00	-40.06	15.61	0.20	0.13	QP
7	11.559	6.59	50.00	-43.41	6.14	0.27	0.18	Average
8	11.559	12.06	60.00	-47.94	11.61	0.27	0.18	QP
9	18.232	18.80	50.00	-31.20	18.27	0.35	0.18	Average
10	18.232	26.40	60.00	-33.60	25.87	0.35	0.18	QP
11	25.727	4.83	50.00	-45.17	4.15	0.43	0.25	Average
12	25.727	11.96	60.00	-48.04	11.28	0.43	0.25	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	GFSK	Test Freq. (MHz)	2441
Power Phase	Neutral		

Freq	Level	Limit	Over	Read	LISN	cable	
MHz	dBuV	Line	Limit	Level	factor	loss	Remark
		dBuV	dB	dBuV	dB	dB	
1	0.153	55.82	-50.53	5.14	0.13	0.02	Average
2	0.153	65.82	-53.04	12.63	0.13	0.02	QP
3	3.840	46.00	-42.73	2.98	0.17	0.12	Average
4	3.840	56.00	-47.15	8.56	0.17	0.12	QP
5	4.622	46.00	-38.14	7.54	0.19	0.13	Average
6	4.622	56.00	-40.53	15.15	0.19	0.13	QP
7	11.683	50.00	-45.77	3.75	0.30	0.18	Average
8	11.683	60.00	-52.46	7.06	0.30	0.18	QP
9@	18.135	50.00	-29.72	19.72	0.38	0.18	Average
10	18.135	60.00	-32.41	27.03	0.38	0.18	QP
11	26.001	50.00	-45.61	3.68	0.46	0.25	Average
12	26.001	60.00	-51.42	7.87	0.46	0.25	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).

2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. Radiated emission above 1GHz / Peak value
RBW=1MHz, VBW=3MHz and Peak detector
Radiated emission above 1GHz / Average value for harmonics
The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:
3.
$$20\log (\text{Duty cycle}) = 20\log \frac{1\text{s} / 1600 * 5}{100 \text{ ms}} = -30.1\text{dB}$$
4. Radiated emission above 1GHz / Average value for other emissions
RBW=1MHz, VBW=1/T and Peak detector

3.2.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



Test Configuration 1: Dipole antenna

3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	1




The graph displays the emission level in dBuV/m on the y-axis (0 to 90) against frequency in MHz on the x-axis (30 to 1000). A red line represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 300 MHz, and 55 dBuV/m from 300 to 1000 MHz. Six blue vertical lines represent measured emissions at 51.34, 154.16, 226.91, 389.87, 572.23, and 634.31 MHz, labeled 1 through 6 respectively. The emission levels are approximately 15.82, 12.67, 13.52, 15.31, 19.17, and 20.48 dBuV/m.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	51.34	15.82	40.00	-24.18	28.95	-13.13	Peak	---	---
2	154.16	12.67	43.50	-30.83	26.18	-13.51	Peak	---	---
3	226.91	13.52	46.00	-32.48	29.08	-15.56	Peak	---	---
4	389.87	15.31	46.00	-30.69	25.63	-10.32	Peak	---	---
5	572.23	19.17	46.00	-26.83	25.70	-6.53	Peak	---	---
6	634.31	20.48	46.00	-25.52	25.77	-5.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	30.00	27.97	40.00	-12.03	41.48	-13.51	Peak	---	---
2	48.43	30.20	40.00	-9.80	43.11	-12.91	Peak	---	---
3	514.03	21.64	46.00	-24.36	29.13	-7.49	Peak	---	---
4	582.90	22.37	46.00	-23.63	28.62	-6.25	Peak	---	---
5	611.03	23.73	46.00	-22.27	29.36	-5.63	Peak	---	---
6	908.82	25.73	46.00	-20.27	26.30	-0.57	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.23	54.00	-16.77	38.59	-1.36	Average	100	28
2	2390.00	48.53	74.00	-25.47	49.89	-1.36	Peak	100	28
3	4804.00	26.19	54.00	-27.81	20.26	5.93	Average	216	117
4	4804.00	56.29	74.00	-17.71	50.36	5.93	Peak	216	117
5	12010.00	26.89	54.00	-27.11	10.87	16.02	Average	315	217
6	12010.00	56.99	74.00	-17.01	40.97	16.02	Peak	315	217

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.08	54.00	-16.92	38.44	-1.36	Average	100	181
2	2390.00	47.99	74.00	-26.01	49.35	-1.36	Peak	100	181
3	4804.00	24.56	54.00	-29.44	18.63	5.93	Average	276	54
4	4804.00	54.66	74.00	-19.34	48.73	5.93	Peak	276	54
5	12010.00	23.77	54.00	-30.23	7.75	16.02	Average	329	137
6	12010.00	53.87	74.00	-20.13	37.85	16.02	Peak	329	137

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.87	54.00	-17.13	38.23	-1.36	Average	115	27
2	2390.00	47.99	74.00	-26.01	49.35	-1.36	Peak	115	27
3	2483.50	37.95	54.00	-16.05	38.97	-1.02	Average	115	27
4	2483.50	48.12	74.00	-25.88	49.14	-1.02	Peak	115	27
5	4882.00	24.53	54.00	-29.47	18.55	5.98	Average	291	177
6	4882.00	54.63	74.00	-19.37	48.65	5.98	Peak	291	177
7	7323.00	27.99	54.00	-26.01	17.22	10.77	Average	271	59
8	7323.00	58.09	74.00	-15.91	47.32	10.77	Peak	271	59

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.89	54.00	-17.11	38.25	-1.36	Average	113	0
2	2390.00	47.60	74.00	-26.40	48.96	-1.36	Peak	113	0
3	2483.50	37.72	54.00	-16.28	38.74	-1.02	Average	113	0
4	2483.50	48.33	74.00	-25.67	49.35	-1.02	Peak	113	0
5	4882.00	26.69	54.00	-27.31	20.71	5.98	Average	202	305
6	4882.00	56.79	74.00	-17.21	50.81	5.98	Peak	202	305
7	7323.00	22.58	54.00	-31.42	11.81	10.77	Average	179	210
8	7323.00	52.68	74.00	-21.32	41.91	10.77	Peak	179	210

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	43.23	54.00	-10.77	44.25	-1.02	Average	114	28
2	2483.50	54.56	74.00	-19.44	55.58	-1.02	Peak	114	28
3	4960.00	31.26	54.00	-22.74	25.23	6.03	Average	217	209
4	4960.00	61.36	74.00	-12.64	55.33	6.03	Peak	217	209
5	7440.00	25.80	54.00	-28.20	14.78	11.02	Average	279	212
6	7440.00	55.90	74.00	-18.10	44.88	11.02	Peak	279	212

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.64	54.00	-7.36	47.66	-1.02	Average	100	355
2	2483.50	58.27	74.00	-15.73	59.29	-1.02	Peak	100	355
3	4960.00	27.26	54.00	-26.74	21.23	6.03	Average	217	93
4	4960.00	57.36	74.00	-16.64	51.33	6.03	Peak	217	93
5	7440.00	24.26	54.00	-29.74	13.24	11.02	Average	267	195
6	7440.00	54.36	74.00	-19.64	43.34	11.02	Peak	267	195


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK


Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.89	54.00	-16.11	39.25	-1.36	Average	100	28
2	2390.00	48.93	74.00	-25.07	50.29	-1.36	Peak	100	28
3	4804.00	27.43	54.00	-26.57	21.50	5.93	Average	279	231
4	4804.00	57.53	74.00	-16.47	51.60	5.93	Peak	279	231
5	12010.00	27.61	54.00	-26.39	11.59	16.02	Average	288	219
6	12010.00	57.71	74.00	-16.29	41.69	16.02	Peak	288	219

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.69	54.00	-16.31	39.05	-1.36	Average	100	181
2	2390.00	48.73	74.00	-25.27	50.09	-1.36	Peak	100	181
3	4804.00	25.49	54.00	-28.51	19.56	5.93	Average	251	292
4	4804.00	55.59	74.00	-18.41	49.66	5.93	Peak	251	292
5	12010.00	24.58	54.00	-29.42	8.56	16.02	Average	296	179
6	12010.00	54.68	74.00	-19.32	38.66	16.02	Peak	296	179

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.82	54.00	-17.18	38.18	-1.36	Average	115	27
2	2390.00	49.26	74.00	-24.74	50.62	-1.36	Peak	115	27
3	2483.50	37.11	54.00	-16.89	38.13	-1.02	Average	115	27
4	2483.50	48.56	74.00	-25.44	49.58	-1.02	Peak	115	27
5	4882.00	28.33	54.00	-25.67	22.35	5.98	Average	312	198
6	4882.00	58.43	74.00	-15.57	52.45	5.98	Peak	261	271
7	7323.00	25.17	54.00	-28.83	14.40	10.77	Average	312	198
8	7323.00	55.27	74.00	-18.73	44.50	10.77	Peak	312	198

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.32	54.00	-16.68	38.68	-1.36	Average	113	0
2	2390.00	48.33	74.00	-25.67	49.69	-1.36	Peak	113	0
3	2483.50	37.93	54.00	-16.07	38.95	-1.02	Average	113	0
4	2483.50	48.33	74.00	-25.67	49.35	-1.02	Peak	113	0
5	4882.00	26.07	54.00	-27.93	20.09	5.98	Average	234	219
6	4882.00	56.17	74.00	-17.83	50.19	5.98	Peak	234	219
7	7323.00	23.36	54.00	-30.64	12.59	10.77	Average	197	22
8	7323.00	53.46	74.00	-20.54	42.69	10.77	Peak	197	22

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	43.33	54.00	-10.67	44.35	-1.02	Average	114	28
2	2483.50	55.36	74.00	-18.64	56.38	-1.02	Peak	114	28
3	4960.00	26.80	54.00	-27.20	20.77	6.03	Average	219	196
4	4960.00	56.90	74.00	-17.10	50.87	6.03	Peak	219	196
5	7440.00	26.28	54.00	-27.72	15.26	11.02	Average	299	218
6	7440.00	56.38	74.00	-17.62	45.36	11.02	Peak	299	218

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.22	54.00	-7.78	47.24	-1.02	Average	100	355
2	2483.50	57.66	74.00	-16.34	58.68	-1.02	Peak	100	355
3	4960.00	25.54	54.00	-28.46	19.51	6.03	Average	261	220
4	4960.00	55.64	74.00	-18.36	49.61	6.03	Peak	261	220
5	7440.00	26.26	54.00	-27.74	15.24	11.02	Average	219	267
6	7440.00	56.36	74.00	-17.64	45.34	11.02	Peak	219	267

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Test Configuration 2: PCB Dipole antenna

3.2.7 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	2




The graph displays the radiated unwanted emissions for a PCB Dipole antenna. The y-axis represents the Level in dBuV/m, ranging from 0 to 90. The x-axis represents the Frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 1000 MHz, and 55 dBuV/m from 1000 to 10000 MHz. Six measured peaks are labeled with numbers 1 through 6, corresponding to the data in the table below.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	48.43	19.28	40.00	-20.72	32.19	-12.91	Peak	---	---
2	140.58	13.03	43.50	-30.47	26.76	-13.73	Peak	---	---
3	226.91	12.44	46.00	-33.56	28.00	-15.56	Peak	---	---
4	552.83	18.91	46.00	-27.09	25.94	-7.03	Peak	---	---
5	658.56	21.32	46.00	-24.68	26.27	-4.95	Peak	---	---
6	847.71	23.06	46.00	-22.94	24.89	-1.83	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	30.00	28.17	40.00	-11.83	41.68	-13.51	Peak	---	---
2	48.43	31.48	40.00	-8.52	44.39	-12.91	Peak	---	---
3	521.79	20.32	46.00	-25.68	27.73	-7.41	Peak	---	---
4	582.90	22.78	46.00	-23.22	29.03	-6.25	Peak	---	---
5	611.03	23.68	46.00	-22.32	29.31	-5.63	Peak	---	---
6	871.96	24.34	46.00	-21.66	25.66	-1.32	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.2.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.63	54.00	-16.37	38.76	-1.13	Average	190	8
2	2390.00	49.35	74.00	-24.65	50.48	-1.13	Peak	190	8
3	4804.00	27.38	54.00	-26.62	20.16	7.22	Average	196	267
4	4804.00	57.48	74.00	-16.52	50.26	7.22	Peak	196	267
5	12010.00	26.93	54.00	-27.07	10.26	16.67	Average	215	218
6	12010.00	57.03	74.00	-16.97	40.36	16.67	Peak	215	218

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	2




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.06	54.00	-15.94	39.19	-1.13	Average	160	189
2	2390.00	51.30	74.00	-22.70	52.43	-1.13	Peak	160	189
3	4804.00	24.16	54.00	-29.84	16.94	7.22	Average	207	294
4	4804.00	54.26	74.00	-19.74	47.04	7.22	Peak	207	294
5	12010.00	24.88	54.00	-29.12	8.21	16.67	Average	320	291
6	12010.00	54.98	74.00	-19.02	38.31	16.67	Peak	320	291

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	2




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.26	54.00	-15.74	39.39	-1.13	Average	188	8
2	2390.00	49.97	74.00	-24.03	51.10	-1.13	Peak	188	8
3	2483.50	37.56	54.00	-16.44	38.36	-0.80	Average	188	8
4	2483.50	49.60	74.00	-24.40	50.40	-0.80	Peak	188	8
5	4882.00	28.06	54.00	-25.94	21.17	6.89	Average	154	274
6	4882.00	58.16	74.00	-15.84	51.27	6.89	Peak	154	274
7	7323.00	24.34	54.00	-29.66	13.26	11.08	Average	208	271
8	7323.00	54.44	74.00	-19.56	43.36	11.08	Peak	208	271

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	2




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.46	54.00	-17.54	37.59	-1.13	Average	188	57
2	2390.00	48.81	74.00	-25.19	49.94	-1.13	Peak	188	57
3	2483.50	38.46	54.00	-15.54	39.26	-0.80	Average	188	57
4	2483.50	50.46	74.00	-23.54	51.26	-0.80	Peak	188	57
5	4882.00	26.55	54.00	-27.45	19.66	6.89	Average	361	2114
6	4882.00	56.65	74.00	-17.35	49.76	6.89	Peak	361	2114
7	7323.00	21.49	54.00	-32.51	10.41	11.08	Average	231	187
8	7323.00	51.59	74.00	-22.41	40.51	11.08	Peak	231	187

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	2




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.65	54.00	-7.35	47.45	-0.80	Average	183	12
2	2483.50	58.26	74.00	-15.74	59.06	-0.80	Peak	183	12
3	4960.00	32.07	54.00	-21.93	25.50	6.57	Average	187	243
4	4960.00	62.17	74.00	-11.83	55.60	6.57	Peak	187	243
5	7440.00	25.50	54.00	-28.50	14.14	11.36	Average	269	320
6	7440.00	55.60	74.00	-18.40	44.24	11.36	Peak	269	320

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	47.46	54.00	-6.54	48.26	-0.80	Average	155	65
2	2483.50	57.80	74.00	-16.20	58.60	-0.80	Peak	155	65
3	4960.00	28.13	54.00	-25.87	21.56	6.57	Average	297	103
4	4960.00	58.23	74.00	-15.77	51.66	6.57	Peak	297	103
5	7440.00	24.47	54.00	-29.53	13.11	11.36	Average	175	263
6	7440.00	54.57	74.00	-19.43	43.21	11.36	Peak	175	263


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.2.9 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK


Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	47.76	54.00	-6.24	48.89	-1.13	Average	190	8
2	2390.00	50.36	74.00	-23.64	51.49	-1.13	Peak	190	8
3	4804.00	27.67	54.00	-26.33	20.45	7.22	Average	192	260
4	4804.00	57.77	74.00	-16.23	50.55	7.22	Peak	192	260
5	12010.00	24.84	54.00	-29.16	8.17	16.67	Average	208	167
6	12010.00	54.94	74.00	-19.06	38.27	16.67	Peak	208	167

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	2




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.38	54.00	-16.62	38.51	-1.13	Average	153	93
2	2390.00	48.36	74.00	-25.64	49.49	-1.13	Peak	153	93
3	4804.00	23.44	54.00	-30.56	16.22	7.22	Average	182	252
4	4804.00	53.54	74.00	-20.46	46.32	7.22	Peak	182	252
5	12010.00	23.11	54.00	-30.89	6.44	16.67	Average	238	146
6	12010.00	53.21	74.00	-20.79	36.54	16.67	Peak	238	146

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	2




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.08	54.00	-16.92	38.21	-1.13	Average	188	3
2	2390.00	50.08	74.00	-23.92	51.21	-1.13	Peak	188	3
3	2483.50	37.46	54.00	-16.54	38.26	-0.80	Average	188	3
4	2483.50	49.69	74.00	-24.31	50.49	-0.80	Peak	188	3
5	4882.00	28.58	54.00	-25.42	21.69	6.89	Average	305	192
6	4882.00	58.68	74.00	-15.32	51.79	6.89	Peak	305	192
7	7323.00	32.26	54.00	-21.74	21.18	11.08	Average	178	21
8	7323.00	62.36	74.00	-11.64	51.28	11.08	Peak	178	21

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	2




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.88	54.00	-17.12	38.01	-1.13	Average	161	65
2	2390.00	48.44	74.00	-25.56	49.57	-1.13	Peak	161	65
3	2483.50	37.82	54.00	-16.18	38.62	-0.80	Average	161	65
4	2483.50	50.78	74.00	-23.22	51.58	-0.80	Peak	161	65
5	4882.00	27.10	54.00	-26.90	20.21	6.89	Average	283	154
6	4882.00	57.20	74.00	-16.80	50.31	6.89	Peak	283	154
7	7323.00	22.24	54.00	-31.76	11.16	11.08	Average	231	200
8	7323.00	52.34	74.00	-21.66	41.26	11.08	Peak	231	200

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	2




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	41.50	54.00	-12.50	42.30	-0.80	Average	183	12
2	2483.50	53.86	74.00	-20.14	54.66	-0.80	Peak	183	12
3	4960.00	29.86	54.00	-24.14	23.29	6.57	Average	160	225
4	4960.00	59.96	74.00	-14.04	53.39	6.57	Peak	160	225
5	7440.00	22.87	54.00	-31.13	11.51	11.36	Average	257	197
6	7440.00	52.97	74.00	-21.03	41.61	11.36	Peak	257	197

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	39.36	54.00	-14.64	40.16	-0.80	Average	155	64
2	2483.50	51.54	74.00	-22.46	52.34	-0.80	Peak	155	64
3	4960.00	27.67	54.00	-26.33	21.10	6.57	Average	270	60
4	4960.00	57.77	74.00	-16.23	51.20	6.57	Peak	270	60
5	7440.00	23.24	54.00	-30.76	11.88	11.36	Average	335	279
6	7440.00	53.34	74.00	-20.66	41.98	11.36	Peak	335	279

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Test Configuration 3: Isolated Magnetic Dipole antenna

3.2.10 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	3




The graph displays the radiated unwanted emissions for a transmitter using GFSK modulation. The y-axis represents the emission level in dBuV/m, ranging from 0 to 90. The x-axis represents the frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 200 MHz, and 55 dBuV/m from 200 to 1000 MHz. Six measured peaks are labeled with numbers 1 through 6. The data for these peaks is provided in the table below.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	51.34	22.87	40.00	-17.13	36.00	-13.13	Peak	---	---
2	138.64	13.92	43.50	-29.58	27.79	-13.87	Peak	---	---
3	226.91	13.03	46.00	-32.97	28.59	-15.56	Peak	---	---
4	624.61	20.30	46.00	-25.70	25.74	-5.44	Peak	---	---
5	803.09	23.01	46.00	-22.99	25.59	-2.58	Peak	---	---
6	936.95	25.09	46.00	-20.91	25.15	-0.06	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	3



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	33.88	26.54	40.00	-13.46	40.03	-13.49	Peak	---	---
2	48.43	29.98	40.00	-10.02	42.89	-12.91	Peak	---	---
3	94.99	15.25	43.50	-28.25	34.25	-19.00	Peak	---	---
4	582.90	22.55	46.00	-23.45	28.80	-6.25	Peak	---	---
5	611.03	23.32	46.00	-22.68	28.95	-5.63	Peak	---	---
6	761.38	27.75	46.00	-18.25	30.89	-3.14	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.2.11 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	3



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.26	54.00	-16.74	38.39	-1.13	Average	185	171
2	2390.00	49.21	74.00	-24.79	50.34	-1.13	Peak	185	171
3	4804.00	28.52	54.00	-25.48	21.30	7.22	Average	182	223
4	4804.00	58.62	74.00	-15.38	51.40	7.22	Peak	182	223
5	12010.00	26.01	54.00	-27.99	9.34	16.67	Average	208	167
6	12010.00	56.11	74.00	-17.89	39.44	16.67	Peak	208	167

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.66	54.00	-16.34	38.79	-1.13	Average	150	91
2	2390.00	50.94	74.00	-23.06	52.07	-1.13	Peak	150	91
3	4804.00	23.90	54.00	-30.10	16.68	7.22	Average	182	252
4	4804.00	54.00	74.00	-20.00	46.78	7.22	Peak	182	252
5	12010.00	25.36	54.00	-28.64	8.69	16.67	Average	238	146
6	12010.00	55.46	74.00	-18.54	38.79	16.67	Peak	238	146

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.62	54.00	-16.38	38.75	-1.13	Average	150	175
2	2390.00	48.49	74.00	-25.51	49.62	-1.13	Peak	150	175
3	2483.50	38.10	54.00	-15.90	38.90	-0.80	Average	150	175
4	2483.50	51.62	74.00	-22.38	52.42	-0.80	Peak	150	175
5	4882.00	29.10	54.00	-24.90	22.21	6.89	Average	182	220
6	4882.00	59.20	74.00	-14.80	52.31	6.89	Peak	182	220
7	7323.00	24.21	54.00	-29.79	13.13	11.08	Average	210	192
8	7323.00	54.31	74.00	-19.69	43.23	11.08	Peak	210	192

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.46	54.00	-16.54	38.59	-1.13	Average	150	91
2	2390.00	49.16	74.00	-24.84	50.29	-1.13	Peak	150	91
3	2483.50	37.43	54.00	-16.57	38.23	-0.80	Average	150	91
4	2483.50	48.58	74.00	-25.42	49.38	-0.80	Peak	150	91
5	4882.00	27.06	54.00	-26.94	20.17	6.89	Average	318	260
6	4882.00	57.16	74.00	-16.84	50.27	6.89	Peak	318	260
7	7323.00	24.24	54.00	-29.76	13.16	11.08	Average	208	202
8	7323.00	54.34	74.00	-19.66	43.26	11.08	Peak	208	202

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.45	54.00	-7.55	47.25	-0.80	Average	165	175
2	2483.50	57.85	74.00	-16.15	58.65	-0.80	Peak	165	175
3	4960.00	30.79	54.00	-23.21	24.22	6.57	Average	158	213
4	4960.00	60.89	74.00	-13.11	54.32	6.57	Peak	158	213
5	7440.00	24.13	54.00	-29.87	12.77	11.36	Average	231	189
6	7440.00	54.23	74.00	-19.77	42.87	11.36	Peak	231	189

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	3



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.34	54.00	-7.66	47.14	-0.80	Average	165	89
2	2483.50	57.10	74.00	-16.90	57.90	-0.80	Peak	165	89
3	4960.00	27.07	54.00	-26.93	20.50	6.57	Average	320	262
4	4960.00	57.17	74.00	-16.83	50.60	6.57	Peak	320	262
5	7440.00	23.55	54.00	-30.45	12.19	11.36	Average	340	187
6	7440.00	53.65	74.00	-20.35	42.29	11.36	Peak	340	187


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.2.12 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK


Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	3



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.12	54.00	-16.88	38.25	-1.13	Average	185	171
2	2390.00	49.22	74.00	-24.78	50.35	-1.13	Peak	185	171
3	4804.00	27.73	54.00	-26.27	20.51	7.22	Average	182	223
4	4804.00	57.83	74.00	-16.17	50.61	7.22	Peak	182	223
5	12010.00	24.84	54.00	-29.16	8.17	16.67	Average	208	167
6	12010.00	54.94	74.00	-19.06	38.27	16.67	Peak	208	167

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.62	54.00	-16.38	38.75	-1.13	Average	177	116
2	2390.00	50.12	74.00	-23.88	51.25	-1.13	Peak	177	116
3	4804.00	23.44	54.00	-30.56	16.22	7.22	Average	182	252
4	4804.00	53.54	74.00	-20.46	46.32	7.22	Peak	182	252
5	12010.00	23.11	54.00	-30.89	6.44	16.67	Average	238	146
6	12010.00	53.21	74.00	-20.79	36.54	16.67	Peak	238	146

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Horizontal	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2380.00	37.32	54.00	-16.68	38.51	-1.19	Average	164	157
2	2380.00	49.51	74.00	-24.49	50.70	-1.19	Peak	164	157
3	2483.50	37.33	54.00	-16.67	38.13	-0.80	Average	164	157
4	2483.50	49.49	74.00	-24.51	50.29	-0.80	Peak	164	157
5	4882.00	28.78	54.00	-25.22	21.89	6.89	Average	182	220
6	4882.00	58.88	74.00	-15.12	51.99	6.89	Peak	182	220
7	7323.00	33.21	54.00	-20.79	22.13	11.08	Average	210	192
8	7323.00	63.31	74.00	-10.69	52.23	11.08	Peak	210	192

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.91	54.00	-17.09	38.04	-1.13	Average	175	87
2	2390.00	49.10	74.00	-24.90	50.23	-1.13	Peak	175	87
3	2483.50	37.41	54.00	-16.59	38.21	-0.80	Average	175	87
4	2483.50	49.21	74.00	-24.79	50.01	-0.80	Peak	175	87
5	4882.00	26.79	54.00	-27.21	19.90	6.89	Average	318	260
6	4882.00	56.89	74.00	-17.11	50.00	6.89	Peak	318	260
7	7323.00	22.06	54.00	-31.94	10.98	11.08	Average	208	202
8	7323.00	52.16	74.00	-21.84	41.08	11.08	Peak	208	202

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.83	54.00	-13.17	41.63	-0.80	Average	181	157
2	2483.50	53.92	74.00	-20.08	54.72	-0.80	Peak	181	157
3	4960.00	30.55	54.00	-23.45	23.98	6.57	Average	158	213
4	4960.00	60.65	74.00	-13.35	54.08	6.57	Peak	158	213
5	7440.00	21.54	54.00	-32.46	10.18	11.36	Average	231	189
6	7440.00	51.64	74.00	-22.36	40.28	11.36	Peak	231	189

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	3



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	40.40	54.00	-13.60	41.20	-0.80	Average	192	112
2	2483.50	53.10	74.00	-20.90	53.90	-0.80	Peak	192	112
3	4960.00	26.96	54.00	-27.04	20.39	6.57	Average	320	262
4	4960.00	57.06	74.00	-16.94	50.49	6.57	Peak	320	262
5	7440.00	22.09	54.00	-31.91	10.73	11.36	Average	340	187
6	7440.00	52.19	74.00	-21.81	40.83	11.36	Peak	340	187

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures


Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement


1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

3.3.3 Test Setup




3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands

GFSK






Hopping off

TX Freq 2441MHz / 30MHz~25GHz (down 20dBc)




Hopping off

TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)




8DPSK






Hopping off

TX Freq 2441MHz / 30MHz~25GHz (down 20dBc)



Hopping off

TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)



3.4 Conducted Output Power


3.4.1 Limit of Conducted Output Power

- ☐ 1 Watt
For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
- ☒ 0.125 Watt
For all other frequency hopping systems in the 2400–2483.5 MHz band.
- ☐ 0.125 Watt
For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

1. A wideband power meter is used for power measurement. Bandwidth of power sensor and meter is 50MHz
2. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup



3.4.4 Test Result of Conducted Output Power

Modulation Mode	Freq. (MHz)	Output Power (mW)	Output Power (dBm)	Limit (mW)
GFSK	2402	4.72	6.74	125
GFSK	2441	5.46	7.37	125
GFSK	2480	5.15	7.12	125
π/4 DQPSK	2402	3.58	5.54	125
π/4 DQPSK	2441	4.24	6.27	125
π/4 DQPSK	2480	4.00	6.02	125
8DPSK	2402	3.80	5.8	125
8DPSK	2441	4.53	6.56	125
8DPSK	2480	4.29	6.32	125

Modulation Mode	Freq. (MHz)	AV Output Power (mW)	AV Output Power (dBm)	Limit (mW)
GFSK	2402	4.49	6.52	---
GFSK	2441	5.21	7.17	---
GFSK	2480	4.90	6.9	---
π/4 DQPSK	2402	2.36	3.73	---
π/4 DQPSK	2441	3.01	4.78	---
π/4 DQPSK	2480	2.88	4.6	---
8DPSK	2402	2.36	3.72	---
8DPSK	2441	3.01	4.78	---
8DPSK	2480	2.88	4.59	---

Note: Average power is for reference only.

3.5 Number of Hopping Frequency


3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.


3.5.2 Test Procedures

1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
2. Allow trace to stabilize.

3.5.3 Test Setup



3.5.4 Test Result of Number of Hopping Frequency



3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures


20 dB Bandwidth

1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak, Trace max hold
2. Allow trace to stabilize
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth


1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak, Trace max hold
2. Allow trace to stabilize
3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup



3.6.3 Test result of 20dB and Occupied Bandwidth

Modulation Mode	Freq. (MHz)	20dB Bandwidth (MHz)	Occupied Bandwidth (MHz)
GFSK	2402	0.952	0.881
GFSK	2441	0.952	0.877
GFSK	2480	0.952	0.881
8DPSK	2402	1.287	1.177
8DPSK	2441	1.278	1.194
8DPSK	2480	1.287	1.207



3.7 Channel Separation


3.7.1 Limit of Channel Separation

- ☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- ☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures


1. Set RBW=100kHz, VBW=300kHz, Sweep time = Auto, Detector=Peak Trace max hold
2. Allow trace to stabilize
3. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup



3.7.4 Test result of Channel Separation

Modulation Mode	Freq. (MHz)	Channel Separation (MHz)	20dB Bandwidth (MHz)	Minimum Limit (MHz)
GFSK	2402	1.003	0.952	0.635
GFSK	2441	1.003	0.952	0.635
GFSK	2480	1.003	0.952	0.635
8DPSK	2402	1.003	1.287	0.858
8DPSK	2441	1.003	1.278	0.852
8DPSK	2480	1.003	1.287	0.858



3.8 Number of Dwell Time


3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures


1. Set RBW=100kHz,VBW=300kHz,Sweep time = 500us(DH1),2ms(DH3),4ms(DH5), Detector=Peak, Span=0Hz,Trace max hold
2. Enable gating and trigger function of spectrum analyzer to measure burst on time.
3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds, or 0.625ms. DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.
4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds, or 1.875ms. DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
5. The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds


3.8.3 Test Setup



3.8.4 Test Result of Dwell Time

Modulation Mode	Freq. (MHz)	Length of Transmission Time (msec)	Number of Transmission in a 31.6 (79 Hopping*0.4)	Result (s)	Limit (s)
GFSK-DH1	2402	0.44203	320	0.141	0.4
GFSK-DH3	2402	1.69203	160	0.271	0.4
GFSK-DH5	2402	2.98406	106.6	0.318	0.4
8DPSK-DH1	2402	0.45217	320	0.145	0.4
8DPSK-DH3	2402	1.70000	160	0.272	0.4
8DPSK-DH5	2402	2.95725	106.6	0.315	0.4





4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==