

IC C2PC Test Report

IC : 3147A-MSD50NBT
Equipment : 802.11abgn Molex 60-pin board-to-board module w/SDIO interface
Model No. : MSD50NBT
Brand Name : Laird
Applicant : LAIRD TECHNOLOGIES
Address : W66N220 Commerce Court, Cedarburg, WI 53012 United States Of America
Standard : RSS-247 Issue 2 February 2017
Received Date : Sep. 11, 2015
Tested Date : Dec. 14, 2015 ~ Jan. 26, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Assistant Manager

Approved by:


Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	Test Equipment List and Calibration Data.....	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	16
3.4	Power Spectral Density	18
3.5	Emissions in Restricted Frequency Bands.....	20
3.6	Emissions in non-restricted Frequency Bands.....	46
4	TEST LABORATORY INFORMATION	49

Release Record

Report No.	Version	Description	Issued Date
CR591103-02AE	Rev. 01	Initial issue	Apr. 24, 2018

Summary of Test Results

IC Rules	Test Items	Measured	Result
RSS-Gen Section 8.8	AC Power Line Conducted Emissions	[dBuV]: 18.039MHz 20.20 (Margin -29.80dB) - AV	Pass
RSS-247 Section 5.5 RSS-Gen Section 8.9	Radiated Emissions	[dBuV/m at 3m]: 4960.00MHz 53.66 (Margin -0.34dB) - AV	Pass
RSS-247 Section 5.4 (d)	Maximum Output Power	Power [dBm]: 6.96	Pass
RSS-247 Section 5.2 (a)	6dB Bandwidth	Meet the requirement of limit	Pass
RSS-247 Section 5.2 (b)	Power Spectral Density	Meet the requirement of limit	Pass
N/A	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

This is a Class II Permissive Change report (C2PC).

This report is issued as a supplementary report to the original ICC report no. CR591103AE. The modification is concerned as complying with latest version of standard. Test requirements are no change thus all test data remain the same in this test report.

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	V4.0 LE	2402-2480	0-39 [40]	1 Mbps
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.				

1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)				
				2400~2483.5	5150~5250	5250~5350	5470~5725	5725~5850
1	Laird MAF94051	Dipole	RP-SMA	2.1	2.4	2.6	3.4	3.4
2	Laird NanoBlade-IP04	PCB Dipole	IPEX MHF	2	3.9	3.9	4	4
3	Laird MAF95310 Mini NanoBlade Flex	PCB Dipole	IPEX MHF	2.79	3.38	3.38	3.38	3.38
4	Laird NanoBlue-IP04	PCB Dipole	IPEX MHF	2	---	---	---	---
5	Ethertronics WLAN_1000146	Isolated Magnetic Dipole	IPEX MHF	2.5	3.5	3.5	3.5	3.5

Note: Ant. No. 1, 3 & 5 were for 2.4G final test.

Ant. No. 1, 2 & 5 were for 5G final test.

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	3.3Vdc from host
-------------------	------------------

1.1.4 Accessories

N/A

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.6 Test Tool and Duty Cycle

Test tool	CSR BlueSuite, V2.5.8
Duty cycle of test signal (%)	67.42%
Duty Factor (dB)	1.71

1.1.7 Power Setting


Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	Default	Default	Default

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	DC Power Supply	GW INSTEK	GPC-3060D	EM884797	---	---
2	Notebook	DELL	Latitude E6430	9ZFB4X1	DoC	---
3	Fixture	---	---	---	---	---

Note: The fixture is provided by applicant.

1.3 Test Setup Chart



Note: The support notebook was disconnected from EUT and removed from test table when EUT is set to transmit continuously.

1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Jan. 08, 2016				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 21, 2015	Oct. 20, 2016
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2015	Nov. 12, 2016
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 21, 2015	Dec. 20, 2016
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Tested Date	Dec. 14 ~ Dec. 29, 2015				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 14, 2015	Sep. 13, 2016
Receiver	Agilent	N9038A	MY53290044	Oct. 14, 2015	Oct. 13, 2016
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-563	Dec. 30, 2014	Dec. 29, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 03, 2015	Feb. 02, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Preamplifier	EMC	EMC02325	980187	Sep. 21, 2015	Sep. 20, 2016
Preamplifier	Agilent	83017A	MY53270014	Sep. 07, 2015	Sep. 06, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 09, 2015	Feb. 08, 2016
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 09, 2015	Feb. 08, 2016
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 09, 2015	Feb. 08, 2016
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Feb. 09, 2015	Feb. 08, 2016
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 09, 2015	Feb. 08, 2016
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Feb. 09, 2015	Feb. 08, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Jan. 12, 2016				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
DC POWER SOURCE	GW INSTEK	GPC-3060D	EM884797	Oct. 20, 2015	Oct. 19, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

RSS-247 Issue 2 February 2017

RSS-Gen Issue 4 November 2014

ANSI C63.10-2013

ANSI C63.4-2014

FCC KDB 558074 D01 DTS Meas Guidance v04

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.90 dB
Radiated emission ≤ 1GHz	±3.66 dB
Radiated emission > 1GHz	±5.37 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	20°C / 60%	Peter Lin
Radiated Emissions	03CH03-WS	20-23°C / 59-64%	Warren Lee Morgan Chen
RF Conducted	TH01-WS	22°C / 63%	Alex Huang

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- IC site registration No.: 10807C-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Conducted Emissions	BT LE	2440	1Mbps	2
Radiated Emissions ≤ 1GHz	BT LE	2440	1Mbps	1, 2, 3
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	1, 2, 3
Maximum Output Power	BT LE	2402, 2440, 2480	1Mbps	2
6dB bandwidth				
Power spectral density				
NOTE: 1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report. 2. The following antennas are used for final testing for this module: (See item 1.1.2 for more details.) 1) Configuration 1 : Dipole antenna 2) Configuration 2 : PCB Dipole antenna 3) Configuration 3 : Isolated Magnetic Dipole antenna				

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	GFSK	Test Freq. (MHz)	2440
Power Phase	Line		




Freq	Level	Limit	Over	Read	LISN	cable	Remark	
MHz	dBuV	dBuV	Limit	Level	factor	loss		
			dB	dBuV	dB	dB		
1	0.159	4.73	55.52	-50.79	4.60	0.11	0.02	Average
2	0.159	12.04	65.52	-53.48	11.91	0.11	0.02	QP
3	3.820	2.91	46.00	-43.09	2.60	0.19	0.12	Average
4	3.820	7.42	56.00	-48.58	7.11	0.19	0.12	QP
5	4.622	7.64	46.00	-38.36	7.31	0.20	0.13	Average
6	4.622	14.61	56.00	-41.39	14.28	0.20	0.13	QP
7	12.124	5.60	50.00	-44.40	5.14	0.28	0.18	Average
8	12.124	12.65	60.00	-47.35	12.19	0.28	0.18	QP
9	13.623	4.98	50.00	-45.02	4.48	0.30	0.20	Average
10	13.623	11.77	60.00	-48.23	11.27	0.30	0.20	QP
11@	18.135	19.45	50.00	-30.55	18.92	0.35	0.18	Average
12	18.135	28.12	60.00	-31.88	27.59	0.35	0.18	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).

2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	GFSK	Test Freq. (MHz)	2440
Power Phase	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.156	11.07	55.65	-44.58	10.92	0.13	0.02	Average
2	0.156	16.83	65.65	-48.82	16.68	0.13	0.02	QP
3	3.881	3.00	46.00	-43.00	2.71	0.17	0.12	Average
4	3.881	6.39	56.00	-49.61	6.10	0.17	0.12	QP
5	4.501	10.66	46.00	-35.34	10.36	0.18	0.12	Average
6	4.501	17.33	56.00	-38.67	17.03	0.18	0.12	QP
7	12.253	6.63	50.00	-43.37	6.13	0.31	0.19	Average
8	12.253	13.62	60.00	-46.38	13.12	0.31	0.19	QP
9@	18.039	20.20	50.00	-29.80	19.64	0.38	0.18	Average
10	18.039	27.04	60.00	-32.96	26.48	0.38	0.18	QP
11	25.727	4.43	50.00	-45.57	3.72	0.46	0.25	Average
12	25.727	12.70	60.00	-47.30	11.99	0.46	0.25	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 1% to 5% of the anticipated emission, Video bandwidth = 3x the RBW.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth


1. Set resolution bandwidth (RBW) = 1 MHz, Video bandwidth = 3 MHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup



3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.691	1.03	500
BT LE	2440	0.696	1.05	500
BT LE	2480	0.696	1.06	500



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

- ☒ Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.
- ☐ Antenna gain $> 6\text{dBi}$
 - ☐ Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
 - ☐ Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

- ☒ Maximum Peak Conducted Output Power
 - ☐ **Spectrum analyzer**
 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
 - ☒ **Power meter**
 1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- ☒ Maximum Conducted Average Output Power (For reference only)
 - ☒ **Power meter**
 1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Mode	Freq. (MHz)	Peak Power			Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
		Power (mW)	Power (dBm)	Limit (dBm)			
BT LE	2402	4.074	6.10	30	2.79	8.89	36
BT LE	2440	4.966	6.96	30	2.79	9.75	36
BT LE	2480	4.699	6.72	30	2.79	9.51	36

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	3.793	5.79	---
BT LE	2440	4.688	6.71	---
BT LE	2480	4.416	6.45	---

Note: Average power is for reference only

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures


- ☒ Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 3kHz, VBW = 10kHz.
 2. Detector = Peak, Sweep time = auto couple.
 3. Trace mode = max hold, allow trace to fully stabilize.
 4. Use the peak marker function to determine the maximum amplitude level.
- ☐ Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 100kHz, VBW = 300 kHz.
 2. Detector = RMS, Sweep time = auto couple.
 3. Set the sweep time to: $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$.
 4. Perform the measurement over a single sweep.
 5. Use the peak marker function to determine the maximum amplitude level.\

3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-9.49	8
BT LE	2440	-8.93	8
BT LE	2480	-9.07	8



3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



Test Configuration 1: Dipole antenna

3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	1




The graph displays the radiated unwanted emissions for a GFSK transmitter at 2440 MHz. The y-axis represents the level in dBuV/m, ranging from 0 to 90. The x-axis represents the frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 300 MHz, and 55 dBuV/m from 300 to 1000 MHz. Six measured peaks are shown as blue vertical lines, labeled 1 through 6. The peak levels are 17.62, 13.25, 12.68, 14.33, 18.17, and 21.16 dBuV/m respectively. The corresponding frequencies are 51.34, 160.95, 226.91, 288.99, 544.10, and 639.16 MHz.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	51.34	17.62	40.00	-22.38	30.75	-13.13	Peak	---	---
2	160.95	13.25	43.50	-30.25	26.92	-13.67	Peak	---	---
3	226.91	12.68	46.00	-33.32	28.24	-15.56	Peak	---	---
4	288.99	14.33	46.00	-31.67	27.49	-13.16	Peak	---	---
5	544.10	18.17	46.00	-27.83	25.34	-7.17	Peak	---	---
6	639.16	21.16	46.00	-24.84	26.39	-5.23	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	30.00	27.06	40.00	-12.94	40.57	-13.51	Peak	---	---
2	46.49	29.37	40.00	-10.63	42.23	-12.86	Peak	---	---
3	515.97	20.48	46.00	-25.52	27.95	-7.47	Peak	---	---
4	582.90	22.58	46.00	-23.42	28.83	-6.25	Peak	---	---
5	611.03	23.30	46.00	-22.70	28.93	-5.63	Peak	---	---
6	639.16	22.33	46.00	-23.67	27.56	-5.23	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.12	54.00	-16.88	38.48	-1.36	Average	100	29
2	2390.00	48.83	74.00	-25.17	50.19	-1.36	Peak	100	29
3	4804.00	50.87	54.00	-3.13	43.65	7.22	Average	187	214
4	4804.00	55.33	74.00	-18.67	48.11	7.22	Peak	187	214
5	12010.00	43.64	54.00	-10.36	27.62	16.02	Average	106	267
6	12010.00	55.61	74.00	-18.39	39.59	16.02	Peak	106	267

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.42	54.00	-16.58	38.78	-1.36	Average	100	181
2	2390.00	48.35	74.00	-25.65	49.71	-1.36	Peak	100	181
3	4804.00	48.72	54.00	-5.28	41.50	7.22	Average	150	222
4	4804.00	53.42	74.00	-20.58	46.20	7.22	Peak	150	222
5	12010.00	44.00	54.00	-10.00	27.98	16.02	Average	317	287
6	12010.00	56.71	74.00	-17.29	40.69	16.02	Peak	317	287

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.13	54.00	-16.87	38.49	-1.36	Average	115	27
2	2390.00	48.00	74.00	-26.00	49.36	-1.36	Peak	115	27
3	2483.50	37.73	54.00	-16.27	38.75	-1.02	Average	115	27
4	2483.50	48.33	74.00	-25.67	49.35	-1.02	Peak	115	27
5	4880.00	52.35	54.00	-1.65	46.37	5.98	Average	265	195
6	4880.00	57.50	74.00	-16.50	50.60	6.90	Peak	265	195
7	7320.00	37.42	54.00	-16.58	26.66	10.76	Average	308	167
8	7320.00	49.36	74.00	-24.64	38.60	10.76	Peak	308	167

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.80	54.00	-17.20	38.16	-1.36	Average	113	0
2	2390.00	47.94	74.00	-26.06	49.30	-1.36	Peak	113	0
3	2483.50	37.27	54.00	-16.73	38.29	-1.02	Average	113	0
4	2483.50	48.57	74.00	-25.43	49.59	-1.02	Peak	113	0
5	4880.00	50.20	54.00	-3.80	43.30	6.90	Average	150	222
6	4880.00	55.70	74.00	-18.30	48.80	6.90	Peak	150	222
7	7320.00	38.36	54.00	-15.64	27.60	10.76	Average	284	249
8	7320.00	49.42	74.00	-24.58	38.66	10.76	Peak	284	249

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	1




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.23	54.00	-7.77	47.25	-1.02	Average	113	31
2	2483.50	59.10	74.00	-14.90	60.12	-1.02	Peak	113	31
3	4960.00	53.65	54.00	-0.35	47.62	6.03	Average	265	200
4	4960.00	60.05	74.00	-13.95	53.48	6.57	Peak	265	200
5	7440.00	38.54	54.00	-15.46	27.52	11.02	Average	315	214
6	7440.00	50.60	74.00	-23.40	39.58	11.02	Peak	315	214

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	1



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	50.70	54.00	-3.30	51.72	-1.02	Average	100	357
2	2483.50	63.23	74.00	-10.77	64.25	-1.02	Peak	100	357
3	4960.00	49.81	54.00	-4.19	43.24	6.57	Average	150	221
4	4960.00	54.27	74.00	-19.73	47.70	6.57	Peak	150	221
5	7440.00	37.60	54.00	-16.40	26.58	11.02	Average	162	267
6	7440.00	50.39	74.00	-23.61	39.37	11.02	Peak	162	267

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Test Configuration 2: PCB Dipole antenna

3.5.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	2




The graph displays the radiated unwanted emissions for a PCB Dipole antenna. The y-axis represents the Level in dBuV/m, ranging from 0 to 90. The x-axis represents the Frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 1000 MHz, and 55 dBuV/m from 1000 to 10000 MHz. Six measured peaks are labeled with numbers 1 through 6, corresponding to the data in the table below.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	48.43	17.72	40.00	-22.28	30.63	-12.91	Peak	---	---
2	160.95	13.30	43.50	-30.20	26.97	-13.67	Peak	---	---
3	412.18	17.00	46.00	-29.00	26.72	-9.72	Peak	---	---
4	603.27	20.38	46.00	-25.62	26.14	-5.76	Peak	---	---
5	680.87	21.57	46.00	-24.43	26.24	-4.67	Peak	---	---
6	850.62	23.36	46.00	-22.64	25.14	-1.78	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	30.00	27.64	40.00	-12.36	41.15	-13.51	Peak	---	---
2	48.43	32.92	40.00	-7.08	45.83	-12.91	Peak	---	---
3	94.99	14.79	43.50	-28.71	33.79	-19.00	Peak	---	---
4	552.83	21.02	46.00	-24.98	28.05	-7.03	Peak	---	---
5	582.90	22.17	46.00	-23.83	28.42	-6.25	Peak	---	---
6	611.03	23.83	46.00	-22.17	29.46	-5.63	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.


3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	2

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.92	54.00	-17.08	38.28	-1.36	Average	204	184
2	2390.00	49.89	74.00	-24.11	51.25	-1.36	Peak	204	184
3	4804.00	51.63	54.00	-2.37	45.70	5.93	Average	238	60
4	4804.00	56.74	74.00	-17.26	50.81	5.93	Peak	238	60
5	12010.00	43.68	54.00	-10.32	27.66	16.02	Average	195	237
6	12010.00	56.62	74.00	-17.38	40.60	16.02	Peak	195	237

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	2




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.20	54.00	-16.80	38.56	-1.36	Average	104	267
2	2390.00	48.30	74.00	-25.70	49.66	-1.36	Peak	104	267
3	4804.00	50.92	54.00	-3.08	44.99	5.93	Average	238	254
4	4804.00	56.38	74.00	-17.62	50.45	5.93	Peak	238	254
5	12010.00	43.38	54.00	-10.62	27.36	16.02	Average	175	66
6	12010.00	55.58	74.00	-18.42	39.56	16.02	Peak	175	66

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	2




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.28	54.00	-16.72	38.64	-1.36	Average	201	180
2	2390.00	47.37	74.00	-26.63	48.73	-1.36	Peak	201	180
3	2483.50	37.36	54.00	-16.64	38.38	-1.02	Average	201	180
4	2483.50	47.57	74.00	-26.43	48.59	-1.02	Peak	201	180
5	4880.00	53.53	54.00	-0.47	47.55	5.98	Average	289	29
6	4880.00	57.58	74.00	-16.42	51.60	5.98	Peak	289	29
7	7320.00	37.11	54.00	-16.89	26.35	10.76	Average	180	291
8	7320.00	49.33	74.00	-24.67	38.57	10.76	Peak	180	291

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	2




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	36.80	54.00	-17.20	38.16	-1.36	Average	101	242
2	2390.00	48.00	74.00	-26.00	49.36	-1.36	Peak	101	242
3	2483.50	37.66	54.00	-16.34	38.68	-1.02	Average	101	242
4	2483.50	48.53	74.00	-25.47	49.55	-1.02	Peak	101	242
5	4880.00	48.28	54.00	-5.72	42.30	5.98	Average	279	255
6	4880.00	53.63	74.00	-20.37	47.65	5.98	Peak	279	255
7	7320.00	38.36	54.00	-15.64	27.60	10.76	Average	241	156
8	7320.00	49.42	74.00	-24.58	38.66	10.76	Peak	241	156

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	2




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	51.11	54.00	-2.89	52.13	-1.02	Average	197	184
2	2483.50	63.52	74.00	-10.48	64.54	-1.02	Peak	197	184
3	4960.00	53.66	54.00	-0.34	47.63	6.03	Average	291	21
4	4960.00	56.63	74.00	-17.37	50.60	6.03	Peak	291	21
5	7440.00	38.51	54.00	-15.49	27.49	11.02	Average	261	225
6	7440.00	49.28	74.00	-24.72	38.26	11.02	Peak	261	225

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	49.92	54.00	-4.08	50.94	-1.02	Average	100	306
2	2483.50	62.13	74.00	-11.87	63.15	-1.02	Peak	100	306
3	4960.00	47.63	54.00	-6.37	41.60	6.03	Average	290	289
4	4960.00	52.42	74.00	-21.58	46.39	6.03	Peak	290	289
5	7440.00	37.40	54.00	-16.60	26.38	11.02	Average	260	271
6	7440.00	50.29	74.00	-23.71	39.27	11.02	Peak	260	271

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Test Configuration 3: Isolated Magnetic Dipole antenna

3.5.8 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	3




The graph displays the radiated unwanted emissions for a transmitter using GFSK modulation. The y-axis represents the emission level in dBuV/m, ranging from 0 to 90. The x-axis represents the frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 1000 MHz, and 55 dBuV/m from 1000 to 10000 MHz. Six measured peaks are labeled with numbers 1 through 6, corresponding to the data in the table below.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	49.40	19.43	40.00	-20.57	32.37	-12.94	Peak	---	---
2	159.01	14.44	43.50	-29.06	28.04	-13.60	Peak	---	---
3	396.66	17.01	46.00	-28.99	27.14	-10.13	Peak	---	---
4	531.49	18.39	46.00	-27.61	25.71	-7.32	Peak	---	---
5	639.16	21.28	46.00	-24.72	26.51	-5.23	Peak	---	---
6	822.49	23.90	46.00	-22.10	26.16	-2.26	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	3



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	49.40	31.09	40.00	-8.91	44.03	-12.94	Peak	---	---
2	151.25	14.27	43.50	-29.23	27.73	-13.46	Peak	---	---
3	524.70	18.94	46.00	-27.06	26.32	-7.38	Peak	---	---
4	552.83	20.25	46.00	-25.75	27.28	-7.03	Peak	---	---
5	582.90	23.01	46.00	-22.99	29.26	-6.25	Peak	---	---
6	611.03	23.17	46.00	-22.83	28.80	-5.63	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.9 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	3



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.56	54.00	-16.44	38.69	-1.13	Average	179	176
2	2390.00	49.53	74.00	-24.47	50.66	-1.13	Peak	179	176
3	4804.00	50.72	54.00	-3.28	43.50	7.22	Average	168	215
4	4804.00	56.74	74.00	-17.26	49.52	7.22	Peak	168	215
5	12200.00	43.98	54.00	-10.02	27.59	16.39	Average	217	165
6	12200.00	56.68	74.00	-17.32	40.29	16.39	Peak	217	165

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	3




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.76	54.00	-16.24	38.89	-1.13	Average	152	90
2	2390.00	49.48	74.00	-24.52	50.61	-1.13	Peak	152	90
3	4804.00	47.48	54.00	-6.52	40.26	7.22	Average	160	261
4	4804.00	51.42	74.00	-22.58	44.20	7.22	Peak	160	261
5	12200.00	42.18	54.00	-11.82	25.79	16.39	Average	302	217
6	12200.00	54.98	74.00	-19.02	38.59	16.39	Peak	302	217

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Horizontal	Test Configuration	3




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.12	54.00	-16.88	38.25	-1.13	Average	180	174
2	2390.00	49.14	74.00	-24.86	50.27	-1.13	Peak	180	174
3	2483.50	38.10	54.00	-15.90	38.90	-0.80	Average	180	174
4	2483.50	49.80	74.00	-24.20	50.60	-0.80	Peak	180	174
5	4880.00	50.60	54.00	-3.40	43.70	6.90	Average	168	215
6	4880.00	55.80	74.00	-18.20	48.90	6.90	Peak	168	215
7	7320.00	42.47	54.00	-11.53	31.40	11.07	Average	228	187
8	7320.00	52.82	74.00	-21.18	41.75	11.07	Peak	228	187

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical	Test Configuration	3




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.12	54.00	-16.88	38.25	-1.13	Average	153	88
2	2390.00	49.01	74.00	-24.99	50.14	-1.13	Peak	153	88
3	2483.50	38.07	54.00	-15.93	38.87	-0.80	Average	153	88
4	2483.50	49.46	74.00	-24.54	50.26	-0.80	Peak	153	88
5	4880.00	47.16	54.00	-6.84	40.26	6.90	Average	343	226
6	4880.00	52.50	74.00	-21.50	45.60	6.90	Peak	343	226
7	7320.00	41.20	54.00	-12.80	30.13	11.07	Average	233	175
8	7320.00	52.37	74.00	-21.63	41.30	11.07	Peak	233	175

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal	Test Configuration	3




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.87	54.00	-7.13	47.67	-0.80	Average	179	181
2	2483.50	61.03	74.00	-12.97	61.83	-0.80	Peak	179	181
3	4960.00	53.65	54.00	-0.35	47.62	6.03	Average	177	217
4	4960.00	59.94	74.00	-14.06	53.37	6.57	Peak	177	217
5	7440.00	43.71	54.00	-10.29	32.35	11.36	Average	228	187
6	7440.00	53.87	74.00	-20.13	42.51	11.36	Peak	228	187

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical	Test Configuration	3



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	46.06	54.00	-7.94	46.86	-0.80	Average	168	79
2	2483.50	60.43	74.00	-13.57	61.23	-0.80	Peak	168	79
3	4960.00	50.14	54.00	-3.86	43.57	6.57	Average	290	261
4	4960.00	54.77	74.00	-19.23	48.20	6.57	Peak	290	261
5	7440.00	41.87	54.00	-12.13	30.51	11.36	Average	232	188
6	7440.00	52.11	74.00	-21.89	40.75	11.36	Peak	232	188

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.


Unwanted Emissions Level Measurement

1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.


3.6.3 Test Setup




3.6.4 Test Result of Emissions in non-restricted Frequency Bands



TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)





4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==