



Laird Connectivity in-building wireless antennas are particularly applicable in environments where aesthetics and wide-angle coverage are necessary for successful wireless deployment. Their surprisingly small size allows the antennas to be hidden almost anywhere, providing an invisible solution for most applications.

External antennas are weather resistant and waterproof high gain antennas that provide an excellent choice for outdoor and indoor installation. They can also be mounted on the outside of a housing.

Our antenna products are designed for maximum efficiency and are customizable and scalable to meet your frequency and application requirements. Contact Laird Connectivity today for your complete application solutions.

FEATURES

- Injection-molded ¼ wave flexible cable antenna
- High durability, high efficiency
- Textured finish with strain-relief base
- Available in various standard connectors

SPECIFICATIONS

Model Name	EXDxx
Operating Frequency (MHz)	UHF
VSWR – Max	1.5:1 max at resonance
Max Power - Ambient 25°C (W)	50
Nominal Impedance (Ohms)	50
Polarization	Vertical
Ingress Protection Rating	IP67
Drop Test (M)	1
Operating Temperature – °C (°F)	-40 to +85°C (-40 to +185°F)

CONFIGURATION

PART NUMBER	FREQUENCY BAND	CONNECTOR	AVERAGE LENGTH
EXD360SFU-001	360 – 400 MHz	SF	8.38 – 10.03 (3.3" – 3.95")
EXD400	400 – 420 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMI, SMV, TN, TNX	8.63 – 9.65 (3.4" – 3.8")
EXD410		SMV	
EXD420	420 – 450 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN, TNX	8.38 – 9.12 (3.3" – 3.59")
EXD450	450 – 470 MHz	BN, BNX, KR, MD, MX, MXI, SF, SM, SMI, SMV, TN, TNX	8.49 – 9.86 (2.95" – 3.88")
EXD470	470 – 512 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMI, SMV, TN, TNX	7.11 – 9.14 (2.8" – 3.6")

Note: The EXD model antenna is available in the above frequencies and connectors. Order by antenna model, frequency, and connector. For example: EXD450MX.

The length of each antenna varies according to the chosen connector. Specifications subject to change without notice.



Laird Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird Connectivity product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Connectivity and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Connectivity materials rests with the end user, since Laird Connectivity and its agents cannot be aware of all potential uses. Laird Connectivity makes no warranties as to the fitness, merchantability or suitability of any Laird Connectivity materials or products for any specific or general uses. Laird Connectivity shall not be liable for incidental or consequential damages of any kind. All Laird Connectivity products are sold pursuant to the Laird Connectivity Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2021 Laird Connectivity All Rights Reserved. Laird Connectivity, the Laird Connectivity logo, and other marks are trademarks or registered trademarks of Laird Connectivity or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Connectivity or any third-party intellectual property rights.

sales@lairdconnect.com
support@lairdconnect.com
www.lairdconnect.com

