

Bluetooth Line Card

Laird Connectivity's Bluetooth product portfolio is designed to expedite time to market with the minimum development time required. Our Classic Bluetooth and Bluetooth Low Energy modules are agency-approved and offer feature-rich firmware in an assortment of data rates, ranges (power), and configurations. Our highly reliable Bluetooth modules are easily integrated and can be readily customized by our local support teams to meet your precise requirements.



Bluetooth Low Energy

Dual-Mode BT



Modules not actual size.

	BL5340 Series	BL654 Series (includes USB adapter)	BL654PA Series	BL653 Series	BL653μ Series	BL652 Series	BL651 Series	BT850/BT860 Series (includes USB adapter)	BT900 Series (includes USB adapter)
Chipset	Nordic nRF5340 SoC	Nordic nRF52840	Nordic nRF52840	Nordic nRF52833	Nordic nRF52833	Nordic nRF52832	Nordic nRF52810	Cypress (Infineon) CYW20704 A2	QCA CSR8811
Wireless Standards	BT5.2 + NFC + Thread	BT5.1 + NFC + Thread	BT5.1 + NFC + Thread	BT5.1 + NFC + Thread	BT5.1 + NFC + Thread	BT5 + NFC	BT5	Dual-Mode BT5	Dual-Mode BT v4.0
Type (Flash/RAM)	SMT w/ dual Cortex M33 (App processor 1MB/512KB, Network processor 256KB/64KB) Optional Power Amplifier.	SMT with onboard MCU (ARM Cortex M4F, 1MB/256k)	SMT with onboard MCU (ARM Cortex M4F, 1MB/256k)	SMT with onboard MCU (ARM Cortex M4F, 512KB/128KB)	SMT with onboard MCU (ARM Cortex M4F, 512KB/128KB)	SMT with onboard MCU (ARM Cortex M4F, 512k/64k)	SMT with onboard MCU (ARM Cortex M4, 192k/24k)	SMT with HCI Interface	SMT with onboard MCU (ARM Cortex M3)
Size (mm)	15 x 10 x 2.2 (main module) 21 x 10 x 2.2 (module with power amplifier)	15 x 10 x 2.2 (module) 18.4 x 50.7 x 11 (USB)	22 x 10 x 2.2	15 x 10 x 2.2	6.3 x 5.6 x 1.6 (trace pad variant) 6.3 x 8.6 x 1.6 (int. antenna)	14 x 10 x 2.1	14 x 10 x 2.1	8.5 x 12.9 x 2.2 (module) 50.7 x 18.4 x 11 (USB)	12.5 x 19 x 2.5 (module) 50.7 x 18.4 x 11 (USB)
Antenna Options	Internal Antenna OR External via trace pin	Internal Antenna OR External via IPEX MHF4	Internal Antenna OR External via IPEX MHF4	Internal Antenna OR External via trace pin	Internal Antenna version OR external trace pin version	Internal Antenna OR External via IPEX MHF4	Internal Antenna OR External via IPEX MHF4	Internal Antenna OR External via trace pad	Internal Antenna OR External via U.FL
Data/Control	USB, UART, QSPI, GPIO, ADC, PWM, PDM, QDEC, FREQ output, I ² S, I ² C, SPI, Comparator, Low Power Comparator	USB, UART, GPIO, ADC, PWM, PDM, FREQ output, I ² S, I ² C, SPI	UART, GPIO, ADC, PWM, PDM, FREQ output, I ² S, I ² C, SPI, QSPI	UART, GPIO, ADC, PWM, PDM, FREQ output, I ² C, SPI, NFC, USB	UART, GPIO, ADC, PWM, PDM, FREQ output, I ² C, I ² S, SPI, NFC, USB	UART, GPIO, ADC, PWM, FREQ output, I ² C, SPI	UART, GPIO, I ² C, SPI, ADC, PWM	USB, HCI (BT850/BT851) UART, HCI (BT860)	UART, GPIO, SPI, I ² C, ADC
Tx Power (dBm)	Up to +5 dBm (standard) Up to +10 (PA Version)	-40 to +8 dBm	-26 to +18. (+14 LE CODED PHY)	-40 to +8	-40 to +8	-40 to +4	-40 to +4	Up to +8	-20 to +8
Rx Sensitivity (dBm)	-98 (standard version) TBD (PA Version)	-103 to -95	-98.5 to -107	-103 to -95	-96 typ. @ 1 MBPS -103 typ. @ 128 KBPS	-96 dBm typ.	-93 to -96	-94	-90 typ.
Temp Range	-40°C to +105°C	-40°C to +85°C	-40° to +85° C	-40°C to +105°C	-40°C to +105°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
Software/Firmware	Zephyr RTOS, Nordic nRF Connect	AT Command Set, smartBASIC OR use Nordic SDK, Zephyr	AT Command Set, smartBASIC OR use Nordic SDK, Zephyr	AT Command Set, smartBASIC OR use Nordic SDK, Zephyr	AT Command Set, smartBASIC OR use Nordic SDK, Zephyr	AT Command Set, smartBASIC OR use Nordic SDK, Zephyr	Nordic SDK or Zephyr RTOS	Any external BT software stack via HCI	Hosted or hosted with smartBASIC
Profiles / Services Supported	Any services available via Nordic/Zephyr	Any available via smartBASIC/Nordic SDK/Zephyr	Any available via smartBASIC/Nordic SDK/Zephyr	Any available via smartBASIC/Nordic SDK/Zephyr	Any available via smartBASIC/Nordic SDK/Zephyr	Any available via smartBASIC/Nordic SDK/Zephyr	Any services available via Nordic/Zephyr	Any supported by chosen BT stack	SPP, HID, any custom BLE Service via smartBASIC
Additional Features	BLE Mesh, AoA/AoD, LE Audio / Isochronous Channels, LE Coded (Long Range)	BLE Mesh Packaged USB Adapters	BLE Mesh Ultra Long Range	BLE Mesh Extended Temp Range	BLE Mesh Extended Temp Range Smallest Size	NFC	ANT and proprietary 2.4 GHz	Support for Searan Dotstack. Packaged USB Adapters	Simultaneous BT and BLE connections. Packaged USB Adapters
Certifications	FCC, IC, ETSI, RCM, MIC, Bluetooth SIG	FCC, IC, ETSI, Giteki, RCM, Bluetooth SIG	FCC, IC, RCM, KCC, Bluetooth SIG	FCC, IC, CE, MIC, RCM, Bluetooth SIG	FCC, IC, CE, MIC, RCM, Bluetooth SIG (pending)	FCC, IC, ETSI, Giteki, KCC, RCM, Bluetooth SIG	FCC, IC, ETSI, Giteki, RCM, Bluetooth SIG	FCC, IC, ETSI, Giteki, KCC (BT850 only), MIC (BT850/860), RCM, Bluetooth SIG	FCC, IC, ETSI, Giteki, Bluetooth SIG