

Sona IF573

Regulatory Information

v2.0

The Sona IF573 holds current certifications in the following countries:

Country/Region	Regulatory ID
USA (FCC)	SQG-SONAIF573
Canada (ISED)	3147A-SONAIF573
UK (UKCA)	*No Regulatory ID required
EU	*No Regulatory ID required
Japan (MIC)	201-220656 / 00 (M.2 1318 SMT) 201-220656 / 01 (M.2 2230)
Australia (AS)	*No Regulatory ID required
New Zealand (NZS)	*No Regulatory ID required

1 Certified Antennas

The antennas listed below were tested for use with the Sona IF573. The OEM can choose a different manufacturer's antenna but must make sure it is of same type and that the gain is less than or equal to the antenna that is approved for use.*

***Note:** Japan (MIC) lists applicable antennas on its certificates. If your antenna is not on the approved list, regardless of whether it is comparative, it must be added to the certificate before it can be used in Japan.

Manufacturer	Model	Part Number	Type	Connector	Frequency Range	Peak Gain (dBi)
Ezurio (Laird Connectivity)	FlexMIMO 6E	EFD2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.8
					5.925 GHz - 7.125 GHz	3.3
Ezurio (Laird Connectivity)	FlexPIFA 6E	EFB2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.9
					5.925 GHz - 7.125 GHz	3.8
Ezurio (Laird Connectivity)	Mini NanoBlade Flex 6GHz	EMF2471A3S-10MH4L	PCB Dipole	MHF4L	2.4 GHz - 2.5 GHz	2.4
					4.9 GHz - 6.0 GHz	4.4
					6.0 GHz - 7.125 GHz	5.2
Joymax Electronics	Dipole 6E	TWX-100BRSAX-2001	Dipole	RP-SMA	2.4 GHz-2.4835 GHz	2.0
					5.15 GHz-5.85 GHz	4.0
					5.85 GHz-7.125 GHz	4.0

2 Documentation Requirements

To ensure regulatory compliance, when integrating the Sona IF573 into a host device, it is necessary to meet the documentation requirements set forth by the applicable regulatory agencies. The following sections (FCC, ISED Canada, European Union, and others) outline the information that may be included in the user's guide and external labels for the host devices into which the Sona IF573 is integrated.

3 FCC Regulatory

Model	Part Number	US- FCC ID
Sona IF573	453-00117 / 453-00118 / 453-00119 / 453-00120	SQG-SONAIF573 SQG-SONAIF573

3.1 Antenna Information

The Sona IF573 family has been designed to operate with the antennas listed below.

Manufacturer	Model	Part Number	Type	Connector	Frequency Range	Peak Gain (dBi)
Ezurio (Laird Connectivity)	FlexMIMO 6E	EFD2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.8
					5.925 GHz - 7.125 GHz	3.3
Ezurio (Laird Connectivity)	FlexPIFA 6E	EFB2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.9
					5.925 GHz - 7.125 GHz	3.8
Ezurio (Laird Connectivity)	Mini NanoBlade Flex 6GHz	EMF2471A3S-10MH4L	PCB Dipole	MHF4L	2.4 GHz - 2.5 GHz	2.4
					4.9 GHz - 6.0 GHz	4.4
					6.0 GHz - 7.125 GHz	5.2
Joymax Electronics	Dipole 6E	TWX-100BRSAX-2001	Dipole	RP-SMA	2.4 GHz-2.4835 GHz	2.0
					5.15 GHz-5.85 GHz	4.0
					5.85 GHz-7.125 GHz	4.0

Note: The OEM is free to choose another vendor's antenna of like type and equal or lesser gain as an antenna appearing in the table and still maintain compliance. Reference FCC Part 15.204(c)(4) for further information on this topic.

3.2 FCC Documentation Requirements

Federal Communication Commission (FCC) Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in an installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference; and
2. This device must accept any interference received, including interference that may cause undesired operation.

FCC Radiation Exposure Statement

This product complies with the FCC RF exposure limit set forth for an uncontrolled environment and is safe for intended operation as described in this manual. Further RF exposure reduction can be achieved if the product is kept as far as possible from the user body or is set to a lower output power if such function is available.

This transmitter has been evaluated as a mobile device with a minimum separation distance of 20cm as noted on the FCC grant of authorization. The transmitter should be installed and operated with a minimum distance of 20cm between the radiator and any operator or bystander.

The module (Part Number: 453-00118) can only be used with a host antenna circuit trace layout design in strict compliance with the OEM instructions.

3.2.1 MPE Evaluation

Non-beamforming mode:

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	*Ratio	Pass / Fail
WLAN								
2412-2462	21.02	21.5	2.4	20	0.049	1	0.049	Pass
5180-5240	21.39	21.5	4.4	20	0.077	1	0.077	Pass
5260-5320	21.55	22.0	4.4	20	0.087	1	0.087	Pass
5500-5720	21.67	22.0	4.4	20	0.087	1	0.087	Pass
5745-5825	21.61	22.0	4.4	20	0.087	1	0.087	Pass
BT								
2402-2480	8.24	8.5	2.4	20	0.002	1	0.002	Pass

Frequency Range (MHz)	EIRP(dBm)	Maximum Tune Up Limit (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	*Ratio	Pass / Fail
5925-6425	14.36	14.5	20	0.006	1	0.006	Pass
6425-6525	14.26	14.5	20	0.006	1	0.006	Pass
6525-6875	14.25	14.5	20	0.006	1	0.006	Pass
6875-7125	14.34	14.5	20	0.006	1	0.006	Pass

*Ratio = Power density / Limit.

Beamforming mode:

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	*Ratio	Pass / Fail
2412-2462	17.52	18.0	5.41	20	0.044	1	0.044	Pass
5180-5240	18.38	18.5	7.41	20	0.078	1	0.078	Pass
5260-5320	18.54	19.0	7.41	20	0.087	1	0.087	Pass
5500-5720	18.66	19.0	7.41	20	0.087	1	0.087	Pass
5745-5825	18.60	19.0	7.41	20	0.087	1	0.087	Pass

*Ratio = Power density / Limit.

Remarks:

For 2412~2462MHz:

Directional gain = $2.4 + 10 \cdot \log(2/1) = 5.41$ dBi

For 5180~5825MHz:

Directional gain = $4.4 + 10 \cdot \log(2/1) = 7.41$ dBi

Frequency Range (MHz)	EIRP(dBm)	Maximum Tune Up Limit (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	*Ratio	Pass / Fail
5925-6425	14.36	14.5	20	0.006	1	0.006	Pass
6425-6525	14.26	14.5	20	0.006	1	0.006	Pass
6525-6875	14.25	14.5	20	0.006	1	0.006	Pass
6875-7125	14.34	14.5	20	0.006	1	0.006	Pass

*Ratio = Power density / Limit.

3.2.2 FCC MPE Calculation Simultaneous Transmission

Mode	Max Ratio of Each Mode
<i>Non-beamforming mode</i> WLAN 5GHz	0.087
BT	0.002
Sum	0.089
Limit	1
Pass / Fail	Pass

Mode	Max Ratio of Each Mode
<i>Beamforming mode</i> WLAN 5GHz	0.087
BT	0.002
Sum	0.089
Limit	1
Pass / Fail	Pass

Mode	Max Ratio of Each Mode
<i>Non-beamforming mode</i> WLAN 6GHz	0.006
BT	0.002
Sum	0.008
Limit	1
Pass / Fail	Pass

Mode	Max Ratio of Each Mode
<i>Beamforming mode</i> WLAN 6GHz	0.006
BT	0.002
Sum	0.008
Limit	1
Pass / Fail	Pass

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter.

This device is intended only for OEM integrators under the following condition:

1. The transmitter module may not be co-located with any other transmitter or antenna,

If the condition above is met, further transmitter testing is not required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this installed module.

IMPORTANT NOTE:

If this condition cannot be met (for example, certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID **cannot** be used on the final product. In these circumstances, the OEM integrator is responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

3.3 End-Product Labeling

The end product must be labeled in a visible area with the following: **Contains FCC ID: SQG-SONA/IF573**

3.4 Manual Information to the End User

The OEM integrator must be aware not to provide information to the end user regarding how to install or remove this RF module in the user's manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as shown in this document and other manuals provided by Ezurio. Specifically, the information outlined **FCC Interference Statement**, **FCC Caution Statement** and **FCC Radiation Exposure Statement**.

4 Industry Canada Statement

Model	Part Number	Canada- IC Number
Sona IF573	453-00117 / 453-00118 /	3147A-SONAIF573
Sona IF573	453-00119 / 453-00120	3147A-SONAIF573

4.1 Antenna Information

This radio transmitter (IC: 3147A-SONAIF573) was approved by Innovation, Science and Economic Development (ISED) Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Le présent émetteur radio (IC: 3147A-SONAIF573) a été approuvé par Innovation, Sciences et Développement économique Canada pour fonctionner avec les types d'antenne énumérés ci-dessous et ayant un gain admissible maximal. Les types d'antenne non inclus dans cette liste, et dont le gain est supérieur au gain maximal indiqué pour tout type figurant sur la liste, sont strictement interdits pour l'exploitation de l'émetteur.

Manufacturer	Model	Part Number	Type	Connector	Frequency Range	Peak Gain (dBi)
Ezurio (Laird Connectivity)	FlexMIMO 6E	EFD2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.8
					5.925 GHz - 7.125 GHz	3.3
Ezurio (Laird Connectivity)	FlexPIFA 6E	EFB2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.9
					5.925 GHz - 7.125 GHz	3.8
Ezurio (Laird Connectivity)	Mini NanoBlade Flex 6GHz	EMF2471A3S-10MH4L	PCB Dipole	MHF4L	2.4 GHz - 2.5 GHz	2.4
					4.9 GHz - 6.0 GHz	4.4
					6.0 GHz - 7.125 GHz	5.2
Joymax Electronics	Dipole 6E	TWX-100BRSAX-2001	Dipole	RP-SMA	2.4 GHz-2.4835 GHz	2.0
					5.15 GHz-5.85 GHz	4.0
					5.85 GHz-7.125 GHz	4.0

4.2 ISED Canada Statement

The end user manual shall include all required regulatory information/warning as shown in this manual.

This device complies with Industry Canada's license-exempt RSSs. Operation is subject to the following two conditions:

1. This device may not cause interference; and
2. This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes:

1. *l'appareil ne doit pas produire de brouillage;*
2. *l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.*

4.3 Radiation Exposure Statement

The product complies with the Canada portable RF exposure limit set forth for an uncontrolled environment and are safe for intended operation as described in this manual. The minimum separation distance for mobile use is limited to 20cm assuming use of antenna with 2.4 dBi of gain at 2.4GHz, 4.4 dBi of gain at 5.825 GHz and 5.2 dBi of gain at 6.425 GHz.. The further RF exposure reduction can be achieved if the product can be kept as far as possible from the user body or set the device to lower output power if such function is available.

4.4 Déclaration d'exposition aux radiations:

Le produit est conforme aux limites d'exposition pour les appareils portables RF pour les Etats-Unis et le Canada établies pour un environnement non contrôlé. La distance de séparation minimale pour une utilisation mobile est limitée à 20 cm en supposant l'utilisation d'une antenne avec 2.4 dBi de gain à 2,4 GHz, 4.4 dBi de gain à 5,825 GHz et 5.2 dBi de gain à 6,425 GHz. Le produit est sûr pour un fonctionnement tel que décrit dans ce manuel. La réduction aux expositions RF peut être augmentée si l'appareil peut être conservé aussi loin que possible du corps de l'utilisateur ou que le dispositif est réglé sur la puissance de sortie la plus faible si une telle fonction est disponible.

This device is intended only for OEM integrators under the following conditions:

1. The transmitter module may not be co-located with any other transmitter or antenna.

If the condition above is met, further transmitter testing is not required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed.

Cet appareil est conçu uniquement pour les intégrateurs OEM dans les conditions suivantes:

1. Le module émetteur peut ne pas être coimplanté avec un autre émetteur ou antenne.

Tant que les 1 condition ci-dessus sont remplies, des essais supplémentaires sur l'émetteur ne seront pas nécessaires. Toutefois, l'intégrateur OEM est toujours responsable des essais sur son produit final pour toutes exigences de conformité supplémentaires requis pour ce module installé.

IMPORTANT NOTE:

If this condition cannot be met (for example, certain laptop configurations or co-location with another transmitter), then the Canada authorization is no longer considered valid and the IC ID **cannot** be used on the final product. In these circumstances, the OEM integrator is responsible for re-evaluating the end product (including the transmitter) and obtaining a separate Canada authorization.

NOTE IMPORTANTE:

Dans le cas où ces conditions ne peuvent être satisfaites (par exemple pour certaines configurations d'ordinateur portable ou de certaines co-localisation avec un autre émetteur), l'autorisation du Canada n'est plus considérée comme valide et l'ID IC ne peut pas être utilisé sur le produit final. Dans ces circonstances, l'intégrateur OEM sera chargé de réévaluer le produit final (y compris l'émetteur) et l'obtention d'une autorisation distincte au Canada.

4.5 End-Product Labeling

The final end product must be labeled in a visible area with the following: **Contains IC:** 3147A-SONAIF573

4.6 Plaque signalétique du produit final

*Le produit final doit être étiqueté dans un endroit visible avec l'inscription suivante: **Contient des IC:** 3147A-SONAIF573*

4.7 Manual Information to the End User

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user's manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.

4.8 Manuel d'information à l'utilisateur final

L'intégrateur OEM doit être conscient de ne pas fournir des informations à l'utilisateur final quant à la façon d'installer ou de supprimer ce module RF dans le manuel de l'utilisateur du produit final qui intègre ce module.

Le manuel de l'utilisateur final doit inclure toutes les informations réglementaires requises et avertissements comme indiqué dans ce manuel.

4.9 ICES-003 Issue 7 Compliance Statement

This device was tested and found to be compliant to the requirements of ICES-003, Issue 7, Information Technology Equipment (Including Digital Apparatus).

5 Japan (MIC) Regulatory

The Sona IF573 is approved for use in the Japanese market. The part numbers listed below hold WW type certification. Refer to **ARIB-STD-T66** and **ARIB-STD-T71**, for further guidance on OEM's responsibilities.

Model	Part Number	Certificate Number
Sona IF573	453-00117 / 453-00118 (M.2 1318 SMT)	201-220656 / 00
Sona IF573	453-00119 / 453-00120 (M.2 2230)	201-220656 / 01

5.1 Antenna Information

The Sona IF573 was tested with antennas listed below.

Note: Japan (MIC) lists applicable antennas on its certificates. If your antenna is not on the approved list, regardless of whether it is comparative, it must be added to the certificate before it can be used in Japan.

Manufacturer	Model	Part Number	Type	Connector	Frequency Range	Peak Gain (dBi)
Ezurio (Laird Connectivity)	FlexMIMO 6E	EFD2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.8
					5.925 GHz - 7.125 GHz	3.3
Ezurio (Laird Connectivity)	FlexPIFA 6E	EFB2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.9
					5.925 GHz - 7.125 GHz	3.8
Ezurio (Laird Connectivity)	Mini NanoBlade Flex 6GHz	EMF2471A3S-10MH4L	PCB Dipole	MHF4L	2.4 GHz - 2.5 GHz	2.4
					4.9 GHz - 6.0 GHz	4.4
					6.0 GHz - 7.125 GHz	5.2
Joymax Electronics	Dipole 6E	TWX-100BRSAX-2001	Dipole	RP-SMA	2.4 GHz-2.4835 GHz	2.0
					5.15 GHz-5.85 GHz	4.0
					5.85 GHz-7.125 GHz	4.0

5.2 Labeling Requirements

It is recommended that the host device bears a label showing the Japanese "GITEKI" mark and the certification number accompanied by the following statement:

当該機器には電波法に基づく、技術基準適合証明等を受けた特定無線設備を装着している

Translation: *This equipment contains specified radio equipment that has been certified to the Technical Regulation Conformity Certification under the Radio Law.*



6 Australia and New Zealand Regulatory

RCM: Compliant to standards AS/NZS 4268: 2017+Amd 1:2021, AS/NZS 2772.2:2016+Amd 1:2018, EN 303 687 V1.1.1 (2023-06) and Title 47 CFR FCC Part 15.407.

If this device is used in a product, the OEM has responsibility to verify compliance of the final end product to the Australia/New Zealand (RCM) Standards. All end-products require their own certification (SDoc). You will not be able to leverage the module certification and ship product into the country.

6.1 Antenna Information

The Sona IF573 was tested with antennas listed below.

Note: The OEM is free to choose another vendor's antenna of like type and equal or lesser gain as an antenna appearing in the table and still maintain compliance.

Manufacturer	Model	Part Number	Type	Connector	Frequency Range	Peak Gain (dBi)
Ezurio (Laird Connectivity)	FlexMIMO 6E	EFD2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.8
					5.925 GHz - 7.125 GHz	3.3
Ezurio (Laird Connectivity)	FlexPIFA 6E	EFB2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.9
					5.925 GHz - 7.125 GHz	3.8
Ezurio (Laird Connectivity)	Mini NanoBlade Flex 6GHz	EMF2471A3S-10MH4L	PCB Dipole	MHF4L	2.4 GHz - 2.5 GHz	2.4
					4.9 GHz - 6.0 GHz	4.4
					6.0 GHz - 7.125 GHz	5.2
Joymax Electronics	Dipole 6E	TWX-100BRSAX-2001	Dipole	RP-SMA	2.4 GHz-2.4835 GHz	2.0
					5.15 GHz-5.85 GHz	4.0
					5.85 GHz-7.125 GHz	4.0

6.2 Labeling Requirements

RCM - Regulatory Compliance Mark

- The compliance label applied to the external surface of the packaging used for the device must:
 - occupy an area that is greater than 1% of that external surface;
 - be clearly visible.
- The compliance label must be durable.
- A compliance label must be applied to a device:
 - permanently; or
 - in a way that makes removal or obliteration difficult.



7 UK (UKCA)

7.1 UKCA Declaration of Conformity

Sona IF573

Manufacturer	Ezurio LLC
Products	453-00117 / 453-00118 / 453-00119 / 453-00120
Product Description	Sona™ IF573 - Wi-Fi 6E + Bluetooth® 5.4 Module
UK Legislation	Radio Equipment Regulations 2017/1206 Electromagnetic Compatibility Regulations 2016/1091 Electrical Equipment (Safety) Regulations 2016/1101




Reference standards used for conformity:

Legislation	Requirement	Reference standard(s)
Safety	Low voltage equipment safety	EN 62368-1: 2014+A11:2017, BS EN 62368-1:2014+A11:2017 IEC 62368-1:2014
	RF Exposure	EN 62311:2020, EN 50385:2017, EN 50665:2017
EMC	Protection requirements – Electromagnetic compatibility	EN 301 489-1 v2.2.3 (2019-11) EN 301 489-17 v3.2.4 (2020-09)
Radio Equipment	Means of the efficient use of the radio frequency spectrum (ERM)	EN 300 328 v2.2.2 (2019-07) Wide-band transmission systems
		EN 300 440 v2.1.1 (2017-03) Short Range Devices (SRD) 1 to 40 GHz
		EN 301 893 v2.1.1 (2017-05) 5GHz RLAN
		EN 303 687 v1.1.1 (2023-06) 6 GHz WAS/RLAN

Declaration:

We, Ezurio, declare under our sole responsibility that the essential test suites have been carried out and that the above product to which this declaration relates is in conformity with all the applicable requirements outlined above, when used for its intended purpose.

The minimum distance between the user and/or any bystander and the radiating structure of the transmitter is 20 cm.

Place of Issue:	Ezurio LLC W66N220 Commerce Court, Cedarburg, WI 53012 USA tel: +1-262-375-4400 fax: +1-262-364-2649
Date of Issue:	March 6, 2025
Name of Authorized Person:	Brian Petted, Technology Leader
Signature of Authorized Person:	

8 EU Regulatory

The Sona IF573 was tested for compliance with relevant standards for the EU market. The Sona IF573 module was evaluated using an antenna with 2.4 dBi of gain at 2.4GHz, 4.4 dBi of gain at 5.18 GHz and 5.2 dBi of gain at 6.425 GHz. The OEM can operate the Sona IF573 module with another antenna of a similar type or brand but must ensure that the gain does not exceed the values listed in the antenna section to maintain the Ezurio approval.

The OEM should consult with a qualified test house before entering their device into an EU member country to make sure all regulatory requirements have been met for their complete device. The OEM will need complete all Host integration, RF exposure, and End-Product EMC evaluations/testing.

8.1 Antenna Information

The Sona IF573 was tested with antennas listed below.

Note: The OEM is free to choose another vendor's antenna of like type and equal or lesser gain as an antenna appearing in the table and still maintain compliance.

Manufacturer	Model	Part Number	Type	Connector	Frequency Range	Peak Gain (dBi)
Ezurio (Laird Connectivity)	FlexMIMO 6E	EFD2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.8
					5.925 GHz - 7.125 GHz	3.3
Ezurio (Laird Connectivity)	FlexPIFA 6E	EFB2471A3S-10MH4L	PIFA	MHF4L	2.4 GHz - 2.5 GHz	2.2
					4.9 GHz - 5.925 GHz	3.9
					5.925 GHz - 7.125 GHz	3.8
Ezurio (Laird Connectivity)	Mini NanoBlade Flex 6GHz	EMF2471A3S-10MH4L	PCB Dipole	MHF4L	2.4 GHz - 2.5 GHz	2.4
					4.9 GHz - 6.0 GHz	4.4
					6.0 GHz - 7.125 GHz	5.2
Joymax Electronics	Dipole 6E	TWX-100BRSAX-2001	Dipole	RP-SMA	2.4 GHz-2.4835 GHz	2.0
					5.15 GHz-5.85 GHz	4.0
					5.85 GHz-7.125 GHz	4.0

User's Guide Requirements

The integrator must include specific information in the user's guide for the device into which the Sona IF573 is integrated. In addition to the required FCC and IC statements outlined above, the following Radio Equipment Directive (RED) statements must be added in their entirety and without modification into a prominent place in the user's guide for the device into which the Sona IF573 is integrated:

This device complies with the essential requirements of the 2014/53/EU – Radio Equipment Directive (RED). The following test methods have been applied in order to prove presumption of conformity with the essential requirements of the 2014/53/EU – Radio Equipment Directive (RED):

Standard	Description
IEC/EN 62368-1: 2014 + A11:2017	Audio/video, information and communication technology equipment - Part 1: Safety requirements
IEC/EN 62311:2020	Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)
IEC/EN 50385:2017	Product standard to demonstrate the compliance of base station equipment with radio frequency electromagnetic field exposure limits (110 MHz – 100GHz), when placed on the market
IEC/EN 50665:2017	Generic standard for assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz – 300 GHz)
EN 301 489-1 v2.2.3 (2019-11)	Electromagnetic compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements
EN 301 489-17 v3.2.4 (2020-09)	Electromagnetic compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for Broadband and Wideband Data Transmission Systems; Harmonised Standard for ElectroMagnetic Compatibility
EN 300 328 v2.2.2 (2019-07)	Electromagnetic compatibility and Radio Spectrum Matters (ERM); Wideband Transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using spread spectrum modulation techniques; Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive
EN 300 440 v2.1.1 (2017-02)	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short range devices; Radio equipment to be used in the 1 GHz to 40 GHz frequency range
EN 301 893 v2.1.1 (2017-05)	5 GHz RLAN; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU
EN 303 687 V1.1.1 (2023-06)	6 GHz WAS/RLAN; Harmonised Standard for access to radio spectrum
EU 2015/863 (RoHS 3)	Declaration of Compliance – EU Directive 2015/863; Reduction of Hazardous Substances (RoHS)

This device is a 2.4 GHz/5GHz/6GHz wideband transmission system (transceiver), intended for use in all EU member states and EFTA countries.

български [Bulgarian]	С настоящото [име на производителя] декларира, че това устройство [вид оборудване] е в съответствие със съществените изисквания и други приложими разпоредби на Директиви 2014/53/EC
Hrvatski [Croatian]	[naziv proizvođača] ovim putem izjavljuje da je ovaj uređaj [vrsta opreme] sukladan osnovnim zahtjevima i ostalim bitnim odredbama Direktiva 2014/53/EU
Česky [Czech]	[Jméno výrobce] tímto prohlašuje, že tento [typ zařízení] je ve shodě se základními požadavky a dalšími příslušnými ustanoveními směrnice 2014/53/EU.
Dansk [Danish]	Undertegnede [fabrikantens navn] erklærer herved, at følgende udstyr [udstyrets typebetegnelse] overholder de væsentlige krav og øvrige relevante krav i direktiv 2014/53/EU.
Deutsch [German]	Hiermit erklärt [Name des Herstellers], dass sich das Gerät [Gerätetyp] in Übereinstimmung mit den grundlegenden Anforderungen und den übrigen einschlägigen Bestimmungen der Richtlinie 2014/53/EU befindet.
Eesti [Estonian]	Käesolevaga kinnitab [tootja nimi] seadme [seadme tüüp] vastavust direktiivi 2014/53/EL põhinõuetele ja nimetatud direktiivist tulenevatele teistele asjakohastele sätetele.

English	Hereby, <i>[name of manufacturer]</i> , declares that this <i>[type of equipment]</i> is in compliance with the essential requirements and other relevant provisions of Directive 2014/53/EU.
Español [Spanish]	Por medio de la presente <i>[nombre del fabricante]</i> declara que el <i>[clase de equipo]</i> cumple con los requisitos esenciales y cualesquiera otras disposiciones aplicables o exigibles de la Directiva 2014/53/UE.
Ελληνική [Greek]	ΜΕ ΤΗΝ ΠΑΡΟΥΣΑ <i>[όνομα του κατασκευαστή]</i> ΔΗΛΩΝΕΙ ΟΤΙ <i>[εξοπλισμού]</i> ΣΥΜΜΟΡΦΩΝΕΤΑΙ ΠΡΟΣ ΤΙΣ ΟΥΣΙΩΔΕΙΣ ΑΠΑΙΤΗΣΕΙΣ ΚΑΙ ΤΙΣ ΛΟΙΠΕΣ ΣΧΕΤΙΚΕΣ ΔΙΑΤΑΞΕΙΣ ΤΗΣ ΟΔΗΓΙΑΣ 2014/53/ΕΕ.
Français [French]	Par la présente <i>[nom du fabricant]</i> déclare que l'appareil <i>[type d'appareil]</i> est conforme aux exigences essentielles et aux autres dispositions pertinentes de la directive 2014/53/UE.
Íslenska [Icelandic]	Hér, <i>[Nafn framleiðanda]</i> , því yfir að þetta <i>[gerð búnaðar]</i> tæki er í samræmi við grunnkröfur og önnur viðeigandi ákvæði tilskipana 2014/53/ ESB
Italiano [Italian]	Con la presente <i>[nome del costruttore]</i> dichiara che questo <i>[tipo di apparecchio]</i> è conforme ai requisiti essenziali ed alle altre disposizioni pertinenti stabilite dalla direttiva 2014/53/UE.
Latviešu valoda [Latvian]	Ar šo <i>[izgatavotājasaukums]</i> deklarē, ka <i>[iekārtas tips]</i> atbilst Direktīvas 2014/53/ES būtiskajām prasībām un citiemar to saistītajiem noteikumiem.
Lietuvių kalba [Lithuanian]	Šiuo <i>[gamintojo pavadinimas]</i> deklaruoją, kad šis <i>[įrangos tipas]</i> atitinka esminius reikalavimus ir kitas 2014/53/ES Direktyvos nuostatas.
Nederlands [Dutch]	Hierbij verklaart <i>[naam van de fabrikant]</i> dat het toestel <i>[type van toestel]</i> in overeenstemming is met de essentiële eisen en de andere relevante bepalingen van richtlijn 2014/53/EU.
Malti [Maltese]	Hawnhekk, <i>[isem tal-manifattur]</i> , jiddikjara li dan <i>[il-mudel tal-prodott]</i> jikkonforma mal-htigijiet essenzjali u ma provvedimenti oħrajn rilevanti li hemm fid-Dirrettiva 2014/53/UE.
Magyar [Hungarian]	Alulírott, <i>[gyártó neve]</i> nyilatkozom, hogy a <i>[... típus]</i> megfelel a vonatkozó alapvető követelményeknek és az 2014/53/EU irányelv egyéb előírásainak.
Norsk [Norwegian]	Herved <i>[navnet på produsenten]</i> , erklærer at denne <i>[type utstyr]</i> enheten, er i samsvar med de grunnleggende kravene og andre relevante bestemmelser i direktivene 2014/53/EU
Polski [Polish]	Niniejszym <i>[nazwa producenta]</i> oświadczam, że <i>[nazwa wyrobu]</i> jest zgodny z zasadniczymi wymogami oraz pozostałymi stosownymi postanowieniami Dyrektywy 2014/53/UE.
Português [Portuguese]	<i>[Nome do fabricante]</i> declara que este <i>[tipo de equipamento]</i> está conforme com os requisitos essenciais e outras disposições da Directiva 2014/53/UE.
Română [Romanian]	Prin prezenta, <i>[numele producătorului]</i> declară că acest dispozitiv <i>[tipul de echipament]</i> este în conformitate cu cerințele esențiale și alte prevederi relevante ale Directivei 2014/53/UE
Slovenščina [Slovenian]	<i>[Ime proizvajalca]</i> izjavlja, da je ta <i>[tip opreme]</i> v skladu z bistvenimi zahtevami in ostalimi relevantnimi določili direktive 2014/53/EU.
Slovenčina [Slovak]	<i>[Menovýrobcu]</i> týmto vyhlasuje, že <i>[typzariadenia]</i> spĺňa základné požiadavky a všetky príslušné ustanovenia Smernice 2014/53/EU.
Suomi [Finnish]	<i>[Valmistaja]</i> vakuuttaa täten että <i>[laitteen tyyppimerkintä]</i> tyyppinen laite on direktiivin 2014/53/EU oleellisten vaatimusten ja sitä koskevien direktiivin muiden ehtojen mukainen.
Svenska [Swedish]	Härmed intygar <i>[företag]</i> att denna <i>[utrustningstyp]</i> står i överensstämmelse med de väsentliga egenskapskrav och övriga relevanta bestämmelser som framgår av direktiv 2014/53/EU.

8.2 EU Declarations of Conformity

Manufacturer	Ezurio LLC
Products	453-00117 / 453-00118 / 453-00119 / 453-00120
Product Description	Sona™ IF573 - Wi-Fi 6E + Bluetooth® 5.4 Module
EU Directives	2014/53/EU – Radio Equipment Directive (RED)




Reference standards used for presumption of conformity:

Legislation	Requirement	Reference standard(s)	
3.1a	Low voltage equipment safety	EN 62368-1: 2014+A11:2017, BS EN 62368-1:2014+A11:2017 IEC 62368-1:2014	
	RF Exposure	EN 62311:2020, EN 50385:2017, EN 50665:2017	
3.1b	Protection requirements – Electromagnetic compatibility	EN 301 489-1 v2.2.3 (2019-11) EN 301 489-17 v3.2.4 (2020-09)	
3.2	Means of the efficient use of the radio frequency spectrum (ERM)	EN 300 328 v2.2.2 (2019-07)	Wide-band transmission systems
		EN 300 440 v2.1.1 (2017-03)	Short Range Devices (SRD) 1 to 40 GHz
		EN 301 893 v2.1.1 (2017-05)	5GHz RLAN
		EN 303 687 v1.1.1 (2023-06)	6 GHz WAS/RLAN

Declaration:

We, Ezurio, declare under our sole responsibility that the essential radio test suites have been carried out and that the above product to which this declaration relates is in conformity with all the applicable essential requirements of Article 3 of the EU Radio Equipment Directive 2014/53/EU, when used for its intended purpose.

The minimum distance between the user and/or any bystander and the radiating structure of the transmitter is 20 cm.

Place of Issue:	Ezurio LLC W66N220 Commerce Court, Cedarburg, WI 53012 USA tel: +1-262-375-4400 fax: +1-262-364-2649
Date of Issue:	March 6, 2025
Name of Authorized Person:	Brian Petted, Technology Leader
Signature of Authorized Person:	

9 Regulatory Domain Support

Domain support but not currently certified for – TBD

10 Revision History

Version	Date	Notes	Contributor(s)	Approver
1.0	10 Oct 2023	Initial version	Dave Drogowski	Brian Petted
2.0	7 Mar 2025	Update to Ezurio format and new RIG template.	Dave Drogowski	Tom Smith

Ezurio's products are subject to standard [Terms & Conditions](#).

© Copyright 2025 Ezurio All Rights Reserved. Any information furnished by Ezurio and its agents is believed to be accurate but cannot be guaranteed. All specifications are subject to change without notice. Responsibility for the use and application of Ezurio materials or products rests with the end user since Ezurio and its agents cannot be aware of all potential uses. Ezurio makes no warranties as to non-infringement nor as to the fitness, merchantability, or sustainability of any Ezurio materials or products for any specific or general uses. Ezurio or any of its affiliates or agents shall not be liable for incidental or consequential damages of any kind. All Ezurio products are sold pursuant to the Ezurio Terms and Conditions of Sale in effect from time to time, a copy of which will be furnished upon request. Nothing herein provides a license under any Ezurio or any third-party intellectual property right. Ezurio and its associated logos are trademarks owned by Ezurio and/or its affiliates.