


Secure, Smart, Standardized, and Connected IOT: Powerful NXP Edge Processing with Wi-Fi 6 or Wi-Fi 6E

Our customers asked for a high performance, robust SoM that simplifies their BOM, has reliable connectivity, uses a standard form factor, and is globally certified. One with multiple software options, a proven security architecture, long term software support, and security fixes.

Our new Nitrogen8M Mini SMARC is powered by NXP's class-leading i.MX 8M Mini processor, NXP PMIC PF8121, and our Sona Wi-Fi 6 or 6E and Bluetooth 5.4 wireless module families based on leading NXP and Infineon solutions, high performance LPDDR4 RAM, and eMMC storage. We combine this with our common SMARC carrier board; together they can serve as a single board computer (SBC) that can speed your product to market. Alternately, work with us to create a custom carrier that fits your mechanical, environmental, temperature, and interface requirements.

- **Powerful Heterogenous Multiprocessing:** Up to 1.8 GHz quad-core Cortex-A53 microprocessor and 400 MHz Cortex-M4 microcontroller allow you to run Linux and an RTOS on dedicated, hardware-firewalled subsystems.
- **Diverse Interfaces:** Display, network, data, audio, camera, and more.
- **SMARC 2.2 Standard Form Factor:** 82mm x 50mm SMARC edge connector form factor which includes onboard ethernet PHY and a USB hub controller. One design supports multiple processor, memory, and wireless configurations.
- **Hardware Upgrade Roadmap:** Build a product design that can easily be upgraded to the latest processors and wireless options as future Ezurio SOMs based on the SMARC standard are released.
- **Advanced Common Carrier/Development Board:** Display, camera, audio, Ethernet, USB, PCI-Express, I2C, SPI, UART, and more. Use in development, as an SBC equivalent in a product, or as reference designs for your carrier board design.



- **Multiple options for Wi-Fi 6 or 6E (802.11ax) and Bluetooth 5.3 or 5.4**
 - Sona NX611 (**NXP IW611**) dual-band Wi-Fi 6 and Bluetooth 5.3
 - Sona IF573 (**Infineon CYW55573**) tri-band Wi-Fi 6E and Bluetooth 5.4
- **Operating Temperature Range:** Commercial Rating (0° to +70 °C) and Industrial Rating (-40° to +85 °C)
- **Multiple high performance memory options:**

1GB LPDDR4 /	2GB LPDDR4 /	4GB LPDDR4 /
16GB eMMC	16GB eMMC	16GB eMMC
- Extensive range of **pre-certified antennas** for optional Sona wireless modules
- **US based manufacturing with Global Options:** Manufacture in USA for local customer base and US market needs. Global manufacturing capability as part of Ezurio footprint, growing reach to EMEA & APAC regions.
- **Diverse Software and Board Support Options:** Yocto Linux / Buildroot Linux / Android for Cortex-A53s, Zephyr RTOS/FreeRTOS for the Cortex-M4
- **Secure and Encrypted Boot, Secure Enclave, and Secure File Storage:** Robust, secure, and optionally encrypted boot mechanism to ensure only trusted software boots on your device. Optionally store and use secure keys, certificates, and credentials in run-time isolated trusted environment.
- **Power Efficient:** NXP PMIC, power optimized LPDDR4 and eMMC memory, core shut off, clock/voltage scaling, low power interfaces, power optimized single stream Wi-Fi mode enable highly optimized power consumption.
- **Long term hardware availability and software support:** Ezurio's products are specifically designed to meet the needs of the industrial and medical markets, which typically require 10 year or more product lifecycles. **Long-term software support** includes LTS Yocto Linux and Zephyr RTOS support with vulnerability remediation.

Key Features



Reliable Connectivity: Optional Wi-Fi 6/6E and BT 5.3/5.4 Excellent Wi-Fi and BT Classic / LE connectivity in difficult environments, plus enterprise Wi-Fi support via WPA3-Enterprise for more secure and robust connections.



Graphics, Video, Vision, and Audio

MIPI-DSI or LVDS display up to 1080p60, GPU, 1080p60 multi codec encode and decode VPU, MIPI-CSI camera interface, I2S audio interfaces



Secure Enclave and Secure Boot Powered by LMX 8M Mini

Dedicated on-board security hardware, secure boot Linux, and high-performance and flexible secure storage system for passwords, certificates, and data storage.



Robust Software and Speed to Market

Choose from Yocto Linux, Buildroot Linux, or Android for the Cortex-A53s, Zephyr RTOS and FreeRTOS for the Cortex-M4



Global Radio Approvals

Sona wireless modules carry several modular FCC, IC, CE, UKCA, RCM, MIC, KC, and Bluetooth SIG approvals.



Personal Support from Design to Manufacture

Our industry-renowned support and field application engineering team is passionate about helping you speed your design to market.

Application Areas



Smart Buildings & Appliances



Touchscreens and Displays



Industrial IoT, Vision Systems



Food and Beverage



Medical Devices

Specifications

Category	Feature	Specification
Processors	Microprocessor	4x Cortex®-A53 cores @ up to 1.8 GHz
	Microcontroller	1x Cortex®-M4 core @ 400 MHz
	Graphics	GC7000NanoUltra for 3D and GC520L for 2D
Memory	RAM	1GB, 2GB, and 4GB
	Storage	16GB. <i>(For custom sizes, please contact Sales)</i>
Graphics and Video	Graphics Processing Unit	<ul style="list-style-type: none"> 50 million triangles/sec 500 megapixel/sec
	Video Processing Unit	Video Decode <ul style="list-style-type: none"> 1080p60 HEVC/H.265 1080p60 VP9 Profile 0, 2 1080p60 VP8 1080p60 AVC/H.264 Baseline, Main, High decoder
	Display Interfaces	<ul style="list-style-type: none"> 1x MIPI DSI, up to 1080p60 (Optional, MOQ required) 1x LVDS, up to 720p60
Vision	Camera	<ul style="list-style-type: none"> 1x 4-lane MIPI CSI
Audio	Audio Interfaces	<ul style="list-style-type: none"> 2x I2S (Optionally 1 as HDA) 1x PCM (for onboard optional Bluetooth)
Peripherals	Input/Output	<ul style="list-style-type: none"> 1x PCIe Gen2 1-Lane Dual Mode with PHY 3x USB 2.0 with PHY 1x Gbit Ethernet including PHY with IEEE® 1588, AVB, EEE
		<ul style="list-style-type: none"> 3x UART 5x I2C 2x SPI 1x SDIO 3.0/eMMC 5.1 14x GPIO
Optional Wireless Specification	Wi-Fi	Wi-Fi 6 or Wi-Fi 6E
	Frequency	Dual-Band 2.4GHz & 5GHz or Tri-Band 2.4GHz, 5GHz, & 6GHz
	Bluetooth	Bluetooth 5.4
Supply Voltage		5 V
Physical	Dimensions	SMARC 2.2 Standard - 82mm x 50mm
Environmental	Temp Range	0°C to +70°C (Commercial) and -40° to +85 °C (Industrial)
Miscellaneous	Lead Free	Lead-free and RoHS-compliant
	Carrier Board	Carrier board, accessories, and evaluation software
Qualifications	Bluetooth® SIG	Bluetooth SIG Qualified Listing
Regulatory	Approvals	FCC/IC/CE/MIC/RCM on optional Sona wireless modules

For full specifications on the Nitrogen8M Plus SMARC, please see the appropriate datasheet.

Ordering Information

Part	Description
8MM_SMARC_SOM_1r16e	SMARC SOM: i.MX8M MINI Quad / 1GB / 16GB eMMC
8MM_SMARC_SOM_2r16e	SMARC SOM: i.MX8M MINI Quad / 2GB / 16GB eMMC
8MM_SMARC_SOM_4r16e	SMARC SOM: i.MX8M MINI Quad / 4GB / 16GB eMMC
8MM_SMARC_SOM_1r16e_i	SMARC SOM: i.MX8M MINI Quad / 1GB / 16GB eMMC / -40° to +85°C
8MM_SMARC_SOM_2r16e_i	SMARC SOM: i.MX8M MINI Quad / 2GB / 16GB eMMC / -40° to +85°C
8MM_SMARC_SOM_4r16e_i	SMARC SOM: i.MX8M MINI Quad / 4GB / 16GB eMMC / -40° to +85°C
8MM_SMARC_SOM_1r16e_NX611_1M	SMARC SOM: i.MX8M MINI Quad / 1GB / 16GB eMMC / NX611
8MM_SMARC_SOM_1r16e_NX611_1M_i	SMARC SOM: i.MX8M MINI Quad / 1GB / 16GB eMMC / NX611 / -40 to +85C
8MM_SMARC_SOM_2r16e_NX611_1M	SMARC SOM: i.MX8M MINI Quad / 2GB / 16GB eMMC / NX611
8MM_SMARC_SOM_2r16e_NX611_1M_i	SMARC SOM: i.MX8M MINI Quad / 2GB / 16GB eMMC / NX611 / -40 to +85C
8MM_SMARC_SOM_4r16e_NX611_1M	SMARC SOM: i.MX8M MINI Quad / 4GB / 16GB eMMC / NX611
8MM_SMARC_SOM_4r16e_NX611_1M_i	SMARC SOM: i.MX8M MINI Quad / 4GB / 16GB eMMC / NX611/ -40 to +85C
8MM_SMARC_SOM_1r16e_IF573_3M	SMARC SOM: i.MX8M MINI Quad / 1GB / 16GB eMMC / IF573
8MM_SMARC_SOM_1r16e_IF573_3M_i	SMARC SOM: i.MX8M MINI Quad / 1GB / 16GB eMMC / IF573 / -40° to +85°C
8MM_SMARC_SOM_2r16e_IF573_3M	SMARC SOM: i.MX8M MINI Quad / 2GB / 16GB eMMC / IF573

Part	Description
8MM_SMARC_SOM_2r16e_IF573_3M_i	SMARC SOM: i.MX8M MINI Quad / 2GB / 16GB eMMC / IF573 / -40° to +85°C
8MM_SMARC_SOM_4r16e_IF573_3M	SMARC SOM: i.MX8M MINI Quad / 4GB / 16GB eMMC / IF573
8MM_SMARC_SOM_4r16e_IF573_3M_i	SMARC SOM: i.MX8M MINI Quad / 4GB / 16GB eMMC / IF573 / -40° to +85°C
SMARC_CAR	Universal Carrier Board Kit - SMARC (Note: SOM sold separately)

Ezurio's products are subject to standard [Terms & Conditions](#).