

CE RF Exposure Report

Equipment : 802.11ac Professional Wi-Fi + BT5.0 Module
Model No. : SU60-SOMC (453-00003),
SU60-SOMC-2G (453-00004)
(please refer to section 1.1.1 for more details.)
Brand Name : Laird Connectivity
Applicant : Laird Connectivity, Inc.
Address : W66N220 Commerce Court, Cedarburg,
Wisconsin 53012, USA
Standard : EN 62311:2008
EN 50665:2017
EN 50385:2017
Received Date : Apr. 11, 2018
Tested Date : Sep. 18 ~ Oct. 03, 2018

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


James Fan / Assistant Manager

Approved by:


Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	4
1.1	Information.....	4
2	RF EXPOSURE EVALUATION	6
2.1	Limits	6
2.2	Evaluation Formula for Far-Field.....	7
2.3	Deviation from Test Standard and Measurement Procedure.....	7
2.4	Measurement Uncertainty	7
2.5	Evaluation Results.....	8
3	TEST LABORATORY INFORMATION	9

Release Record

Report No.	Version	Description	Issued Date
EA841101-02	Rev. 01	Initial issue	Jul. 30, 2020

1 General Description

1.1 Information

This report is issued as a supplementary report to original ICC report no. EA841101. The difference is concerned with following items:

- ✧ New applicant name

Due to no impact on tests, all data remain unchanged.

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
Laird	SU60-SOMC (453-00003)	802.11ac Professional Wi-Fi + BT5.0 Module	2G/1G MCP
	SU60-SOMC-2G (453-00004)		4G/2G MCP
✦ The above models, both options were assessed and SU60-SOMC-2G (453-00004) was found to be worst case and was selected for the final testing.			

1.1.2 Specification of the Equipment under Test (EUT)

WLAN	
Operating Frequency	802.11b/g/n: 2412 MHz ~ 2472 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5700 MHz
Modulation Type	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
BT	
Operating Frequency	2402 MHz ~ 2480 MHz
Modulation Type	Bluetooth 4.2 LE: GFSK Bluetooth BR(1Mbps): GFSK Bluetooth EDR (2Mbps): $\pi/4$ -DQPSK Bluetooth EDR (3Mbps): 8-DPSK

1.1.3 Antenna Details

For WLAN

Brand	Model	Type	Connector	Operating Frequency (MHz) / Gain (dBi)			
				2400~2483.5	5150~5250	5250~5350	5470~5725
LSR	001-0009	Dipole	IPEX U.FL	2	2		
Laird	NanoBlade-IP04	PCB Dipole	IPEX U.FL	2	3.9	3.9	4
Laird	MAF95310 Mini NanoBlade Flex	PCB Dipole	IPEX U.FL	2.79	3.38		
LSR	FlexPIFA 001-0016	PIFA	IPEX U.FL	2.5	3		
Ethertronics	WLAN_1000146	Magnetic Dipole	IPEX U.FL	2.5	3.5	3.5	3.5
Laird	MIMO FlexPIFA Antenna	PIFA	IPEX U.FL	2	3		
LSR	001-0009 (with filter)	Dipole	IPEX U.FL	2	2		

For Bluetooth

Brand	Model	Type	Connector	Gain (dBi)
LSR	001-0009	Dipole	IPEX U.FL	2
Laird	NanoBlade-IP04	PCB Dipole	IPEX U.FL	2
Laird	MAF95310 Mini NanoBlade Flex	PCB Dipole	IPEX U.FL	2.79
LSR	FlexPIFA 001-0016	PIFA	IPEX U.FL	2.5
Ethertronics	WLAN_1000146	Magnetic Dipole	IPEX U.FL	2.5
Laird	MIMO FlexPIFA Antenna	PIFA	IPEX U.FL	2
LSR	001-0009 (with filter)	Dipole	IPEX U.FL	2

1.1.4 EUT Operational Condition

Power Supply Type	3.3Vdc from host
-------------------	------------------

2 RF exposure evaluation

2.1 Limits

The device shall comply with the relevant limits for general public exposure specified as basic restrictions or reference levels in the Council Recommendation 1999/519/EC as below table.

Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	—	$3,2 \times 10^4$	4×10^4	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Notes:

1. f as indicated in the frequency range column.
2. For frequencies between 100 kHz and 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any six-minute period.
3. For frequencies exceeding 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any $68/f^{1.05}$ -minute period (f in GHz).
4. No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.

2.2 Evaluation Formula for Far-Field

Follow below formula to evaluate E-field strength.

$$E = \frac{\sqrt{30 * P * G}}{R}$$

Where

P(W) is the input power of antenna

G is the gain of antenna

R(m) Is the distance between the human body and the antenna

2.3 Deviation from Test Standard and Measurement Procedure

None

2.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Parameters	Uncertainty
Conducted power	±0.808 dB

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

2.5 Evaluation Results

Mode	Frequency Range (MHz)	Maximum E.I.R.P. (dBm)	Distance (m)	Evaluation E-Field Strength (V/m)	Limit (V/m)	PASS / FAIL
BT LE	2402-2480	9.98	0.20	2.73	61	Pass
BT EDR	2402-2480	12.50	0.20	3.65	61	Pass
Wi-Fi	2412-2472	19.09	0.20	7.80	61	Pass
	5180-5240	21.94	0.20	10.83	61	Pass
	5260-5320	21.81	0.20	10.67	61	Pass
	5500-5700	22.05	0.20	10.97	61	Pass

3 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==