

CE Test Report

Equipment : 802.11ac Professional Wi-Fi + BT5.0 Module
Model No. : SU60-SOMC (453-00003),
SU60-SOMC-2G (453-00004)
(please refer to section 1.1.1 for more details.)
Brand Name : Laird Connectivity
Applicant : Laird Connectivity, Inc.
Address : W66N220 Commerce Court, Cedarburg,
Wisconsin 53012, USA
Standard : EN 300 328 V2.2.2 (2019-07)
Received Date : Apr. 15, 2020
Tested Date : Sep. 19 ~ Oct. 04, 2018(for original test)
Apr. 15, 2020 (for new test)

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


James Fan / Assistant Manager

Approved by:


Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	9
1.3	Test Setup Chart	9
1.4	Test Equipment List and Calibration Data.....	10
1.5	Testing Applied Standards	12
1.6	Deviation from Test Standard and Measurement Procedure.....	12
1.7	Measurement Uncertainty	12
2	TEST CONFIGURATION	13
2.1	Testing Condition	13
2.2	Testing Facility.....	13
2.3	The Worst Test Modes and Channel Details	14
3	TRANSMITTER TEST RESULTS.....	15
3.1	RF Output Power	15
3.2	Accumulated Transmit Time, Minimum Frequency Occupation and Hopping Sequence.....	17
3.3	Hopping Frequency Separation.....	21
3.4	Occupied Channel Bandwidth	23
3.5	Transmitter Unwanted Emissions in the Out-Of-Band Domain.....	25
3.6	Transmitter Unwanted Emissions in the Spurious Domain	38
4	RECEIVER TEST RESULTS	64
4.1	Receiver Spurious Emissions.....	64
5	ADAPTIVITY TEST RESULTS	90
5.1	Adaptivity and Unwanted Signal Parameters	90
6	RECEIVER BLOCKING TEST RESULTS.....	96
6.1	Receiver Blocking.....	96
7	PHOTOGRAPHS OF THE TEST CONFIGURATION	100
8	TEST LABORATORY INFORMATION	103

Release Record

Report No.	Version	Description	Issued Date
ER841101-02AD	Rev. 01	Initial issue	Jul. 30, 2020

Summary of Test Results

Ref. Std. Clause	Test Items	Measured	Result
4.3.1.2	RF Output Power	EIRP (dBm): 12.50	Pass
4.3.1.3	Duty cycle, Tx-Sequence, Tx-gap	Only for non-adaptive equipment	N/A
4.3.1.4	Dwell time, Minimum Frequency Occupation & Hopping Sequence	Meet the requirement of limit.	Pass
4.3.1.5	Hopping Frequency Separation	Meet the requirement of limit.	Pass
4.3.1.6	Medium Utilisation (MU) factor	Only for non-adaptive equipment	N/A
4.3.1.7	Adaptivity	Meet the requirement of limit.	Pass
4.3.1.8	Occupied Channel Bandwidth	Meet the requirement of limit.	Pass
4.3.1.9	Transmitter unwanted emissions in the out of band domain	Meet the requirement of limit.	Pass
4.3.1.10	Transmitter unwanted emissions in the spurious domain	Meet the requirement of limit.	Pass
4.3.1.11	Receiver spurious emissions	Meet the requirement of limit.	Pass
4.3.1.12	Receiver Blocking	Meet the requirement of limit.	Pass
4.3.1.13	Geo-location capability	The device has no geo-location capability.	N/A

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

This report is issued as a supplementary report to original ICC report no. ER841101AD. The difference is concerned with following items:

- ✧ Updating standard version from V2.1.1 to V2.2.2.
- ✧ New applicant name.

Therefore, related test items had been performed and presented in the following sections.

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
Laird	SU60-SOMC (453-00003)	802.11ac Professional Wi-Fi + BT5.0 Module	2G/1G MCP
	SU60-SOMC-2G (453-00004)		4G/2G MCP
✦ The above models, both options were assessed and SU60-SOMC-2G (453-00004) was found to be worst case and was selected for the final testing.			

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	3 Mbps
Note 1: Bluetooth BR uses a GFSK modulation.				
Note 2: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK modulation.				

1.1.3 Antenna Details

No.	Brand	Model	Type	Connector	Gain (dBi)
1	LSR	001-0009	Dipole	IPEX U.FL	2
2	Laird	NanoBlade-IP04	PCB Dipole	IPEX U.FL	2
3	Laird	MAF95310 Mini NanoBlade Flex	PCB Dipole	IPEX U.FL	2.79
4	LSR	FlexPIFA 001-0016	PIFA	IPEX U.FL	2.5
5	Ethertronics	WLAN_1000146	Magnetic Dipole	IPEX U.FL	2.5
6	Laird	MIMO FlexPIFA Antenna	PIFA	IPEX U.FL	2
7	LSR	001-0009 (with filter)	Dipole	IPEX U.FL	2

1.1.4 EUT Operational Condition

Power Supply Type	3.3 Vdc from host		
SW Version	6.0.0.x		
Operational Climatic	☒ Tnom (20°C)	☒ Tmax (85°C)	☒ Tmin (-30°C)

1.1.5 Accessories

Accessories		
No.	Equipment	Description
1	AC Adapter	Brand Name: I.T.E POWER SUPPLY Model Name: MU12AY120100-A1 Power Rating: I/P: 100-240Vac, 50/60Hz, 0.3A O/P: 12Vdc, 1A Power Line: 1.48m non-shielded cable without core

1.1.6 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	--	--

1.1.7 Test Tool and Duty Cycle

Test Tool	Test Command	
Modulation Mode	Duty Cycle Of Test Signal (%)	Duty Factor (dB)
BR-1Mbps	72.27%	1.41
EDR-3Mbps	78.47%	1.05

1.1.8 Power Setting


Modulation Mode	Test Frequency (MHz)
	hopping
BR-1Mbps	Default
EDR-3Mbps	Default


1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	S/N	Remarks
1	Notebook	DELL	Latitude E6430	F2JB4X1	---
2	Notebook	DELL	Latitude E6430	D3LNYW1	---
3	Fixture	---	---	---	Provided by applicant.

Note: Fixture is provided by applicant.

1.3 Test Setup Chart

Test Setup Diagram (Conducted)	
	
No.	Signal cable / Length (m)
1	USB, 1m shielded.

Test Setup Diagram (Radiated)	
	
No.	Signal cable / Length (m)
1	USB, 1m shielded.

1.4 Test Equipment List and Calibration Data

For original test

Test Item	Radiated Emissions				
Test Site	Fully-anechoic chamber 2 / (05CH02-WS)				
Tested Date	Sep. 19, 2018				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	Agilent	N9010A	MY52221474	Oct. 16, 2017	Oct. 15, 2018
Bilog Antenna 30-1000MHz	SCHWARZBECK	VULB9168	9168-563	Jan. 02, 2018	Jan. 01, 2019
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	9120D-1205	Jan. 11, 2018	Jan. 10, 2019
Preamplifier	Agilent	83017A	MY53270013	Dec. 26, 2017	Dec. 25, 2018
Preamplifier	EMC	EMC02325	980188	Dec. 12, 2017	Dec. 11, 2018
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22622/4	Dec. 05, 2017	Dec. 04, 2018
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22623/4	Dec. 05, 2017	Dec. 04, 2018
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22621/4	Dec. 05, 2017	Dec. 04, 2018
RF cable-4M	HUBER+SUHNER	SUCOFLEX104	MY22579/4	Dec. 05, 2017	Dec. 04, 2018
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-002	Dec. 05, 2017	Dec. 04, 2018
LF cable-3M	EMC	EMC8D-NM-NM-3000	131102	Dec. 05, 2017	Dec. 04, 2018
LF cable-10M	EMC	EMC8D-NM-NM-10000	131101	Dec. 05, 2017	Dec. 04, 2018
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Oct. 04, 2018				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101486	Nov. 21, 2017	Nov. 20, 2018
Power Sensor	Agilent	U2021XA	MY53480019	Jan. 29, 2018	Jan. 28, 2019
Power Sensor	Agilent	U2021XA	MY53510003	Jan. 29, 2018	Jan. 28, 2019
Power Sensor	Agilent	U2021XA	MY54070003	Feb. 08, 2018	Feb. 07, 2019
Power Sensor	Agilent	U2021XA	MY54060013	Feb. 08, 2018	Feb. 07, 2019
AC POWER SOURCE	APC	AFC-500W	F312060012	Dec. 01, 2017	Nov. 30, 2018
Combiner(1X2)	woken	0120A02201801O	DOM2AEW1A23	Dec. 04, 2017	Dec. 03, 2018
Combiner(1X4)	woken	0120A04056002D	111204	Dec. 04, 2017	Dec. 03, 2018
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Measurement Software	Agilent	EN RF test	1.1501125	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Adaptivity				
Test Site	(TH01-WS)				
Tested Date	Sep. 26, 2018				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV-7	101607	Dec. 14, 2017	Dec. 13, 2018
Signal Generator	R&S	SMB 100A	175727	Oct. 26, 2017	Oct. 25, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX_104	MY15686/4	Nov. 24, 2017	Nov. 23, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX_104	296081/4	Dec. 07, 2017	Dec. 06, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX_104	329023/4	Dec. 07, 2017	Dec. 06, 2018
RF Cable	HUBER+SUHNER	SUCOFLEX_104	329021/4	Dec. 07, 2017	Dec. 06, 2018
Vector signal generator	Agilent	N5182B	MY53051912	Apr. 16, 2018	Apr. 15, 2019
Preamplifier	Burgeon	BPA-530	100219	Nov. 08, 2017	Nov. 07, 2018
Oscilloscope	National Instruments	USB-5133	F651FF	Jun. 19, 2018	Jun. 18, 2019
Measurement Software	Sporton	Sporton-3	2.2.0.0	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

For new test

Test Item	Receiver Blocking				
Test Site	(05CH01-WS)				
Tested Date	Apr. 15, 2020				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Wireless connectivity tester	ROHDE&SCHWARZ	CMW270	100856	Oct. 24, 2019	Oct. 23, 2020
Signal Generator	ROHDE&SCHWARZ	SMB100A	175727	Dec. 27, 2019	Dec. 26, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX_104	500202/4	Oct. 16, 2019	Oct. 15, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX_104	296088/4	Oct. 16, 2019	Oct. 15, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX_104	329023/4	Oct. 16, 2019	Oct. 15, 2020
Combiner(1X2)	WOKEN	2WAYDIV	12101200003	Oct. 16, 2019	Oct. 15, 2020
Note: Calibration Interval of instruments listed above is one year.					

1.5 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

EN 300 328 V2.2.2 (2019-07)

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty		
Parameters	Uncertainty	Limit
Occupied Channel Bandwidth	$\pm 0.0034 \%$	$\pm 5 \%$
RF output power, conducted	$\pm 0.537 \text{ dB}$	$\pm 1,5 \text{ dB}$
Power Spectral Density, conducted	$\pm 0.463 \text{ dB}$	$\pm 3 \text{ dB}$
Unwanted Emissions, conducted	$\pm 2.505 \text{ dB}$	$\pm 3 \text{ dB}$
All emissions, radiated	$\pm 3.401 \text{ dB}$	$\pm 6 \text{ dB}$
Temperature	$\pm 0.6 \text{ }^{\circ}\text{C}$	$\pm 3 \text{ }^{\circ}\text{C}$
Supply voltages	$\pm 0.16 \%$	$\pm 3 \%$
Time	$\pm 0.1 \%$	$\pm 5 \%$

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
RF Conducted	TH01-WS	25°C / 65%	Ryan Lee Jack Li
Radiated Emission	05CH02-WS	24°C / 65%	Ryan Lee
Adaptivity	TH01-WS	23°C / 67%	Jack Li
Receiver Blocking	05CH01-WS	25°C / 65%	Nai Xu

2.2 Testing Facility

Test Laboratory	International Certification Corp.
Test Site	TH01-WS, 05CH01-WS
Address of Test Site (Kwei Shan)	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Test Site	05CH02-WS
Address of Test Site (Kwei Shan II)	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

2.3 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
RF Output Power	GFSK 8DPSK	Hopping Hopping	1 Mbps 3 Mbps	1, 2, 3, 4
Accumulated Transmit Time Minimum Frequency Occupation Hopping Sequence	GFSK 8DPSK	Hopping Hopping	1 Mbps 3 Mbps	2
Hopping Frequency Separation	GFSK 8DPSK	two-adjacent	1 Mbps 3 Mbps	2
Occupied Channel Bandwidth Adaptivity	GFSK 8DPSK	2402 / 2480 2402 / 2480	1 Mbps 3 Mbps	2
Transmitter unwanted emissions in the OOB domain	GFSK 8DPSK	Hopping Hopping	1 Mbps 3 Mbps	1, 2, 3, 4
Transmitter Spurious Emissions Receiver Spurious Emissions	GFSK 8DPSK	2402 / 2480 2402 / 2480	1 Mbps 3 Mbps	2
Receiver Blocking	GFSK	Hopping	1 Mbps	2

NOTE:

- The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** result was found as the worst case and was shown in this report.
- 4 types antenna are used for this device, highest gain antenna of each type is selected to perform test as below test configuration.
 Configuration 1 : Dipole antenna with 2 dBi gain
 Configuration 2 : PCB Dipole antenna with 2.79dBi gain
 Configuration 3 : PIFA antenna with 2.5dBi gain
 Configuration 4 : Magnetic Dipolewith 2.5dBi gain
- Two 50Ω terminators are connected to antenna port of EUT for radiated emission measurement.

3 Transmitter Test Results

3.1 RF Output Power


3.1.1 Limit of RF Output Power

The maximum RF output power shall be equal to or less than 20 dBm

3.1.2 Test Procedures

Reference to clause 5.4.2.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.1.3 Test Setup



3.1.4 Test Result of RF Output Power

Test Configuration 1

Condition	Modulation Mode	Freq. (MHz)	EIRP Power	Limit (dBm)
TnomVnom	BR-1Mbps	Hopping	11.26	20
TminVnom	BR-1Mbps	Hopping	11.71	20
TmaxVnom	BR-1Mbps	Hopping	10.82	20
TnomVnom	EDR-3Mbps	Hopping	8.16	20
TminVnom	EDR-3Mbps	Hopping	8.65	20
TmaxVnom	EDR-3Mbps	Hopping	7.56	20

Test Configuration 2

Condition	Modulation Mode	Freq. (MHz)	EIRP Power	Limit (dBm)
TnomVnom	BR-1Mbps	Hopping	12.05	20
TminVnom	BR-1Mbps	Hopping	12.50	20
TmaxVnom	BR-1Mbps	Hopping	11.61	20
TnomVnom	EDR-3Mbps	Hopping	8.95	20
TminVnom	EDR-3Mbps	Hopping	9.44	20
TmaxVnom	EDR-3Mbps	Hopping	8.35	20

Test Configuration 3

Condition	Modulation Mode	Freq. (MHz)	EIRP Power	Limit (dBm)
TnomVnom	BR-1Mbps	Hopping	11.76	20
TminVnom	BR-1Mbps	Hopping	12.21	20
TmaxVnom	BR-1Mbps	Hopping	11.32	20
TnomVnom	EDR-3Mbps	Hopping	8.66	20
TminVnom	EDR-3Mbps	Hopping	9.15	20
TmaxVnom	EDR-3Mbps	Hopping	8.06	20

Test Configuration 4

Condition	Modulation Mode	Freq. (MHz)	EIRP Power	Limit (dBm)
TnomVnom	BR-1Mbps	Hopping	11.76	20
TminVnom	BR-1Mbps	Hopping	12.21	20
TmaxVnom	BR-1Mbps	Hopping	11.32	20
TnomVnom	EDR-3Mbps	Hopping	8.66	20
TminVnom	EDR-3Mbps	Hopping	9.15	20
TmaxVnom	EDR-3Mbps	Hopping	8.06	20

3.2 Accumulated Transmit Time, Minimum Frequency Occupation and Hopping Sequence

3.2.1 Limit of Accumulated Transmit Time, Minimum Frequency Occupation and Hopping Sequence

Adaptive mode

Adaptive Frequency Hopping equipment shall be capable of operating over a minimum of 70 % of the band 2.4GHz to 2.4835GHz. The Accumulated Transmit Time on any hopping frequency shall not be greater than 400 ms within any observation period of 400 ms multiplied by the minimum number of hopping frequencies (N) that have to be used. In order for the equipment to comply with the Frequency Occupation requirement, it shall meet either of the following two options:

Option 1: Each hopping frequency of the hopping sequence shall be occupied at least once within a period not exceeding four times the product of the dwell time and the number of hopping frequencies in use.

Option 2: The occupation probability for each frequency shall be between $((1 / U) \times 25 \%)$ and 77 % where U is the number of hopping frequencies in use. The hopping sequence(s) shall contain at least N hopping frequencies at all times, where N is 15 or 15 divided by the minimum Hopping Frequency Separation in MHz, whichever is the greater.

Non-Adaptive mode

The Accumulated Transmit Time on any hopping frequency shall not be greater than 15 ms within any observation period of 15 ms multiplied by the minimum number of hopping frequencies (N) that have to be used. Non-adaptive medical devices requiring reverse compatibility with other medical devices placed on the market that are compliant with version 1.7.1 or earlier versions of ETSI EN 300 328, are allowed to have an operating mode in which the maximum Accumulated Transmit Time is 400 ms within any observation period of 400 ms multiplied by the minimum number of hopping frequencies (N) that have to be used, only when communicating to these legacy devices already placed on the market. In order for the equipment to comply with the Frequency Occupation requirement, it shall meet either of the following two options:


Option 1: Each hopping frequency of the hopping sequence shall be occupied at least once within a period not exceeding four times the product of the dwell time and the number of hopping frequencies in use.

Option 2: The occupation probability for each frequency shall be between $((1 / U) \times 25 \%)$ and 77 % where U is the number of hopping frequencies in use. The hopping sequence(s) shall contain at least N hopping frequencies where N is 15 or 15 divided by the minimum Hopping Frequency Separation in MHz, whichever is the greater.

3.2.2 Test Procedures

Reference to clause 5.4.4.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.2.3 Test Setup



3.2.4 Test Result of Accumulated Transmit Time, Minimum Frequency Occupation and Hopping Sequence

Test Configuration 2

Summary

Mode	Max-Dwell (s)
2.4-2.4835GHz	-
BT-BR(1Mbps)	154.33702m
BT-EDR(3Mbps)	154.28369m


Result

Mode	Result	Function	Hopping Ch	ATT Period (s)	ATT (s)	ATT Limit (s)	Dwell/Ch (s)	FO Period (s)	FO (Hop)	FO Limit (Hop)
BT-BR(1Mbps)	-	-	-	-	-	-	-	-	-	-
2441MHz_ TnomVnom	Pass	Non-AFH	79	1.185	11.576 m	15m	3.75m	1.185	4	1
2441MHz_ TnomVnom	Pass	AFH	20	8	154.33 702m	400m	7.5m	600m	4	1
BT-EDR(3Mbps)	-	-	-	-	-	-	-	-	-	-
2441MHz_ TnomVnom	Pass	Non-AFH	79	1.185	11.572 m	15m	3.75m	1.185	4	1
2441MHz_ TnomVnom	Pass	AFH	20	8	154.28 369m	400m	7.5m	600m	4	1

BT-BR(1Mbps)

ATT Non-AFH


2441MHz



BT-BR(1Mbps)

ATT AFH


2441MHz



BT-EDR(3Mbps)


ATT Non-AFH

2441MHz



BT-EDR(3Mbps)

2441MHz



ATT AFH

Test Configuration 2

Summary

Mode	Max-Hop No
2.4-2.4835GHz	-
BT-BR(1Mbps)	79
BT-EDR(3Mbps)	79

Result

Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2441MHz_TnomVnom	Pass	79	15
BT-EDR(3Mbps)	-	-	-
2441MHz_TnomVnom	Pass	79	15

3.3 Hopping Frequency Separation


3.3.1 Limit of Hopping Frequency Separation

For adaptive Frequency Hopping equipment, the minimum Hopping Frequency Separation shall be 100 kHz.
For non-adaptive Frequency Hopping equipment, the Hopping Frequency Separation shall be equal or greater than the Occupied Channel Bandwidth, with a minimum separation of 100 kHz.

3.3.2 Test Procedures

Reference to clause 5.4.5.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.3.3 Test Setup



3.3.4 Test Result of Hopping Frequency Separation

Test Configuration 2

Summary

Mode	Max-Space (Hz)	Min-Space (Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	996k	996k
BT-EDR(3Mbps)	816k	816k


Result

Mode	Result	FI (Hz)	Fh (Hz)	Ch.Space (Hz)	Limit (Hz)
BT-BR(1Mbps)	-	-	-	-	-
2441MHz_TnomVnom	Pass	2.440992G	2.441988G	996k	100k
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz_TnomVnom	Pass	2.441167G	2.441983G	816k	100k

BT-BR(1Mbps)

Channel Separation

2.441G/2.442GHz



BT-EDR(3Mbps)

Channel Separation

2.441G/2.442GHz



3.4 Occupied Channel Bandwidth


3.4.1 Limit of Occupied Channel Bandwidth

The Occupied Channel Bandwidth for each hopping frequency shall fall completely within 2.4~2.4835 GHz. For non-adaptive Frequency Hopping equipment with e.i.r.p greater than 10 dBm, the Occupied Channel Bandwidth for every occupied hopping frequency shall be equal to or less than the value declared by the supplier. This declared value shall not be greater than 5 MHz.

3.4.2 Test Procedures

Reference to clause 5.4.7.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.4.3 Test Setup



3.4.4 Test Result of Occupied Channel Bandwidth

Test Configuration 2

Summary

Mode	OBW (Hz)	ITU-Code
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	880.56k	881KF1D
BT-EDR(3Mbps)	1.198M	1M20G1D

OBW = 99% occupied bandwidth;

Result


Mode	Result	Limit (Hz)	fl-OBW (Hz)	fh-OBW (Hz)	OBW (Hz)	N dB (Hz)
BT-BR(1Mbps)	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.4-2.4835 G	2.401562G	2.402441G	878.561k	344k
2480MHz_TnomVnom	Pass	2.4-2.4835 G	2.479562G	2.480443G	880.56k	342k
BT-EDR(3Mbps)	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.4-2.4835 G	2.401405G	2.402603G	1.198M	1.037M
2480MHz_TnomVnom	Pass	2.4-2.4835 G	2.479405G	2.480602G	1.197M	1.04M

fl-OBW = fl lower edge 99% occupied bandwidth; **fh-OBW** = fh higher edge 99% occupied bandwidth; **OBW** = 99% occupied bandwidth;

N dB = 20dB down bandwidth;

3.5 Transmitter Unwanted Emissions in the Out-Of-Band Domain


3.5.1 Limit of Transmitter Unwanted Emissions in the Out-Of-Band Domain



3.5.2 Test Procedures

Reference to clause 5.4.8.2 of ETSI EN 300 328 V2.2.2 (2019-07).

3.5.3 Test Setup



3.5.4 Test Result of Transmitter Unwanted Emissions in the Out-Of-Band Domain

Test Configuration 1

Summary

Mode	EIRP-A (dBm)	Limit-A (dBm)	EIRP-B (dBm)	Limit-B (dBm)
2.4-2.4835GHz	-	-	-	-
BT-BR(1Mbps)	-40.66	-10	-41.91	-20
BT-EDR(3Mbps)	-33.82	-10	-41.07	-20

Result

Mode	Result	Freq (Hz)	EIRP (dBm)	Limit (dBm)	Freq (Hz)	EIRP (dBm)	Limit (dBm)
BT-BR(1Mbps)	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.3985G	-41.91	-20	2.3995G	-40.66	-10
2402MHz_TnomVnom	Pass	2.485G	-42.71	-20	2.484G	-43.95	-10
2480MHz_TnomVnom	Pass	2.3985G	-43.98	-20	2.3995G	-43.73	-10
2480MHz_TnomVnom	Pass	2.485G	-43.89	-20	2.484G	-43.04	-10
BT-EDR(3Mbps)	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.398302G	-41.07	-20	2.399302G	-33.82	-10
2402MHz_TnomVnom	Pass	2.485198G	-43.60	-20	2.484G	-43.43	-10
2480MHz_TnomVnom	Pass	2.398303G	-43.96	-20	2.399303G	-44.85	-10
2480MHz_TnomVnom	Pass	2.485394G	-42.64	-20	2.484G	-40.88	-10

BT-BR(1Mbps)

2402MHz_TnomVnom




BT-BR(1Mbps)

2480MHz_TnomVnom



BT-EDR(3Mbps)

2402MHz_TnomVnom



BT-EDR(3Mbps)

2480MHz_TnomVnom

Mask



Test Configuration 2

Summary


Mode	EIRP-A (dBm)	Limit-A (dBm)	EIRP-B (dBm)	Limit-B (dBm)
2.4-2.4835GHz	-	-	-	-
BT-BR(1Mbps)	-38.35	-10	-41.58	-20
BT-EDR(3Mbps)	-34.11	-10	-39.01	-20

Result


Mode	Result	Freq (Hz)	EIRP (dBm)	Limit (dBm)	Freq (Hz)	EIRP (dBm)	Limit (dBm)
BT-BR(1Mbps)	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.3985G	-41.58	-20	2.3995G	-38.35	-10
2402MHz_TnomVnom	Pass	2.485G	-42.35	-20	2.484G	-41.75	-10
2480MHz_TnomVnom	Pass	2.3985G	-42.79	-20	2.3995G	-43.64	-10
2480MHz_TnomVnom	Pass	2.485G	-42.74	-20	2.484G	-40.80	-10
BT-EDR(3Mbps)	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.398302G	-39.01	-20	2.3995G	-34.11	-10
2402MHz_TnomVnom	Pass	2.485396G	-43.54	-20	2.484198G	-43.89	-10
2480MHz_TnomVnom	Pass	2.398302G	-43.35	-20	2.3995G	-42.93	-10
2480MHz_TnomVnom	Pass	2.485396G	-42.63	-20	2.484G	-41.57	-10

BT-BR(1Mbps)

2402MHz_TnomVnom




Mask




Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)
2.3985G	-41.58	-20	2.3995G	-38.35	-10	2.484G	-41.75	-10	2.485G	-42.35	-20

BT-BR(1Mbps)

2480MHz_TnomVnom




Mask




Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)
2.3985G	-42.79	-20	2.3995G	-43.64	-10	2.484G	-40.80	-10	2.485G	-42.74	-20

BT-EDR(3Mbps)

2402MHz_TnomVnom




Mask



Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)
2.398302G	-39.01	-20	2.3995G	-34.11	-10	2.484198G	-43.89	-10	2.485396G	-43.54	-20

BT-EDR(3Mbps)

2480MHz_TnomVnom



Mask

Limit
EIRP
Port 1

Limit
EIRP
Port 1

Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)	Freq(Hz)	EIRP(dBm)	Limit(dBm)
2.398302G	-43.35	-20	2.3995G	-42.93	-10	2.484G	-41.57	-10	2.485396G	-42.63	-20

Test Configuration 3

Summary

Mode	EIRP-A (dBm)	Limit-A (dBm)	EIRP-B (dBm)	Limit-B (dBm)
2.4-2.4835GHz	-	-	-	-
BT-BR(1Mbps)	-41.32	-10	-41.61	-20
BT-EDR(3Mbps)	-34.47	-10	-39.98	-20

Result

Mode	Result	Freq (Hz)	EIRP (dBm)	Limit (dBm)	Freq (Hz)	EIRP (dBm)	Limit (dBm)
BT-BR(1Mbps)	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.3985G	-42.59	-20	2.3995G	-41.32	-10
2402MHz_TnomVnom	Pass	2.485G	-41.61	-20	2.484G	-43.22	-10
2480MHz_TnomVnom	Pass	2.3985G	-43.97	-20	2.3995G	-42.68	-10
2480MHz_TnomVnom	Pass	2.485G	-42.51	-20	2.484G	-41.88	-10
BT-EDR(3Mbps)	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.398104G	-39.98	-20	2.3995G	-34.47	-10
2402MHz_TnomVnom	Pass	2.485198G	-43.14	-20	2.484G	-41.28	-10
2480MHz_TnomVnom	Pass	2.398302G	-43.75	-20	2.399302G	-43.25	-10
2480MHz_TnomVnom	Pass	2.485396G	-43.30	-20	2.484198G	-42.14	-10

BT-BR(1Mbps)

2402MHz_TnomVnom




BT-BR(1Mbps)

2480MHz_TnomVnom



BT-EDR(3Mbps)

2402MHz_TnomVnom



BT-EDR(3Mbps)

2480MHz_TnomVnom



Test Configuration 4

Summary

Mode	EIRP-A (dBm)	Limit-A (dBm)	EIRP-B (dBm)	Limit-B (dBm)
2.4-2.4835GHz	-	-	-	-
BT-BR(1Mbps)	-40.56	-10	-39.8	-20
BT-EDR(3Mbps)	-34.17	-10	-40.08	-20

Result

Mode	Result	Freq (Hz)	EIRP (dBm)	Limit (dBm)	Freq (Hz)	EIRP (dBm)	Limit (dBm)
BT-BR(1Mbps)	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.3985G	-40.40	-20	2.3995G	-40.56	-10
2402MHz_TnomVnom	Pass	2.485G	-42.93	-20	2.484G	-43.79	-10
2480MHz_TnomVnom	Pass	2.3985G	-43.92	-20	2.3995G	-42.19	-10
2480MHz_TnomVnom	Pass	2.485G	-39.80	-20	2.484G	-40.62	-10
BT-EDR(3Mbps)	-	-	-	-	-	-	-
2402MHz_TnomVnom	Pass	2.398302G	-40.08	-20	2.3995G	-34.17	-10
2402MHz_TnomVnom	Pass	2.485198G	-42.13	-20	2.484198G	-43.25	-10
2480MHz_TnomVnom	Pass	2.398104G	-42.85	-20	2.3995G	-43.14	-10
2480MHz_TnomVnom	Pass	2.485396G	-42.52	-20	2.484G	-41.38	-10

BT-BR(1Mbps)

Mask

2402MHz_TnomVnom



BT-BR(1Mbps)

Mask


2480MHz_TnomVnom



BT-EDR(3Mbps)

Mask

2402MHz_TnomVnom



BT-EDR(3Mbps)

2480MHz_TnomVnom



3.6 Transmitter Unwanted Emissions in the Spurious Domain

3.6.1 Limit of Transmitter Unwanted Emissions in the Spurious Domain

Frequency Range (MHz)	Maximum power (dBm)	Bandwidth (kHz)
30 to 47	-36	100
47 to 74	-54	100
74 to 87,5	-36	100
87,5 to 118	-54	100
118 to 174	-36	100
174 to 230	-54	100
230 to 470	-36	100
470 to 694	-54	100
694 to 1000	-36	100
1000 to 12750	-30	1000


3.6.2 Test Procedures

Reference to clause 5.4.9.2 of ETSI EN 300 328 V2.2.2 (2019-07).


3.6.3 Test Setup

Radiated Emission


Below 1GHz




Above 1 GHz



Conducted Emission



3.6.4 Transmitter Conducted Unwanted Emissions (Below 1GHz)



Modulation	GFSK	Test Freq. (MHz)	2480
Level (dBm) </			

Modulation	8DPSK	Test Freq. (MHz)	2402
Level (dBm)			

Modulation	8DPSK	Test Freq. (MHz)	2480
<			


3.6.5 Transmitter Conducted Unwanted Emissions (Above 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
</			

Modulation	GFSK	Test Freq. (MHz)	2480

Modulation	8DPSK	Test Freq. (MHz)	2402
Level (dBm) <			

Modulation	8DPSK	Test Freq. (MHz)	2480
------------	-------	------------------	------



Freq.	Measured value	Limit	Margin	Factor	Reading
MHz	dBm	dBm	dB	dB	dBm
1 4959.79	-59.78	-30.00	-29.78	0.00	-59.78
2 7441.01	-61.23	-30.00	-31.23	0.00	-61.23

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal		
</			


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		
Level (dBm) <			

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		
Level (dBm) </			

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		
<			

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		
<			

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	500.45	-63.91	-54.00	-9.91	3.37	-67.28
2	600.36	-67.64	-54.00	-13.64	5.72	-73.36
3	663.07	-66.65	-54.00	-12.65	6.26	-72.91


Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		
Level (dBm)			

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		

Level (dBm)



Frequency (MHz)

	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	500.45	-63.57	-54.00	-9.57	3.37	-66.94
2	588.77	-68.00	-54.00	-14.00	5.46	-73.46
3	644.98	-67.61	-54.00	-13.61	5.96	-73.57

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal		

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		

Level (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		
</			

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		




	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4960.85	-52.18	-30.00	-22.18	12.94	-65.12
2	7440.66	-49.04	-30.00	-19.04	17.00	-66.04

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		
<			

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		




	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.92	-53.33	-30.00	-23.33	12.66	-65.99
2	7206.49	-50.22	-30.00	-20.22	16.74	-66.96

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		




	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4960.20	-53.76	-30.00	-23.76	12.60	-66.36
2	7440.72	-48.81	-30.00	-18.81	17.28	-66.09

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4960.18	-53.32	-30.00	-23.32	12.93	-66.25
2	7440.20	-48.86	-30.00	-18.86	17.00	-65.86

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4 Receiver Test Results

4.1 Receiver Spurious Emissions

4.1.1 Limit of Receiver Spurious Emissions

Frequency Range	Maximum power (dBm)	Measurement bandwidth(kHz)
30 MHz to 1 GHz	-57	100
Above 1 GHz to 12,75 GHz	-47	1000


4.1.2 Test Procedures

Reference to clause 5.4.10.2 of ETSI EN 300 328 V2.2.2 (2019-07).


4.1.3 Test Setup

Radiated Emission


Below 1GHz



Above 1 GHz



Conducted Emission



4.1.4 Receiver Conducted Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402

Modulation	GFSK	Test Freq. (MHz)	2480

Modulation	8DPSK	Test Freq. (MHz)	2402

Modulation	8DPSK	Test Freq. (MHz)	2480

4.1.5 Receiver Conducted Unwanted Emissions (Above 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
Level (dBm)			

Modulation	GFSK	Test Freq. (MHz)	2480
Level (dBm) </			


Modulation	8DPSK	Test Freq. (MHz)	2402
Level (dBm) </			

Modulation	8DPSK	Test Freq. (MHz)	2480
Level (dBm)			

4.1.6 Receiver Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal		
<			

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	35.82	-63.88	-57.00	-6.88	-1.67	-62.21
2	375.32	-62.66	-57.00	-5.66	0.73	-63.39
3	500.45	-63.59	-57.00	-6.59	3.37	-66.96

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		


	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	375.32	-60.26	-57.00	-3.26	0.06	-60.32
2	500.45	-60.67	-57.00	-3.67	3.46	-64.13
3	874.87	-60.74	-57.00	-3.74	9.63	-70.37

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		
<			

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		




	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	35.82	-61.48	-57.00	-4.48	-1.67	-59.81
2	375.32	-62.46	-57.00	-5.46	0.73	-63.19
3	500.45	-63.64	-57.00	-6.64	3.37	-67.01

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	35.82	-62.25	-57.00	-5.25	-1.67	-60.58
2	375.32	-62.14	-57.00	-5.14	0.73	-62.87
3	500.45	-63.68	-57.00	-6.68	3.37	-67.05

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

4.1.7 Receiver Radiated Unwanted Emissions (Above 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal		

The spectrum plot displays Level (dBm) on the y-axis (ranging from -107 to -10) and Frequency (MHz) on the x-axis (ranging from 1000 to 12750). A red horizontal line at -50 dBm is labeled '300-328 RX'. A blue vertical line is positioned at 4804.02 MHz, with a small blue arrow pointing upwards at the intersection.

	Freq.	Measured value	Limit	Margin	Factor	Reading
	MHz	dBm	dBm	dB	dB	dBm
1	4804.02	-54.06	-47.00	-7.06	12.67	-66.73

Note 1: Measured Value (dBm) = Reading (dBm) + Factor (dB)

Note 2: Margin (dB) = Measured Value (dBm) – Limit (dBm)

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		

Level (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		

Level (dBm)

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		

Level (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Horizontal		

Level (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		

Level (dBm)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		

Level (dBm)

<

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		

Level (dBm)

5 Adaptivity Test Results

5.1 Adaptivity and Unwanted Signal Parameters

5.1.1 Limit of Adaptivity and Unwanted Signal Parameters


Adaptivity and Unwanted Signal Limit	
☒	Only for adaptive systems and RF Output Power > 10 dBm
☐	Non-LBT based Detect and Avoid: • minimum remain unavailable = 1sec; • minimum Idle Period time = 100us; • maximum Channel Occupancy Time (COT) = 40ms • detection threshold level = $-70 \text{ dBm/MHz} + 10 \times \log_{10}(100\text{mW} / P_{\text{out}})$ (P_{out} in mW e.i.r.p);
☐	LBT based Detect and Avoid (Frame Based Equipment): • minimum Clear Channel Assessment (CCA) time = 18 us; • COT = 1 ms to 10 ms • Idle Period = 5% of COT • detection threshold level = $-70 \text{ dBm/MHz} + 10 \times \log_{10}(100\text{mW} / P_{\text{out}})$ (P_{out} in mW e.i.r.p);
☒	LBT based Detect and Avoid (Load Based Equipment with spectrum sharing mechanism IEEE Std.): • LBT based spectrum sharing mechanism may implement IEEE 802.11™-2012 [i.3] clause 9, clause 10, clause 16, clause 17, clause 19 and clause 20, or in IEEE 802.15.4™-2011 [i.4], clause 4, clause 5 and clause 8 • detection threshold level = $-70 \text{ dBm/MHz} + 10 \times \log_{10}(100\text{mW} / P_{\text{out}})$ (P_{out} in mW e.i.r.p);
☒	Short Control Signalling Transmissions: • Short Control Signalling Transmissions shall have a maximum duty cycle of 10 % within an observation period of 50 ms.

Unwanted Signal Parameters				
Equipment Type	Wanted Signal Mean Power from Companion Device	Blocking Signal Frequency (MHz)	Blocking Signal Mean power (dBm)	Type of Interfering Signal
LBT	sufficient to maintain the link (see note 2)	2395 or 2488,5 (see note 1)	-35 (see note 3)	CW
Non-LBT	-30 dBm			
Note 1: The highest frequency shall be used for testing operating channels within the range 2 400 MHz to 2 442 MHz, while the lowest frequency shall be used for testing operating channels within the range 2 442 MHz to 2 483,5 MHz. Note 2: A typical value which can be used in most cases is -50 dBm/MHz. Note 3: The level specified is the level in front of the UUT antenna. In case of conducted measurements, this level has to be corrected by the actual antenna assembly gain.				

5.1.2 Test Procedures

Reference to clause 5.4.6.2 of ETSI EN 300 328 V2.2.2 (2019-07).


5.1.3 Test Setup




5.1.4 Test Result of Adaptivity 、Unwanted Signal and Short Control Signalling Transmissions

Adaptivity and Unwanted Signal Result						
EUT firmware / software version			6.0.0.x			
Adaptivity Detection Threshold Level (dBm)			-59.71			
Unwanted Signal Level (dBm)			-32.21			
Modulation Mode	Freq. (MHz)	Short Control Signalling Transmissions (ms)	Channel Occupancy Time (ms)	Idle Period Time (μs)	Adaptivity	Unwanted Signal Test Status
GFSK/8DPSK	2402	0.122	0.386	865	Pass	Pass
GFSK/8DPSK	2480	0	0.388	865		
Limit		< 5 ms	< 13 ms	>18μs		
Result		Complied				

5.1.5 Test Result of Adaptivity and Unwanted Signal Plots



5.1.6 Test Result of Short Control Signalling Transmissions Plots




Note: Zoom TX is short control signalling transmission time.

Channel Occupancy Time

GFSK/8DPSK - 2402MHz


Max On Time



386us

GFSK/8DPSK - 2480MHz

Max On Time




388us

Idle Period Time

GFSK/8DPSK - 2402MHz


Min Off Time



865us

GFSK/8DPSK - 2480MHz

Min Off Time



865us

6 Receiver Blocking Test Results

6.1 Receiver Blocking

6.1.1 Limit of Receiver Blocking

Receiver Blocking Parameters for Receiver Category 1 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm) (see notes 1 and 4)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (see note 4)	Type of Blocking Signal
(-133 dBm + 10 × log10(OCBW)) or -68 dBm whichever is less (see note 2)	2 380	-34	CW
	2 504		
(-139 dBm + 10 × log10(OCBW)) or -74 dBm whichever is less (see note 3)	2 300		
	2 330		
	2 360		
	2 524		
	2 584		
	2 674		
Note 1: OCBW is in Hz. Note 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P_{min} + 26 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal. Note 3: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to P_{min} + 20 dB where P_{min} is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal. Note 4: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned.			


Receiver Blocking Parameters for Receiver Category 2 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm) (see notes 1 and 3)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (see note 3)	Type of Blocking Signal
$(-139 \text{ dBm} + 10 \times \log_{10}(\text{OCBW}) + 10 \text{ dB})$ or $(-74 \text{ dBm} + 10 \text{ dB})$ whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW
Note 1: OCBW is in Hz. Note 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to $P_{\min} + 26 \text{ dB}$ where $P_{\min}$ is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal. Note 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned.			

Receiver Blocking Parameters for Receiver Category 3 Equipment Limit			
Wanted Signal Mean Power from Companion Device (dBm) (see notes 1 and 3)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm) (see note 3)	Type of Blocking Signal
$(-139 \text{ dBm} + 10 \times \log_{10}(\text{OCBW}) + 20 \text{ dB})$ or $(-74 \text{ dBm} + 20 \text{ dB})$ whichever is less	2 380 2 504 2 300 2 584	-34	CW
Note 1: OCBW is in Hz. Note 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative the test may be performed using a wanted signal up to $P_{\min} + 30 \text{ dB}$ where $P_{\min}$ is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal. Note 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned.			

6.1.2 Test Procedures

Reference to clause 5.4.11.2 of ETSI EN 300 328 V2.2.2 (2019-07).

6.1.3 Test Setup



6.1.4 Test Result of Receiver Blocking

Hopping mode

CMW 270 V 3.7.10 - Bluetooth Signaling V3.7.10 - RX Measurement

BER BER Search

Bit Errors

BER [%] 0.02963

Bit Errors 64

NAK

NAK Rate [%] 25.40

Packet Errors

PER [%] 23.49

Missing Packets Rate [%] 23.26

HEC Error Rate [%] 0.00

CRC Error Rate [%] 0.00

Wrong Packet Type [%] 0.00

Wrong Payload Length [%] 0.23

Packets Received

1000 / 1000

Packets to be received by CMW 1000

Payload bits to be received 216000

General Setup

Operating Mode RF Test

Burst Type Basic Rate

Test Mode Loopback Test

RF Setup

Rx (EUT) 78 Tx (EUT) 0

Frequency 2480.0 MHz 2402.0 MHz

Hopping ☒

Tx Level (CMW) -96.00 dBm

Exp. Nom. Power 10.00 dBm

Auto Ranging ☐

Dirty Tx ☒

Signal Characteristics

Packet Type DH1

Payload Length 27 byte(s)

Pattern Type PRBS9

Whitening ☐

CMW (Master) Signaling

CONNECTED TESTMODE

EUT for Paging C0EE405014A7

Repetition ...

Packets...

Bluetooth

Rx Quality

RDY

RF Settings

Dirty Tx

Bluetooth Signaling



ON

Config ...


Receiver Category	1		
Performance Criteria Limit	PER ≤ 10 %		
Wanted Signal Mean Power from Companion Device (dBm)	Blocking Signal Frequency (MHz)	Blocking Signal Power (dBm)	Test Result
-70.77	2380	-31.21	Pass
-70.77	2504	-31.21	Pass
-76.77	2300	-31.21	Pass
-76.77	2330	-31.21	Pass
-76.77	2360	-31.21	Pass
-76.77	2524	-31.21	Pass
-76.77	2584	-31.21	Pass
-76.77	2674	-31.21	Pass

7 Photographs of the Test Configuration


Radiated Spurious Emission Test



Conducted Spurious Emission Test



Receiver Blocking Test



Adaptivity, Unwanted Signal and Short Control Signalling Transmissions Test



8 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==