



2.4-2.5 and 4.9-5.9 GHz, 3.5 dBi CEILING GRID MOUNTED OMNI

The S24493TS is a dual-band three-element omni-directional antenna for use in 802.11n MIMO applications. Housed in a compact, low-profile PVC/acrylic radome, the antenna can be mounted to a variety of drop-ceiling grids using the integrated spring clips. It can also be mounted to a flush surface via the four mounting holes. Each of the three MIMO antenna elements is connected to the WLAN access point via a low loss, plenum-rated coax pigtail.

The radiation patterns are uniform and symmetrical, providing high level signal density into defined coverage zones. This antenna greatly enhances the performance of 802.11n systems. The dual band frequency coverage means that a single type of antenna can be deployed with any MIMO radio in the 2.4-2.5 GHz and 4.9-5.9 GHz bands. A wide choice of coax lengths and connector types are available.





FEATURES

- Vertically-polarized and omni-directional
- Compact, low-profile housing
- Wide choice of coax length and connector types
- 2.4-2.5 GHz and full wide-band 4.9-5.9 GHz performance
- RoHS-compliant

APPLICATIONS

- 802.11n MIMO
- Offices, hotels, and college campuses
- Airports and hospitals
- Offices, hotels, and college campuses
- Bus terminals and train stations
- Museums, libraries, and retail malls

SPECIFICATIONS	
Frequency Range	2.4-2.5 GHz and 4.9-5.9 GHz
Gain	3.0 dBi for 2.4-2.5 GHz nominal; 4.0 dBi for 4.9-5.9 GHz nominal
Maximum VSWR	2.0:1
2 dB Beamwidth- Elevation	60°
3 dB Beamwidth- Azimuth	Omnidirectional
Polarization	Vertical linear
Maximum Input Power	2 Watts
Mechanical Size (mm)	308.2 x 22 x 92
Weight	0.39 kg
Antenna Connection	Reverse SMA (3x)
Radome	ASA
Mount Style	Ceiling grid/suspended tile
All specifications subject to change without notice.	



Americas: +1.847.839.6925
 IAS-AmericasSales@lairdtech.com
 Europe: +44.1628.858941
 IAS-EUSales@lairdtech.com

Asia:
 IAS-AsiaSales@lairdtech.com

Middle East and Africa: +44.1628.858941
 IAS-MEASales@lairdtech.com
 www.lairdtech.com

ANT-DS-S24493TS 1117

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2017 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.