



Internal Wireless Device Antenna 2400-2500 MHz/4900-6000 MHz



The evolution of technology has brought the need to communicate everywhere and at all times without being confined to one space. Lairds' internal wireless device antennas feature wide bandwidth to enhance the performance and application of portable wireless devices based on standards such as 802.11 and Bluetooth®. The antennas are specifically designed to be embedded inside devices for aesthetically-pleasing integration with high durability.

FEATURES AND BENEFITS


- Covers 2.4 to 2.5 GHz for 802.11b and
 4.9 to 6 GHz for 802.11a, and all US, European, and Japanese WLAN applications
- Coaxial cable pigtail with various connector choices
- Omnidirectional patterns and all frequencies with increased gain in upper bands for optimal coverage
- Conformance to European RoHS Directive

SPECIFICATIONS				
Operating Frequency (MHz)	2400-2500	5150-5350	5600	
VSWR – Max	2:1			
Gain (dBi)	2	3.9	4	
Nominal Impedance (Ohms)		50		
Polarization	\	Vertical, Omnidirectional		
Dimensions – cm (in.)		5.08 x 1.65 (2.0 x 0.65)		
Material Substance Compliance		RoHS		


CONFIGURATION


MODEL NUMBER	PART NUMBER	CABLE LENGTH	CONNECTOR
NanoBlade – MMCX4	CAF94504	100 mm, RG-178	RA-MMCX
NanoBlade-IP04	CAF94505	100 mm, Ø 1.13 mm	IPEX MHF
NanoBlade-MMCX4	MAF95056	100 mm, RG-178	Flying lead
MAF95090	MAF95090	175 mm, Ø 1.13 mm	IPEX MHF

RADIATION PATTERNS



Americas: +1.847 839.6925 IAS-AmericasSales@lairdtech.com Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: IAS-AsiaSales@lairdtech.com Middle East and Africa: +44.1628.858941 IAS-MEAUSales@lairdtech.com www.lairdtech.com







Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations
Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force
for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5)
years from the original date of the end product purchase.



Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2018 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.